

## SafeSite®



- **Hazardous**
- UL 844 (CID2, CIII), CSA
- 7,200-7,500 lumens
- Up to 88 lm/W
- 120-277 VAC
- Up to 25' (7.5m) Mounting Height
- 5 year warranty

**Ratings:** IP66, IK07/IK10

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 7,200-7,500 lumens

**Operating temperature range of:** -40°F + 149°F  
(-40°C to +65°C)

## DuroSite®



- **Non-Hazardous**
- UL 1598/A, CSA
- 7,200-7,500 lumens
- Up to 88 lm/W
- 120-277 VAC
- Up to 25' (7.5m) Mounting Height
- 5 year warranty

**Ratings:** IP66, IK07/IK10

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 7,200-7,500 lumens

**Operating temperature range of:** -40°F + 149°F  
(-40°C to +65°C)

## Vigilant®



- **Non-Hazardous**
- UL 1598/A, CSA, CE, ENEC, RCM, NOM
- 2,800 – 9,000 lumens
- Up to 143 lm/W
- 100-277 VAC, 120-250 VDC
- Up to 30' (9m) Mounting Height
- 10 year warranty

**Ratings:** IP66/67/69, NEMA 4X, IK07/IK10

**Operating Voltage:** 100-277 VAC, 120-250 VDC

**Lumen Type:** 2,800 - 9,000 lumens

**Operating temperature range of:** -40°F + 149°F (-40°C to +65°C)

## SafeSite®



- **Hazardous**
- UL 844 (CID1, CID2, CII, CIII), CSA, IECEx/ATEX (Zone 1, 21, Zone 2, 22), INMETRO
- 2,800 – 9,000 lumens
- Up 143 lm/W
- 100-277 VAC, 120-250 VDC or 347-480 VAC or 24-48 VDC
- Up to 30' (9m) Mounting Height
- 10 year warranty (most models)

**Ratings:** IP66/67/69, NEMA 4X, IK07/IK10

**Operating Voltage:** 100-277 VAC, 120-250 VDC or 347-480 VAC or 24-48 VDC

**Lumen Type:** 2,800 - 9,000 lumens

**Operating temperature range of:** -40°F to +149°F (-40°C to +65°C)

DuroSite®



- Non-Hazardous
  - UL 1598/A, CSA
  - 2,200-7,200 lumens
  - Up to 111 lm/W
  - 347-480 VAC or 24-48 VDC
  - Up to 25' (7.5m) Mounting Height
  - 5 year warranty
- 

**Ratings:** IP66/67, NEMA 4X, IK07/IK10

**Operating Voltage:** 347-480 VAC or 24-48 VDC

**Lumen Type:** 2,200-7,200 lumens

**Operating temperature range of:** -40°F to +149°F (-40°C to +65°C)

## Vigilant®



- Non-Hazardous
  - UL 1598/A, CE, CSA, ENEC, RCM
  - 6,700-7,300 lumens
  - Up to 114 lm/W
  - 100-277 VAC, 120-250 VDC
  - 10' (3m) Mounting Height
  - 10 year warranty
- 

**Ratings:** IP66/67, NEMA 4X, IK07/IK10

**Operating Voltage:** 100-277 VAC, 120-250 VDC

**Lumen Type:** 6,700-7,300 lumens

**Operating temperature range of:** -40°F + 149°F  
(-40°C to +65°C)