

SafeSite®



- **Hazardous**
- UL 844 (CID2, CIID1, CIID2, CIII), CSA
- 10,000-15,000 lumens
- Up to 111 lm/W
- 100-277 VAC, 347/480 VAC
- Up to 40' (12m) Mounting Height
- 10 year warranty

Ratings: IK07/10

Operating Voltage: 100-277 VAC, 347-480 VAC

Lumen Type: 10,000-15,000 lumens

Operating temperature range of: -40°F + 149°F (-40°C to +65°C)

DuroSite®



- **Non-Hazardous**
- UL 1598/A, CE, RCM, CSA
- 10,000-15,000 lumens
- Up to 111 lm/W
- 100-277 VAC, 347/480 VAC
- Up to 40' (12m) Mounting Height
- 10 year warranty

Ratings: IP 66/67, IK07/10

Operating Voltage: 100-277 VAC, 347-480 VAC

Lumen Type: 10,000-15,000 lumens

Operating temperature range of: -40°F + 149°F (-40°C to +65°C)

Vigilant®



- Non-Hazardous
- UL 1598/A, CE, RCM, CSA
- 26,400-56,000 lumens
- Up to 149 lm/W
- 100-277 VAC, 120-250 VDC, 347/480 VAC
- Up to 80' (24m) Mounting Height
- 10 year warranty

Ratings: NEMA 4X, IK07

Operating Voltage: 100-277 VAC, 120-250 VDC, 347/480 VAC

Lumen Type: 26,400-56,000 lumens

Operating temperature range of: -40°F + 149°F (-40°C to +65°C)

SafeSite® IECEx/ATEX



- Hazardous
- IECEx/ATEX (Zone 1, 21, Zone 2, 22)
- 9,650-23,500 lumens
- Up to 111 lm/W
- 120-277 VAC
- Up to 60' (18m) Mounting Height
- 10 year warranty

Ratings: IP66

Operating Voltage: 100-277 VAC

Lumen Type: 9,650-23,500 lumens

Operating temperature range of: -40°F + 149°F (-40°C to +65°C)

SafeSite® UL



- Hazardous
- UL 844 (CID2), CSA
- 37,500-56,000 lumens
- Up to 145 lm/W
- 100-277 VAC, 120-250 VDC; 347/480 VAC
- Up to 80' (24m) Mounting Height
- 10 year warranty

Ratings: NEMA 4X, IK07

Operating Voltage: 100-277 VAC, 120-250 VDC;
347/480 VAC

Lumen Type: 37,500-56,000 lumens

Operating temperature range of: -40°F + 149°F (-40°C to
+65°C)

ProSite Floodlight



- **Non-Hazardous & Hazardous**
 - UL 1598/A, UL 844 (CID2, CIID1* – Pending, CIID2, CII), CE, ENEC, RCM, CSA
 - 12,000 – 65,000 lumens
 - Up to 165 lm/W
 - 120-277VAC / 120-250VDC 347-480 VAC
 - Up to 100' (30m) Mounting Height
 - 10 year warranty
-

Ratings: IK10 (integrated PC optic/lens/lens cover), IK08 (glass lens)

Operating Voltage: 120-277VAC / 120-250VDC 347-480 VAC

Lumen Type: 12,000 - 65,000 lumens

Operating temperature range of: -40°F + 149°F (-40°C to +65°C)