

## SafeSite®



- **Hazardous**
- UL 844 (CID2, CIID1, CIID2, CIII), CSA
- 7,000 lumens
- Up to 82 lm/W
- 120-277 VAC
- Up to 20' (6m) mounting height
- 5 year warranty (excluding batteries)

**Ratings:** IP66, NEMA 4X

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 7,000 Lumens

**Operating temperature range of:** -4°F to +149°F (-20°C to +65°C)

## DuroSite®



- **Non-Hazardous**
- UL 1598/A, UL 924, CSA
- 7,000 lumens
- Up to 82 lm/W
- 120-277 VAC
- Up to 20' (6m) mounting height
- 5 year warranty (excluding batteries)

**Ratings:** IP66, NEMA 4X

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 7,000 Lumens

**Operating temperature range of:** -4°F to +149°F (-20°C to +65°C)

SafeSite®



- Hazardous
- UL 1598/A, UL 844 (CID1, CID2), CSA
- 3,600-7,250 lumens
- Up to 106 lm/W
- 100-277 VAC, 347-480 VAC
- Up to 20' (6m) mounting height
- 5 year warranty (excluding batteries)

**Ratings:** IP66, NEMA 4X

**Operating Voltage:** 100-277 VAC, 347-480 VAC

**Lumen Type:** 3,600-7,250 lumens

**Operating temperature range of:** -4°F to +149°F (-20°C to +65°C)

## SafeSite®



- **Hazardous**
- UL 844 (CID2, CIID1, CIID2, CIII), CSA
- 3,500-7,500 lumens
- Up to 125 lm/W
- 120-277 VAC
- Up to 20' (6m) mounting height
- 5 year warranty

**Ratings:** IP66/67, NEMA 4X

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 3,500-7,500 lumens

**Operating temperature range of:** -40°F to +149°F  
(-40°C to +65°C)

## DuroSite®



- **Non-Hazardous**
- UL 1598/A, CE, CSA,  
NSF (available on select models)
- 3,500-7,500 lumens
- Up to 125 lm/W
- 120-277 VAC
- Up to 20' (6m) mounting height
- 5 year warranty

**Ratings:** IP66/67, NEMA 4X

**Operating Voltage:** 120-277 VAC

**Lumen Type:** 3,500-7,500 lumens

**Operating temperature range of:** -40°F to +149°F  
(-40°C to +65°C)

SafeSite®



- **Hazardous**
- IECEx/ATEX (Zone 1, 2, 21 & 22), CE, RCM, INMETRO
- Up to 2,785 & 5,750 (nominal) lumen outputs
- Up to 123 lm/W
- 100-277 VAC/120-250 VDC, 230/240 VAC or 110/120 VAC (emergency)
- DALI 1.0/2.0 standard
- 10 year warranty

**Ratings:** IP66/67

**Operating Voltage:** 100-277 VAC, 50/60Hz; 120-250 VDC; 230/240 VAC or 110/120 VAC (emergency)

**Lumen Type:** 2,785-5,750 lumens

**Operating temperature range of:** -40°C to +65°C; -20°C to +50°C

SafeSite®



- **Hazardous**
  - IECEx/ATEX (Zone 1 & 2, 21 & 22), INMETRO, RCM
  - 3,100-6,000 lumens
  - Up to 88 lm/W
  - 100-277 VAC
  - Up to 20' (6m) mounting height
  - 5 year warranty
- 

**Ratings:** IP66, NEMA 4X

**Operating Voltage:** 100-277 VAC

**Lumen Type:** 3,100-6,000 lumens

**Operating temperature range of:** -40°C to +65°C;  
-20°C to +50°C

## Vigilant®



- **Non-Hazardous**
- UL 1598/A, CSA, CE, ENEC, RCM
- 4,200-9,600 lumens
- Up to 139 lm/W
- 100-277 VAC / 120-250 VDC
- Up to 30' (9m) mounting height
- 10 year warranty

**Ratings:** IP66, IP67 (LP models only), NEMA 4X

**Operating Voltage:** 100-277 VAC / 120-250 VDC

**Lumen Type:** 4,200 - 9,600 lumens

**Operating temperature range of:** -40°F to +149°F (-40°C to +65°C)

## SafeSite®



- **Hazardous**
- UL 844 (CID2, CIID1, CIID2, CIII), CSA
- 3,300-9,600 lumens
- Up to 139 lm/W
- 100-277 VAC
- Up to 30' (9m) mounting height
- 5/10 year warranty

**Ratings:** IP66, IP67 (LP models only), NEMA 4X

**Operating Voltage:** 100-277 VAC (5 year) / 100-277 VAC / 120-250 VDC (10 year)

**Lumen Type:** 3,300-7,900 lumens (5 year) / 4,200-9,600 lumens (10 year)

**Operating temperature range of:** -40°F to +149°F (-40°C to +65°C)

## DuroSite®



- Non-Hazardous
- UL 1598/A, CE, CSA
- 3,300-7,900 lumens
- Up to 133 lm/W
- 100-277 VAC
- Up to 20' (6m) mounting height
- 5 year warranty

**Ratings:** IP66, IP67 (LP models only), NEMA 4X

**Operating Voltage:** 100-277 VAC

**Lumen Type:** 3,300-7,900 lumens

**Operating temperature range of:** -40°F to +149°F (-40°C to +65°C)

## SafeSite®



- **Hazardous**
- IECEx/ATEX (Zone 1, 21, Zone 2, 22), RCM
- 2,600-5,100 lumens
- Up to 76 lm/W
- 110-250 VAC, 230/240 VAC (emergency)
- Up to 20' (6m) mounting height
- 5 year warranty (excluding batteries)

**Ratings:** IP66/67

**Operating Voltage:** 110-250 VAC (standard), 230/240 VAC (emergency)

**Lumen Type:** 2,600-5,100 lumens

**Operating temperature range of:** -20°C to +60°C (-4°F to +140°F)

## DuroSite®



- **Non-Hazardous**
- CE, RCM
- 2,600-5,100 lumens
- Up to 76 lm/W
- 100-277 VAC, 230/240 VAC (emergency)
- Up to 20' (6m) mounting height
- 5 year warranty (excluding batteries)

**Ratings:** IP66/67

**Operating Voltage:** 100-277 VAC (Standard), 230/240 VAC (Emergency)

**Lumen Type:** 2,600-5,100 lumens

**Operating temperature range of:** -20°C to +60°C (-4°F to +140°F)