



# INSULATED CUTTING TOOLS

ES20HVX, ESC32HVX, ESC25HVX

**NEW**



ES20HVX



## ES20HVX – IN-LINE ACSR CUTTER

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ES20HVX11	783310040491	20 mm Cutter, (PVC) 120V Charger, Two 4.0Ah Batteries
<b>N</b> ES20HVX12	783310040507	20 mm Cutter, (PVC) 12V Charger, Two 4.0Ah Batteries
<b>N</b> ES20HVX22	783310040514	20 mm Cutter, (PVC) 230V Charger, Two 4.0Ah Batteries
<b>N B</b> ES20HVXB	783310040521	20 mm Cutter, (PVC) Bare Tool Only



ES32HVX

## ES32HVX – IN-LINE CABLE CUTTER

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ES32HVX11	783310038085	32 mm Cutter, (PVC) 120V Charger, Two 4.0Ah Batteries
<b>N</b> ES32HVX12	783310038092	32 mm Cutter, (PVC) 12V Charger, Two 4.0Ah Batteries
<b>N</b> ES32HVX22	783310038108	32 mm Cutter, (PVC) 230V Charger, Two 4.0Ah Batteries
<b>N B</b> ES32HVXB	783310038115	32 mm Cutter, (PVC) Bare Tool Only



ESC25HVX



## ESC25HVX – IN-LINE ACSR CUTTER

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ESC25HVX11	783310040538	25 mm Cutter, (PVC) 120V Charger, Two 4.0Ah Batteries
<b>N</b> ESC25HVX12	783310040545	25 mm Cutter, (PVC) 12V Charger, Two 4.0Ah Batteries
<b>N</b> ESC25HVX22	783310040552	25 mm Cutter, (PVC) 230V Charger, Two 4.0Ah Batteries
<b>N B</b> ESC25HVXB	783310040569	25 mm Cutter, (PVC) Bare Tool Only





# 6-TON IN-LINE

## EK425LX, EK628LX



EK425LX



EK628LX

- Intelli-CRIMP® technology notifies operator with a visual and audible alert in real time if crimp force is not achieved
- One trigger controls all tool functions
- Crimping head rotates 350°
- Patented spring pin jaw engagement
- LED work light illuminates dark work areas
- LED display with real time PSI reading
- Bluetooth® enabled
- EK628LX used with Greenlee 22 series dies – See page 262

### SPECIFICATIONS

Crimping Force	6-Ton (54kN)
Length	14-3/4" (375 mm) without head or battery
Width	4" (108 mm)
Weight	6.6 lb (3 kg)
Battery	18V 4.0Ah Li-ion (EK425) or 18V 2.0Ah Li-ion (EK628)

### CAPACITY (EK425LX)

5/8" Service Entrance Connectors	10-1/0 AWG
.840 Service Entrance Connectors	1/0-4/0 AWG
Aluminum "H" Taps	6-4/0 AWG
Copper "H" Taps	10-2 AWG
Copper Tension Splices	6-2/0 AWG
Aluminum Tension Splices	6-4/0 AWG
One Piece ACSR Tension Splices	4-1/0 AWG
Two Piece ACSR Tension Splices	2 AWG to 477 kcmil
Aluminum Jumper Splices	4 AWG to 266.8 kcmil
Stirrups	2-4/0 AWG
Aluminum Color-Coded Lugs and Splices	8-4/0 AWG

### CAPACITY (EK628LX)

Copper color-coded connectors	8 AWG to 600 kcmil
Aluminum color-coded connectors	8 AWG to 350 kcmil



## INTERCHANGEABLE JAWS FOR EK425 AND EK628

### CRIMPING JAWS



CJD30



CJD3BG



CJD3



CJK



CJXPJ

### CUTTING JAWS



CJB



CJ-CUAL



CJ-ACSR1

## 12-TON PISTOL EK1240LX, EK1240CLX, EK1250KLX



EK1240LX



EK1240CLX



EK1240KLX

- Intelli-CRIMP® technology notifies operator with a visual and audible alert in real time if crimp force is not achieved
- Automatic Retraction Stop (ARS) retracts the ram just enough to get ready for the next cycle saving time and energy
- One trigger controls all tool functions
- Crimping head rotates 350°
- EK1240L with 1.65" (42 mm) opening uses Greenlee KC12, KA12 & KD12 crimping dies plus all industry "U" style crimping dies, EK1240KL uses Kearney PH2 style crimping dies
- Covered head models have two layers of PVC that total approximately 3/16" (4.8 mm) thick

### SPECIFICATIONS

Crimping Force	12 Tons (106 kN)
Length	16-1/4" (80 mm)
Width	3-1/8" (413 mm)
Height	13-1/2" (343 mm)
Weight	15 lb (6.8 kg)
Capacity	8 AWG – 750 kcmil Cu & Al lugs and splices

CAT NO.	UPC NO.	DESCRIPTION
EK1240LX11	783310609834	12-Ton 42 mm Crimper, 120V Charger, Two 4.0Ah Batteries
EK1240LX12	783310609841	12-Ton 42 mm Crimper, 12V Charger, Two 4.0Ah Batteries
EK1240LX22	783310609858	12-Ton 42 mm Crimper, 230V Charger, Two 4.0Ah Batteries
<b>B</b> EK1240LXB	783310609889	12-Ton 42 mm Crimper, Bare Tool Only

### EK1240CLX – PVC BRUSH GUARD

CAT NO.	UPC NO.	DESCRIPTION
EK1240CLX11	783310610342	12-Ton 42 mm Crimper, 120V Charger, Two 4.0 Ah Batteries
EK1240CLX12	783310610359	12-Ton 42 mm Crimper, 12V Charger, Two 4.0 Ah Batteries
EK1240CLX22	783310610366	12-Ton 42 mm Crimper, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> EK1240CLXB	783310610397	12-Ton 42 mm Crimper, Bare Tool Only

### EK1240KLX – PVC BRUSH GUARD

CAT NO.	UPC NO.	DESCRIPTION
EK1240KLX11	783310610465	12-Ton 30 mm Crimper, 120V Charger, Two 4.0 Ah Batteries
EK1240KLX12	783310610472	12-Ton 30 mm Crimper, 12V Charger, Two 4.0 Ah Batteries
EK1240KLX22	783310610489	12-Ton 30 mm Crimper, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> EK1240KLXB	783310610519	12-Ton 30 mm Crimper, Bare Tool Only



### Crimping Dies for 12-Ton Tools

Crimping dies on page 263

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 05167	783310051671	18V 4.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap

**N** = NEW PRODUCT

**R** = REPLACEMENT PART

**A** = ACCESSORY

**B** = BARE TOOL

# 6-TON CRIMPING DIE COMPATIBILITY



FOR USE WITH:



EK622LX  
page 256



EK628LX  
page 254

FOR USE WITH:



EK425LX  
page 254



**\*NOTE:** Connections are UL and cUL classified for copper and aluminum, when used with Greenlee tools on Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts® and Penn-Union® Color-Coded Lugs and Splices.

## Crimping Dies for 6-Ton Tools

- All dies on this page for use with battery tool models: ECCXLX, EK628LX, EK622LX

### SPECIFICATIONS – 22 SERIES CRIMPING DIES

Cable Size	Aluminum		Copper	
	Catalog No.	Color	Catalog No.	Color
8 AWG	KA22-8	Blue	KC22-8	Red
6 AWG	KA22-6	Gray	KC22-6	Blue
4 AWG	KA22-4	Green	KC22-4	Gray
2 AWG	KA22-2	Pink	KC22-2	Brown
1 AWG	KA22-1	Gold	KC22-1	Green
1/0 AWG	KA22-1/0	Tan	KC22-1/0	Pink
2/0 AWG	KA22-2/0	Olive	KC22-2/0	Black
3/0 AWG	KA22-3/0	Ruby	KC22-3/0	Orange
4/0 AWG	KA22-4/0	White	KC22-4/0	Purple
250 KCMIL (MCM)	KA22-250	Red	KC22-250	Yellow
300 KCMIL (MCM)	KA22-300	Blue	KC22-300	White
350 KCMIL (MCM)	KA22-350	Brown	KC22-350	Red
400 KCMIL (MCM)	–	–	KC22-400	Blue
500 KCMIL (MCM)	–	–	KC22-500	Brown
600 KCMIL (MCM)	–	–	KC22-600	Green

**NOTE:** Dies for Crimping Color-Coded Copper & Aluminum Lugs & Splices\* (Require UA22 adapter when used with ECCXL, HCCX, & RCCX tools)

### “W”-STYLE DIES

Catalog No.	Burndy No.	Catalog No.	Burndy No.
KD6-10	W-BG	KD6-18	W-166
KD6-11	W-O	KD6-19	W-243
KD6-12	W-C	KD6-20	W-247
KD6-13	W-K840	KD6-21	W-249
KD6-14	W-161	KD6-22	W-164
KD6-15	W-162	KD6-24	W-237
KD6-16	W-163	KD6-25	W-239
KD6-17	W-165	KD6-27	W-28K

**NOTE:** Dies for use with service entrance connectors, c-taps, h-taps, overhead and underground connectors (Require UAW adapter when used with ECCXL tools, Requires CJD3, CJD3BG, or CJD30 jaws when used with EK628L tools)

CAT. NO.	UPC NO.	DESCRIPTION
K22S1GL	783310030782	Die Kit for 8 AWG to 600 kcmil Copper Connectors – Includes all copper die sets listed below and carrying case
KD06AL	783310016311	Die Kit for 8 AWG to 350 kcmil Aluminum Connectors – Includes all aluminum die sets listed below and carrying case

# 6- AND 12-TON CCX MULTI-TOOLS

## E12CCXLX, E6CCXLX



E12CCXLX



### Crimping Dies for 12-Ton Tools

Crimping dies on page 263



E6CCXLX



### Crimping Dies for 6-Ton Tools

Crimping dies on page 262

- Retraction Stop Repeat (RSR) allows the operator to partially retract the ram and then the tool repeats the retraction for subsequent crimps
- Use optional CCX blades and adapters (see page 263)

#### SPECIFICATIONS

<b>Crimping Force</b>	E12CCXLX – 24,000 lb (107kN) 12-Ton; E6CCXLX – 12,000 lb (53 kN) 6-Ton
<b>Length</b>	E12CCXLX – 16-1/2" (419 mm); E6CCXLX – 15-1/2" (394 mm)
<b>Weight</b>	E12CCXLX – 15 lb (6.8 kg); E6CCXLX – 14 lb (6.3 kg)
<b>Battery</b>	E12CCXLX – 18V 4.0Ah Li-ion; E6CCXLX – 18V 4.0Ah Li-ion

#### EC12CCXLX

CAT NO.	UPC NO.	DESCRIPTION
E12CCXLX11	783310611462	12-Ton, Multi-Tool, 120V Charger, Two 4.0 Ah Batteries
E12CCXLX12	783310611479	12-Ton, Multi-Tool, 12V Charger, Two 4.0 Ah Batteries
E12CCXLX22	783310611486	12-Ton, Multi-Tool, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> E12CCXLXB	783310611516	12-Ton, Multi-Tool, Bare Tool Only

#### E6CCXLX

CAT NO.	UPC NO.	DESCRIPTION
E6CCXLX11	783310611585	6-Ton, Multi-Tool, 120V Charger, Two 4.0 Ah Batteries
E6CCXLX12	783310611592	6-Ton, Multi-Tool, 12V Charger, Two 4.0 Ah Batteries
E6CCXLX22	783310611608	6-Ton, Multi-Tool, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> E6CCXLXB	783310611639	6-Ton, Multi-Tool, Bare Tool Only

#### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
05167	783310051671	18V 4.0Ah Li-ion Battery
52178	783310521785	120V Li-ion Battery Charger
52179	783310521792	230V Li-ion Battery Charger
52180	783310521808	12V Li-ion Battery Charger
12274	783310122746	Carrying Strap



## CCX TOOL ACCESSORIES

(OPTIONAL, ALL IN PAIRS EXCEPT PUNCH DRIVER)



UA22



UAK



UC40



UCUNC38



UA12P



UA12ID

### DIE ADAPTERS

CAT NO.	UPC NO.	DESCRIPTION	E6CCXLX	E12CCXLX
<b>A</b> UA22	783310070627	Adapter for Greenlee® K22 dies	X	-
<b>A</b> UAK	783310070337	Adapter for Kearney "O", Thomas & Betts® "6-Ton", and Blackburn® "OD" dies	X	-
<b>A</b> UAW	783310070351	Adapter for Burndy® "W" and Panduit® "CD-2001" dies (equivalent to "D3" die)	X	-
<b>A</b> UA12T	783310201588	Adapter for "U" dies (included with E12CCXL tool)	-	-

### CABLE CUTTING BLADES

CAT NO.	UPC NO.	DESCRIPTION	E6CCXLX	E12CCXLX
<b>A</b> UC26	783310067146	Cutter blades AL & CU 1" capacity	X	X
<b>A</b> UC40	783310070368	Cutter blades AL & CU 1-1/2" capacity	X	X
<b>A</b> UCACSR	783310070375	Cutter blades for ACSR & guy strand	X	X

### THREADED ROD CUTTING BLADES

CAT NO.	UPC NO.	DESCRIPTION	E6CCXLX	E12CCXLX
<b>A</b> UCUNC14	783310070382	Cutter blades for 1/4" threaded rod	X	X
<b>A</b> UCUNC38	783310070399	Cutter blades for 3/8" threaded rod	X	X
<b>A</b> UCUNC12	783310072744	Cutter blades for 1/2" threaded rod	X	X

### KNOCKOUT PUNCH ADAPTER

CAT NO.	UPC NO.	DESCRIPTION	E6CCXLX	E12CCXLX
<b>A</b> UA12P	783310118909	Punch Driver Adapter (accepts 3/4" draw stud)	X	X

### DIELESS CRIMP ADAPTER

CAT NO.	UPC NO.	DESCRIPTION	E6CCXLX	E12CCXLX
<b>A</b> UA12ID	783310008033	Dieless Crimp Adapter	-	X

## 6-TON IN-LINE INDENTER EK6IDLX, EK6IDCLX



**NEW**

- Two-stage telescopic ram design identifies correct pressure to apply
- Single trigger operation for controlling all tool functions
- PVC coated head for brush protection

### SPECIFICATIONS

Crimping Force	Variable 6-Ton (30-60kN)
Head Rotation	350°
Weight with Battery	5.5 lb (2.5 kg)
Height	15" (380 mm)
Capacity	Standard Strand Wire Classes – B; C Copper: #8 – 500 kcmil (MCM) Aluminum: 1/0 – 350 kcmil (MCM) Fine Strand – Copper Wire Classes – G; H; I; K; M: 1/0 – 350 kcmil (MCM) DLO – Copper Locomotive: #8 – 373.7 kcmil (MCM)

Please contact Greenlee Customer Service for specific wire class classification.

### EK6IDLX – FLIP TOP STYLE

CAT NO.	UPC NO.	DESCRIPTION
EK6IDLX11	783310610793	6-Ton, Dieless Crimper, 120V Charger, Two 2.0 Ah Batteries
EK6IDLX12	783310610984	6-Ton, Dieless Crimper, 12V Charger, Two 2.0 Ah Batteries
EK6IDLX22	783310610991	6-Ton, Dieless Crimper, 230V Charger, Two 2.0 Ah Batteries
<b>B</b> EK6IDLXB	783310610748	6-Ton, Dieless Crimper, Bare Tool Only

### EK6IDCLX – PVC COATED

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> EK6IDCLX11	783310080558	6-Ton, Dieless Crimper, 120V Charger, Two 4.0 Ah Batteries
<b>N</b> EK6IDCLX12	783310085959	6-Ton, Dieless Crimper, 12V Charger, Two 4.0 Ah Batteries
<b>N</b> EK6IDCLX22	783310085966	6-Ton, Dieless Crimper, 230V Charger, Two 4.0 Ah Batteries
<b>N B</b> EK6IDCLXB	783310080541	6-Ton, Dieless Crimper, Bare Tool Only



### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 05167	783310051671	18V 4.0Ah Li-ion Battery
<b>A</b> 52177	783310521778	18V 2.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap



**DIELESS**



# IN-LINE QUAD POINT INDENTER

## EK6ATILX & EK6FTILX

**NEW**



EK6ATILX



EK6FTILX

### SPECIFICATIONS

Crimping Force	12,400 lb (55 kN)
Height	19.5" (495 mm)
Weight	8.2 lb (3.75 kg)
Battery	18V 4.0Ah Li-ion
Head Rotation	360°

### CAPACITY

Open Face	Copper: 6 AWG – 500 kcmil
	Aluminum: 6 AWG – 400 kcmil
Flip-top	Copper: 6 AWG – 750 kcmil
	Aluminum: 6 AWG – 750 kcmil

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> EK6ATILX11	783310084686	6-Ton Quad Point Crimper, Open Face, 120V Charger, Two 4.0Ah Batteries
<b>N</b> EK6ATILX12	783310084693	6-Ton Quad Point Crimper, Open Face, 12V Charger, Two 4.0Ah Batteries
<b>N</b> EK6ATILX22	783310084709	6-Ton Quad Point Crimper, Open Face, 230V Charger, Two 4.0Ah Batteries
<b>N B</b> EK6ATILXB	783310085904	6-Ton Quad Point Crimper, Open Face, Bare Tool Only
<b>N</b> EK6FTILX11	783310085911	6-Ton Quad Point Crimper, Flip Top, 120V Charger, Two 4.0Ah Batteries
<b>N</b> EK6FTILX12	783310085928	6-Ton Quad Point Crimper, Flip Top, 12V Charger, Two 4.0Ah Batteries
<b>N</b> EK6FTILX22	783310085935	6-Ton Quad Point Crimper, Flip Top, 230V Charger, Two 4.0Ah Batteries
<b>N B</b> EK6FTILXB	783310085942	6-Ton Quad Point Crimper, Flip Top, Bare Tool Only

# 6-TON PISTOL

## EK6FTLX, EK6ATLX



EK6FTLX

### SPECIFICATIONS

Crimping Force	12,400 lb (55kN)
Length	EK6ATLX – 14" (355mm) EK6FTLX – 14-7/8" (378mm)
Weight	EK6ATLX – 12 lb (5.4kg) EK6FTLX – 11 lb (5kg)
Battery	18V 4.0Ah Li-ion

### CAPACITY

<b>EK6ATLX</b>	Copper: 6 AWG – 500 kcmil
	Aluminum: 6 AWG – 400 kcmil
<b>EK6FTLX</b>	Copper: 6 AWG – 750 kcmil
	Aluminum: 6 AWG – 750 kcmil

### EK6FTLX

CAT NO.	UPC NO.	DESCRIPTION
EK6FTLX11	783310611196	6 Ton Quad Point Crimper, Flip Top, 120V Charger, Two 4.0 Ah Batteries
EK6FTLX12	783310611202	6 Ton Quad Point Crimper, Flip Top, 12V Charger, Two 4.0 Ah Batteries
EK6FTLX22	783310611219	6 Ton Quad Point Crimper, Flip Top, 230V Charger, Two 4.0 Ah Batteries
EK6FTLXB	783310611240	6 Ton Quad Point Crimper, Flip Top, Bare Tool Only

### EK6ATLX

CAT NO.	UPC NO.	DESCRIPTION
EK6ATLX11	783310611073	6 Ton Quad Point Crimper, Open Face, 120V Charger, Two 4.0 Ah Batteries
EK6ATLX12	783310611080	6 Ton Quad Point Crimper, Open Face, 12V Charger, Two 4.0 Ah Batteries
EK6ATLX22	783310611097	6 Ton Quad Point Crimper, Open Face, 230V Charger, Two 4.0 Ah Batteries
EK6ATLXB	783310611127	6 Ton Quad Point Crimper, Bare Tool Only



EK6ATLX

# HIGH PRESSURE HOSES



NC-6-38MF  
NC-10-38MF  
NC-30-38MF

- Comes pre-charged in 6', 10', and 33' lengths
- Standard 3/8" NPT screw type male and female fittings installed
- High pressure – up to 10,000 PSI
- Certified non-conductive
- Double rubber cap comes standard to protect fittings while not in use

CAT NO.	UPC NO.	DESCRIPTION
NC-10-38MF	783310024101	Hose, HYD, 3/8 Male/Female (10')
NC-30-38MF	783310024118	Hose, HYDC, 3/8 Male/Female (10 m)
NC-6-38MF	783310024071	Hose, HYD, 3/8 Male/Female (6')

# 10,000 PSI HIGH PRESSURE COUPLERS



130868

130878

54169



F024631

F022061

F021627

CAT NO.	UPC NO.	DESCRIPTION
130868	783310406471	Coupler-Hyd Parker #3010-2-542 Male
130878	783310406525	Coupler-Hyd Female 1/4-19 NPSM
54169	783310541691	Coupler-Half 1/4" Male Nipple
F024631	783310420965	Coupler, Female 1/4"-18 NPTM
F022061	783310419419	Coupler-HYD, Male 3/8-18 NPTF
F021627	783310418771	Coupler, Female 3/8"-18 NPTM

## CRIMPING REMOTES



RK1550

### RK1550

#### SPECIFICATIONS

Crimping Force at 10,000 PSI (700 bar)	30,000 lb (133kN)
Length	15" (380 mm)
Width	3" (76 mm)
Height	5-3/8" (135 mm)
Weight	14.1 lb (6.4 kg)
Operating Pressure	10,000 PSI (700 bar)
Capacity	Copper Color-Coded Lugs and Splices: #8 to 1500 kcmil (MCM) Aluminum Color-Coded Lugs and Splices: #8 to 1000 kcmil (MCM)

CAT NO.	UPC NO.	DESCRIPTION
RK1550	783310053538	Remote Crimping Tool, 15-Ton Kearney Style

### RK1550FT



RK1550FT

#### SPECIFICATIONS

Crimping Force at 10,000 PSI (700 bar)	30,000 lb (135 kN)
Length	13.75" (349 mm)
Width	3" (76 mm)
Height	5" (127 mm)
Weight	11.4 lb (5.2 kg)
Operating Pressure	10,000 PSI (700 bar)
Capacity	Copper Color-Coded Lugs and Splices: #8 to 1500 kcmil (MCM) Color-Coded Lugs and Splices: #8 to 1250 kcmil (MCM)

CAT NO.	UPC NO.	DESCRIPTION
RK1550FT	783310005520	Remote Crimping Tool, 15-Ton, Flip-Top
UA15T	783310002604	Die Adapters – Greenlee® "U" style dies, Burndy® "U" style dies, ILSCO® ILD style dies, Thomas & Betts® 15500 style dies, Blackburn® 15500 style dies



# CRIMPING REMOTES

## RK1240, RK1240C



RK1240

### SPECIFICATIONS

<b>Crimping Force</b>	24,000 lb (106 kN)
<b>Length</b>	11-7/8" (302 mm)
<b>Weight</b>	RK1240 – 9.7 lb (4.4 kg)
<b>Operating Pressure</b>	10,000 PSI (700 bar)
<b>Capacity</b>	8 AWG – 750 kcmil Copper lugs and splices 8 AWG – 750 kcmil Aluminum lugs and splices



RK1240C



RK121D

## RK121D

### SPECIFICATIONS

<b>Crimping Force</b>	24,000 lb (106 kN)
<b>Length</b>	13" (330 mm)
<b>Width</b>	3.75" (95 mm)
<b>Weight</b>	9.75 lb (4.42 kg)
<b>Operating Pressure</b>	10,000 PSI (700 bar)
<b>Capacity</b>	4 AWG – 1000 kcmil copper lugs and splices 6 AWG – 1000 kcmil Aluminum lugs and splices

## RK6040



RK6040

### SPECIFICATIONS

<b>Crimping Force</b>	120,000 lb (530 kN)
<b>Length</b>	17" (432 mm)
<b>Width</b>	6" (153 mm)
<b>Weight</b>	45 lb (20 kg)
<b>Operating Pressure</b>	10,000 PSI (700 bar)
<b>Capacity</b>	Copper Stranded Code Cable 300 kcmil–2000 kcmil Aluminum Stranded Code Cable 250 kcmil–2000 kcmil Copper Tension Sleeves 1/0 AWG–1000 kcmil Aluminum Tension Sleeves 1/0 AWG–2300 kcmil ACSR Tension Sleeves 1/0 AWG–2156 (Bluebird) kcmil Copper Aerial Connectors 4/0 AWG–2500 kcmil Aluminum Aerial Connectors 3/0 AWG–2500 kcmil

CAT. NO.	UPC NO.	DESCRIPTION
RK1240	783310053514	Crimping Tool SA 12T 42 mm (RK1240)
RK1240C	783310072058	Crimping Tool Assembly, 42 mm-PVC COV
RK121D	783310015659	Crimping Tool, Dieless Remote
RK6040	783310106043	60-Ton Crimping Tool – Single Acting
A 54169	783310541691	Coupler-Half 1/4" Male Nipple
A 130868	783310406471	Coupler-HYD Parker #3010-2-542 Male
A 130878	783310406525	Coupler-HYD Female 1/4-18 NPSM
A F021627	783310418771	Coupler, Female 3/8-18 NPTM
A F022061	783310419419	Coupler-HYD Male 3/8-18 NPTF
A F024631	783310420965	Coupler, Female 1/4-18 NPTM

## HYDRAULIC PUMP ACCESSORIES

### Hydraulic Hose Selection Guide

TOOL CAT. NO.	DESCRIPTION	TOOL COUPLER	PUMP CAT. NO.	HOSE CAT. NO.
750	Cable Cutter	1/4" Female Coupler	767	38316
750	Cable Cutter	1/4" Female Coupler	1725	37729
750	Cable Cutter	1/4" Female Coupler	975	17707
777	Bender	3/8" Female Coupler	755, 975, or 980	11289
782	Bender	3/8" Female Coupler	755 or 975	11289
800	Cable Bender	1/4" Female Coupler	1725	37729
880	Bender	3/8" Female Coupler	755 or 975	11289
882	Bender	3/8" Female Coupler	755 or 975	11289
884	Bender	3/8" Female Coupler	980	11289
885	Bender	3/8" Female Coupler	980	11289
1731	C-Frame Driver	1/4" Female Coupler	767	06302
1731	C-Frame Driver	1/4" Female Coupler	1725	37729
1731	C-Frame Driver	1/4" Female Coupler	755 or 975	11289
SDK2021GL	Cable Cutter	3/8" Male Coupler	7475H, 975 or 980	05850, 05851
RK06AT, RK06FT	Crimping Tool	3/8" Male Coupler	7475H, 975 or 980	05850, 05851
RK1240,	Crimping Tool	3/8" Male Coupler	7475H, 975 or 980	05850, 05851
RK1550	Crimping Tool	3/8" Male Coupler	7475H, 975 or 980	05850, 05851

## IN-LINE CABLE CUTTERS ES32LX



ES32LX



**COPPER/ALUMINIUM CUTTER**

- Small size makes the ES32LX an excellent tool for use inside panel boxes
- In-line tool style is light weight and very easy to control
- One trigger controls all tool functions
- Tools automatically retract when the cutting cycle is complete
- Head rotates 350°

### SPECIFICATIONS

Height	15-1/2" (394 mm)
Width	2-7/8" (73 mm)
Weight	5 lb (2.2 kg)
Capacity	600 kcmil (304 mm) Cu or Al cable

### ES32LX

CAT NO.	UPC NO.	DESCRIPTION
ES32LX11	783310611943	32 mm Soft Metal Cable Cutter, 120V Charger, Two 2.0 Ah Batteries
ES32LX12	783310611950	32 mm Soft Metal Cable Cutter, 12V Charger, Two 2.0 Ah Batteries
ES32LX22	783310611967	32 mm Soft Metal Cable Cutter, 230V Charger, Two 2.0 Ah Batteries
<b>B</b> ES32LXB	783310611998	32 mm Soft Metal Cable Cutter, Bare Tool Only

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 05167	783310051671	18V 4.0Ah Li-ion Battery
<b>A</b> 52177	783310521778	18V 2.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>R</b> HE.10314	783310120926	Movable Blade
<b>R</b> HE.10315	783310120933	Fixed Blade
<b>A</b> 12274	783310122746	Carrying Strap



# IN-LINE CABLE CUTTER

## ESC35LX, ESC50LX

- Cutting head rotates 350°
- Tool automatically retracts when the cutting cycle is complete
- Overmolded tacky grip area make gripping the tool easier and more comfortable
- Retraction stop feature reduces time between cuts on smaller wire sizes

**NEW**



ESC35LX



ESC50LX






### SPECIFICATIONS

	ESC35LX	ESC50LX
Height	18" (457 mm)	21" (533 mm)
Width	3" (76 mm)	3" (76 mm)
Length	4.5" (114 mm)	4.5" (114 mm)
Weight	6.6 lb (3 kg)	7.2 lb (3.25 kg)
Capacity	Cuts up to 1.38" diameter Copper (Cu) and Aluminum (Al) Standard/ Fine Stranded Cable	Cuts up to 2" diameter Copper (Cu)/ Aluminum (Al) Standard and Fine Stranded Cable







### ESC35LX

CAT NO.	UPC NO.	DESCRIPTION
ESC35LX11	783310613350	35 mm Soft Metal Cable Cutter, 120V Charger, Two 2.0 Ah Batteries
ESC35LX12	783310613367	35 mm Soft Metal Cable Cutter, 12V Charger, Two 2.0 Ah Batteries
ESC35LX22	783310613374	35 mm Soft Metal Cable Cutter, 230V Charger, Two 2.0 Ah Batteries

### ESC50LX

CAT NO.	UPC NO.	DESCRIPTION
 ESC50LX11	783310080060	50 mm Soft Metal Cable Cutter, 120V Charger, Two 4.0 Ah Batteries
 ESC50LX12	783310080077	50 mm Soft Metal Cable Cutter, 12V Charger, Two 4.0 Ah Batteries
 ESC50LX22	783310080107	50 mm Soft Metal Cable Cutter, 230V Charger, Two 4.0 Ah Batteries
  ESC50LXB	783310080053	50 mm Soft Metal Cable Cutter, Bare Tool Only

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
 ES35E	783310071891	Cutting Blade (2)
 05167	783310051671	18V 4.0Ah Li-ion Battery
 52178	783310521785	120V Li-ion Battery Charger
 52179	783310521792	230V Li-ion Battery Charger
 52180	783310521808	12V Li-ion Battery Charger
 12274	783310122746	Carrying Strap



**COPPER/ALUMINIUM CUTTER**

# PISTOL STYLE CABLE CUTTERS

ESC85LX, ESC105LX,  
ESG105LX

- 350° rotating guillotine cutting head
- Dual position handles for easy operation and transport
- Single trigger operation
- Automatic retraction after completed cycle

## SPECIFICATIONS

	ESC85LX	ESC105LX, ESG105LX
Length	21" (533 mm)	23-3/4" (604 mm)
Width	3-1/8" (80 mm)	3-1/8" (80 mm)
Height	13" (330 mm)	22 lb (9.9 kg)
Weight	15.2 lb (6.9 kg)	13" (330 mm)
Capacity	3.35" diameter (85 mm) Communications, Cu & Al Power Cables	4" diameter (105 mm) Communications, Cu & Al Power Cables



ESC85LX

## ESC85LX

CAT NO.	UPC NO.	DESCRIPTION
ESC85LX11	783310612759	85 mm Soft Metal Cable Cutter, 120V Charger, Two 4.0 Ah Batteries
ESC85LX12	783310612766	85 mm Soft Metal Cable Cutter, 12V Charger, Two 4.0 Ah Batteries
ESC85LX22	783310612773	85 mm Soft Metal Cable Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESC85LXB	783310612803	85 mm Soft Metal Cable Cutter, Bare Tool Only



ESC105LX

## ESC105LX – SCISSOR STYLE

CAT NO.	UPC NO.	DESCRIPTION
ESC105LX11	783310612636	105 mm Soft Metal Cable Cutter, 120V Charger, Two 4.0 Ah Batteries
ESC105LX12	783310612643	105 mm Soft Metal Cable Cutter, 12V Charger, Two 4.0 Ah Batteries
ESC105LX22	783310612650	105 mm Soft Metal Cable Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESC105LXB	783310612681	105 mm Soft Metal Cable Cutter, Bare Tool Only



ESG105LX

## ESG105LX – GUILLOTINE STYLE

CAT NO.	UPC NO.	DESCRIPTION
ESG105LX11	783310612513	105 mm Soft Metal Cable Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG105LX12	783310612520	105 mm Soft Metal Cable Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG105LX22	783310612537	105 mm Soft Metal Cable Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESG105LXB	783310612568	Cable Cutter, Li-ion, 105 mm STD, Bare Tool Only

## ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 05167	783310051671	18V 4.0Ah Li-ion Battery
<b>A</b> 52177	783310521778	18V 2.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap
HE.10310	783310234920	Handle (ESC105LX, ESG105LX)



**COPPER/ALUMINIUM CUTTER**

## RATCHET STYLE CABLE CUTTER ESR1000LX, ESR25LX

**NEW**



ESR1000LX

**COPPER/ALUMINIUM CUTTER**

### SPECIFICATIONS

	ESR1000LX	ESR25LX
Height	15" (380 mm)	15" (380 mm)
Width	4/5" (115 mm)	4/5" (115 mm)
Length	7.75" (197 mm)	7.75" (197 mm)
Weight	7.4 lb (3.35 kg)	7.4 lb (3.35 kg)
Capacity	1250 kcmil Cu / 1500 kcmil Al	ACSR: 636 kcmil (Grosbeak) (25 mm) Standard Guy Strand: 5/8" (16 mm)

### ESR1000LX

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ESR1000LX11	783310079552	Cu/Al Ratchet Cutter with two 18V 4.0Ah Batteries, 120V Charger
<b>N</b> ESR1000LX12	783310079569	Cu/Al Ratchet Cutter with two 18V 4.0Ah Batteries, 12V Charger
<b>N</b> ESR1000LX22	783310079576	Cu/Al Ratchet Cutter with two 18V 4.0Ah Batteries, 230V Charger
<b>N B</b> ESR1000LXB	783310079545	Bare Tool Only – Cu/Al Ratchet Cutter

### ESR25LX

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ESR25LX11	783310079606	ACSR Ratchet Cutter, 120V Charger, Two 4.0Ah Batteries
<b>N</b> ESR25LX12	783310079613	ACSR Ratchet Cutter, 12V Charger, Two 4.0Ah Batteries
<b>N</b> ESR25LX22	783310079620	ACSR Ratchet Cutter, 230V Charger, Two 4.0Ah Batteries
<b>N B</b> ESR25LXB	783310079590	Bare Tool Only – ACSR Ratchet Cutter

**NEW**



ESR25LX

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 52176	783310521761	18V 4.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap





## IN-LINE ACSR CUTTER ES20LX



ES20LX



### SPECIFICATIONS

Height	15" (381 mm)
Width	2-7/8" (73 mm)
Weight	4.6 lb (2 kg)

### CAPACITY

Max Diameter	3/4" diameter
ACSR	336.4 kcmil Merlin
Standard Guy Strand	3/8" diameter
Ground Rod	3/8" diameter
Rebar (SCH 60)	3/8" diameter
Soft Steel Bolts	3/8" diameter

### ES20LX

CAT NO.	UPC NO.	DESCRIPTION
ES20LX11	783310612186	20 mm ACSR Cutter, 120V charger, Two 4.0Ah Batteries
ES20LX12	783310612193	20 mm ACSR Cutter, 12V charger, Two 4.0Ah Batteries
ES20LX22	783310612209	20 mm ACSR Cutter, 230V charger, Two 4.0Ah Batteries
<b>B</b> ES20LXB	783310612230	20 mm ACSR Cutter, Bare Tool Only

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>R</b> ES20E	783310055259	Blade Kit
<b>A</b> 52176	783310521761	18V 4.0Ah Li-ion Battery
<b>A</b> 52177	783310521778	18V 2.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap

# IN-LINE ACSR CUTTERS

## ESC25LX, ESG25LX

**NEW**


ESC25LX


**SPECIFICATIONS**

Width	3" (76 mm)
Height	18.5" (470 mm)
Weight	7 lb (3.17 kg)

**CAPACITY**

Cutter Head Opening	1" (25 mm)
ACSR	557 kcmil
Standard Guy Strand	1/2" (12 mm)
EHS Guy Strand	3/8" (10 mm)

**ESC25LX – SCISSOR STYLE**

CAT NO.	UPC NO.	DESCRIPTION
<b>N</b> ESC25LX11	783310084907	25 mm ACSR Cutter, 120V Charger, Two 4.0Ah Batteries
<b>N</b> ESC25LX12	783310084914	25 mm ACSR Cutter, 12V Charger, Two 4.0Ah Batteries
<b>N</b> ESC25LX22	783310084921	25 mm ACSR Cutter, 230V Charger, Two 4.0Ah Batteries
<b>N B</b> ESC25LXB	783310084938	25 mm ACSR Cutter, Bare Tool Only

**ACCESSORIES**

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 52176	783310521761	18V 4.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap



ESG25LX



- Designed to cut ACSR, guy strand, and ground rod
- Guillotine style head
- Equipped with retraction stop to aid in time and battery savings
- Replaceable hardened blades for increased tool longevity

**SPECIFICATIONS**

Width	2-7/8" (73 mm)
Height	16.5" (419 mm)
Weight	5.8 lb (2.6 kg)

**CAPACITY**

Cutter Head Opening	1" (25 mm)
ACSR	636 kcmil
Standard Guy Strand	5/8" (16 mm)
EHS Guy Strand	7/16" (11 mm)

**ESG45LX – GUILLOTINE STYLE**

CAT NO.	UPC NO.	DESCRIPTION
ESG25LX11	783310612308	25 mm ACSR Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG25LX12	783310612315	25 mm ACSR Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG25LX22	783310612322	25 mm ACSR Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESG25LXB	783310612353	25 mm ACSR Cutter, Bare Tool Only

## ACSR CUTTERS ESG45LX, ESG55LX



ESG45LX



- Designed specifically to cut ACSR, guy strand and ground rods
- Retraction Stop allows the operator to stop the ram retraction at any point simply by tapping the trigger, and then starting the next cutting cycle from that point saving time and energy
- Two-stage hydraulic system provides fast advance and power speeds
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tools automatically retract when the cutting cycle is complete

### SPECIFICATIONS

Width	4" (101 mm)
Height	20" (508 mm)
Weight	10 lb (4.5 kg)

### CAPACITY

ACSR	1590 kcmil
Standard Guy Strand	5/8" diameter (16 mm)
EHS Guy Strand	1/2" diameter (13 mm)

### ESG45LX

CAT NO.	UPC NO.	DESCRIPTION
ESG45LX11	783310612872	45 mm ACSR Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG45LX12	783310612889	45 mm ACSR Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG45LX22	783310612896	45 mm ACSR Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESG45LXB	783310612926	45 mm ACSR Cutter, Bare Tool Only

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 52176	783310521761	18V 4.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> 12274	783310122746	Carrying Strap



ESG55LX



- Lightweight and very easy to handle
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tools automatically retract when the cutting cycle is complete

### SPECIFICATIONS

Length	18-1/8" (460 mm)
Width	3-1/8" (80 mm)
Height	13-1/4" (337 mm)
Weight	17.5 lb (8 kg)

### CAPACITY

ACSR	2515 kcmil
Standard Guy Strand	5/8" diameter (16 mm)
EHS Guy Strand	9/16" diameter (14 mm)

### ESG55LX

CAT NO.	UPC NO.	DESCRIPTION
ESG55LX11	783310612995	55 mm ACSR Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG55LX12	783310613008	55 mm ACSR Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG55LX22	783310613015	55 mm ACSR Cutter, 230V Charger, Two 4.0 Ah Batteries
<b>B</b> ESG55LXB	783310613046	55 mm ACSR Cutter, Bare Tool Only



# REMOTE CUTTING HEADS



SDK105



SDG85



SDG45



SDG105



SDG55



SPECIFICATIONS	SDG45	SDG55	SDG85	SDG105	SDK105
Length	16-5/8" (423 mm)	18-18" (460 mm)	21" (533 mm)	23-3/4" (604 mm)	20" (510 mm)
Weight	8.38 lb (3.8 kg)	12.35 lb (5.6 kg)	9.48 lb (4.3 kg)	16.98 lb (7.7 kg)	17 lb (7.7 kg)
Connector	3/8" NPT Male (Screw-Type)	3/8" NPT Male (Screw-Type)	3/8" NPT Male (Screw-Type)	3/8" NPT Male (Screw-Type)	3/8" NPT Male (Screw-Type)
Communications, Cu & Al Power Cables	1-3/4" (50 mm)	2-1/8" (55 mm)	3-3/8" (85 mm)	4" (105 mm)	4" (105 mm)
ACSR	1590 kcmil (MCM)	2515 kcmil	-	-	-

STANDARD GUY STRAND	SDG45	SDG55
Standard Guy Strand	5/8" (16 mm)	5/8" (16 mm)
EHS Guy Strand	1/2" (13 mm)	9/16" (14 mm)
Ground Rod	5/8" (16 mm)	3/4" (19 mm)
Rebar	1/2" (13 mm)	5/8" (16 mm)
Wire Rope	5/8" (16 mm)	5/8" (16 mm)
Copper and Aluminum Cable	1500 kcmil (MCM)	1500 kcmil (MCM)

# 10K PSI PUMP

## EHP700L



EHP700L



- Capable of powering any high-pressure hydraulic remote head
- Equipped with Intelli-CRIMP® technology to monitor crimping force
- Retraction Stop Repeat (RSR) allows users to teach pump where to start and stop each cycle
- Real-time LED readout permits user to visually monitor pressure cycle
- Job specific crimp, cut, and punch settings
- Mode dial allows for pump to learn new operating cycles
- Dual battery ports – 1 active/1 stored

### SPECIFICATIONS

Length	14" (356 mm)
Width	6-1/2" (165 mm)
Height	11-1/2" (292 mm)
Weight	14.1 lb (6.4 kg)
Operating Pressure	10,000 psi (700 bar)

### EHP700L

CAT NO.	UPC NO.	DESCRIPTION
EHP700L11	783310007357	Power Pump, Li-ion, STD, 120V
EHP700L12	783310007647	Power Pump, Li-ion, STD, 12V
EHP700L22	783310007654	Power Pump, Li-ion, STD, 230V
EHP700L120	783310007661	Power Pump, Li-ion, STD, 120V AC
EHP700L230	783310007678	Power Pump, Li-ion, STD, 230V AC
<b>B</b> EHP700LB	783310011514	Power Pump, Li-ion, STD, Bare

### ACCESSORIES

CAT NO.	UPC NO.	DESCRIPTION
<b>A</b> 52176	783310521761	18V 3.0Ah Li-ion Battery
<b>A</b> 52178	783310521785	120V Li-ion Battery Charger
<b>A</b> 52179	783310521792	230V Li-ion Battery Charger
<b>A</b> 52180	783310521808	12V Li-ion Battery Charger
<b>A</b> TG3	783310010548	Strap
<b>A</b> 25766	783310257660	Adapter, Charger 18V Li-ion to 12V Ni
<b>A</b> EAC18120	783310521914	Adapter, AC – 230V to 18V
<b>A</b> HTA4GL	783310007593	Remote Control
<b>R</b> EL122/32	783310020424	Hydraulic Fluid, Biodegradable
<b>R</b> 17707	783310177074	Hose Assembly, 1/4" X 10' 3/8M & 1/4M Filled
<b>R</b> 05850	783310058502	Hose Assembly, 1/4" X 10' 3/8M & 3/8F Filled
<b>R</b> 01058	783310010586	Hose Assembly, 1/4" X 6' 3/8M & 1/4M Filled
<b>R</b> 01059	783310010593	Hose Assembly, 1/4" X 6' 3/8M & 3/8F Filled

# COPPER ALUMINUM CABLE CUTTERS



45206



45206i

## One-Hand Operation Ratchet Cutter

- Simple, one-hand operation
- Exclusive two-speed ratcheting mechanism adjusts for light/heavy cutting
- Well-suited for tight working spaces
- Blades can be opened mid-cycle
- Available with cushioned handles or with insulated cushioned handles

### SPECIFICATIONS

	45206I	45207I
<b>Maximum Capacity*</b>	Copper: 600 kcmil (MCM) (300 mm <sup>2</sup> ) Aluminum: 600 kcmil (MCM) (300 mm <sup>2</sup> ) Communications Cable: 1-3/8" (35 mm) dia.	Copper: 750 kcmil (MCM) (400 mm <sup>2</sup> ) Aluminum: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Communications Cable: 2" (51 mm) dia.
<b>Frequent Use Capacity*</b>	Copper: 500 kcmil (MCM) (240 mm <sup>2</sup> ) Aluminum: 500 kcmil (MCM) (240 mm <sup>2</sup> )	Copper: 600 kcmil (MCM) (300 mm <sup>2</sup> ) Aluminum: 750 kcmil (MCM) (400 mm <sup>2</sup> )
<b>Length</b>	10" (254 mm)	11" (279 mm)
<b>Weight</b>	1-7/16" (36.5 mm)	2" (51 mm)

CAT. NO.	UPC NO.	DESCRIPTION
45206	783310452065	Cutter, Cable-Ratchet
45206i	783310126805	Cutter, Ratchet Cable-Insulated
45207	783310452072	Cutter, Cable-Ratchet
45207i	783310126812	Cutter, Cable-Insulated
<b>R</b> 45218	783310452188	Blade Set-Movable
<b>R</b> 45212	783310452126	Blade-Fixed (PA-1815)
<b>R</b> 45211	783310452119	Blade Set-Moveable
<b>R</b> 45228	783310452287	Blade/Handle-Fixed (45207)

\*Capacity may be less for compact and compressed cables



## High Capacity Ratchet Cutter

- Two cutting actions – fast scissor cutting for small cable and insulation; converts automatically to ratchet mode
- Extra thick blades, ground flat to reduce potential for breakage
- Ratchet action for heavy-duty cutting
- Anti-slip mechanism for positive ratchet action

### SPECIFICATIONS

Maximum Capacity*	Copper: 1500 kcmil (MCM) (800 mm <sup>2</sup> ) Aluminum: 1500 kcmil (MCM) (800 mm <sup>2</sup> )
Frequent Use Capacity*	Copper: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Aluminum: 1000 kcmil (MCM) (500 mm <sup>2</sup> )
Length	27-1/2" (698 mm) long
Jaw opening	2" (51 mm)
Weight	11.41 lb (5.17 kg)

\*Capacity may be less for compact and compressed cables

CAT. NO.	UPC NO.	DESCRIPTION
756	783310340812	Heavy-Duty Ratchet Cable Cutter with Rubber Boot
<b>R</b> 34188	783310341888	Cutter Head Unit (Includes 2 Blades)



## Compact Fiberglass Handled Ratchet Cutter

- Two-handed operation for compact actuation
- Short fiberglass handles make it easy to use in tight places and to store in tool boxes
- Single-speed ratchet mechanism
- Blade release allows blades to be opened in mid-cut
- Heavy-duty forged steel blades provide long life

### SPECIFICATIONS

Cutting Capacity*	Copper: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Aluminum: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Communications Cable: 1-1/8" dia. (28 mm <sup>2</sup> )
Length	10-3/4" (273 mm)
Weight	3.6 lb (1.6 kg)

\*Capacity may be less for compact and compressed cables

CAT. NO.	UPC NO.	DESCRIPTION
761	783310117612	Two-Hand Ratchet Cable Cutter
<b>R</b> 11768	783310117681	Movable Blade (761)



## Extended Fiberglass Handle Cable Cutters

- Strong, lightweight fiberglass handles
- Adjustable pivot bolt provides for blade adjustment
- Replaceable, forged, heat-treated, and precision ground blades (Excludes 718F)



### SPECIFICATIONS

	718F	704	705	706
<b>Maximum Capacity*</b>	Copper: 350 kcmil (MCM) (150 mm <sup>2</sup> ) Aluminum: 500 kcmil (MCM) (240 mm <sup>2</sup> ) Communications Cable: 1" (25 mm) dia.	Copper: 350 kcmil (MCM) (150 mm <sup>2</sup> ) Aluminum: 500 kcmil (MCM) (240 mm <sup>2</sup> ) Communications Cable: 1-1/4" (32 mm) dia.	Copper: 500 kcmil (MCM) (240 mm <sup>2</sup> ) Aluminum: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Communications Cable: 1-3/4" (44 mm) dia.	Copper: 750 kcmil (MCM) (400 mm <sup>2</sup> ) Aluminum: 1000 kcmil (MCM) (500 mm <sup>2</sup> ) Communications Cable: 1-1/2" (38 mm) dia.
<b>Frequent Use Capacity*</b>	Copper: Copper 4/0 AWG (95) Aluminum: 350 kcmil (MCM) (150 mm <sup>2</sup> )	Copper: 250 kcmil (MCM) (120 mm <sup>2</sup> ) Aluminum: 350 kcmil (MCM) (150 mm <sup>2</sup> )	Copper: 350 kcmil (MCM) (150 mm <sup>2</sup> ) Aluminum: 750 kcmil (MCM) (400 mm <sup>2</sup> )	Copper: 500 kcmil (MCM) (240 mm <sup>2</sup> ) Aluminum: 750 kcmil (MCM) (400 mm <sup>2</sup> )
<b>Length</b>	17-1/2" (444 mm)	21" (533 mm)	25-1/2" (648 mm)	31-1/2" (800 mm)
<b>Weight</b>	2.8 lb (1.3 kg)	3.01 lb (1.37 kg)	5.5 lb (2.5 kg)	6.2 lb (2.8 kg)

\*Capacity may be less for compact and compressed cables

CAT. NO.	UPC NO.	DESCRIPTION
718F	783310105077	Heavy-Duty Cable Cutter, 17-1/2"
704	783310245643	Heavy-Duty Cable Cutter, 21"
705	783310059233	Heavy-Duty Cable Cutter, 25-1/2"
706	783310222910	Heavy-Duty Cable Cutter, 31-1/2"
<b>R</b> 24565	783310245650	704 Cutter Unit (Includes 2 Blades)
<b>R</b> 24567	783310245674	704 Handle Unit (Includes Handle, Sleeve, Grip)
<b>R</b> 05930	783310059301	705 Handle Unit (Includes Handle, Sleeve, Grip)
<b>R</b> 06555	783310065555	705 & 706 Cutter Unit (Includes 2 Blades)
<b>R</b> 22296	783310222965	706 Handle Unit (Includes Handle, Sleeve, Grip)



727

## Hand-Held Cable Cutter

- Precision-ground, shear-action, curved cutting blades
- 727 has PVC-covered, high-leverage handles for easier cuts
- 727M has cushion grip, high-leverage handles for added comfort
- Heat-treated for long life
- Made of heavy-duty forged steel
- Rust-resistant black oxide finish

### SPECIFICATIONS

Maximum Capacity*	Copper: 2/0 (70 mm <sup>2</sup> ) Aluminum: – Communications Cable: –
Frequent Use Capacity*	Copper: #1 AWG (35 mm <sup>2</sup> ) Aluminum: 2/0 (70 mm <sup>2</sup> ) Communications Cable: 100 pair
Length	10-3/4" (273 mm)
Weight	3.6 lb (1.6 kg)

\*Capacity may be less for compact and compressed cables



727M

CAT. NO.	UPC NO.	DESCRIPTION
727	783310312918	Cable Cutter
727M	783310126294	Cable Cutter with Molded Grip

## Heavy-Duty Manual Communications Cable Cutter

- Forged and heat-treated blades specially designed for communications cable
- Makes clean cuts with minimal distortion on lead, rubber, PVC and polyethylene-sheathed cables
- Blades and handles are replaceable
- Precision-ground, shear-type blades
- Fiberglass handles with non-slip rubber grips

### SPECIFICATIONS

Cutting Capacity	2-1/4" (57 mm) Communications Cable (900 pair, 24 AWG)
Length	37" (940 mm)
Weight	7.2 lb (3.3 kg)



765

CAT. NO.	UPC NO.	DESCRIPTION
765	783310060116	Heavy-Duty Communications Cutter
<b>R</b> 05935	783310059356	Cutter Blade (765) (2 required)

## CUTTER DIES



### Guy-Wire Cutter Dies

- Works with any crimping tool that accepts 12-ton "U" type dies
- Simple to install in crimping tools
- Requires no adjustments for cutting different materials
- Will cleanly cut guy-wire (including EHS), grade 60 rebar, ground rod, soft steel bolts up to 5/8" (16 mm) and up to 477 kcmil (MCM) (240 mm<sup>2</sup>) ACSR
- For use in 12 and 15-ton crimping tools

#### SPECIFICATIONS

<b>Capacity</b>	Guy-Wire: 5/8" (16 mm) dia. Ground Rod: 5/8" (16 mm) dia. EHS Guy-Wire: 5/8" (16 mm) dia. Soft Steel Bolts: 5/8" (16 mm) dia. Rebar (grade 60): 5/8" (16 mm) dia. ACSR: 477 kcmil (MCM) (240 mm <sup>2</sup> )
-----------------	---

CAT. NO.	UPC NO.	DESCRIPTION
00949	783310009498	Cutting Dies For 12-Ton "U" Die Type Crimping Tools



### ACSR "W" Cutter Dies

- "W" style dies for cutting ACSR
- Improved steel and heat treatment for better durability
- Can be used with any crimping tool that accepts "W" dies including: Greenlee EK622L, and EK628L (with CJD3 jaws)
- For use in 6-ton crimping tools

#### SPECIFICATIONS

<b>Capacity</b>	4/0 ACSR
-----------------	----------

CAT. NO.	UPC NO.	DESCRIPTION
KD6-27	783310101826	"W" Style Cutting Dies for ACSR



## WIRE CRIMPING TOOLS



EK50ML138B



### Micro Crimping Tool

- Ergonomic; total weight less than 2.2 lb
- Crimp 3x faster with 90% less force
- LED work light
- 65% faster crimping cycle vs. ratcheting tool
- 250 crimps per cycle charge when crimping 10 AWG wire
- Patented Jaw Actuation for crimping cycle
- Innovative trigger with PowerSense™ Technology
- Overmolded grip for maximum comfort
- 10.8V Li-ion battery with charge indicator

#### SPECIFICATIONS

Weight	2.2 lb (1 kg)
--------	---------------

CAT. NO.	UPC NO.	DESCRIPTION
EK50ML12011	783310031055	Crimping Tool Kit with 12 mm Jaw and 110V Charger with Carrying Case
EK50ML13811	783310031086	Crimping Tool Kit with 13.8 mm Jaw and 110V Charger with Carrying Case
EK50ML12022	783310031239	Crimping Tool Kit with 12 mm Jaw and 230V Charger with Carrying Case
EK50ML13822	783310031246	Crimping Tool Kit with 13.8 mm Jaw and 230V Charger with Carrying Case
EK50ML120B	783310031284	12 mm Jaw EK50ML Bare Tool
<b>R</b> EK50ML138B	783310031307	13.8 mm Jaw EK50ML Bare Tool
<b>R</b> MBP108	783310031277	10.8V EK50ML Li-Ion Battery
<b>R</b> MBC110	783310031253	10.8V EK50ML Li-Ion Battery Charger, 110V
<b>R</b> MBC230	783310031260	10.8V EK50ML Li-Ion Battery Charger, 230V

See page 302 for the complete line of dies.

**The EK50ML138 is compatible with all Greenlee Kwik Cycle® dies for various types of cables and sizes.**

#### COMPATIBLE DIE SETS

	WEZAG®	PANDUIT®	THOMAS & BETTS®	IDEAL®
EK50ML120	CS30, CS150	CT-2600, CT-300	Sta-Kon®	-
EK50ML138	-	-	-	Crimpmaster™



## Premium Terminal Crimping Tool



K210

- Storage for two sets of crimping dies in the handles
- No tools needed to change dies
- Precision mechanism for smooth crimping cycles
- Hardened mechanism components for long term durability
- Cushioned handles for comfort
- Full cycle mechanism helps assure complete crimps, but tool can be opened in mid-cycle if necessary
- Equipped with 3 crimping die sets for 22-10 AWG insulated terminals (red, yellow, blue), 22-10 AWG uninsulated terminals and 26-8 AWG wire ferrules

### SPECIFICATIONS

Length	9" (23 cm)
Weight	1.35 lb (.6 kg)
Crimping Dies Included	22-10 AWG Insulated Terminals 22-10 AWG Uninsulated Terminals 26-8 AWG Wire Ferrules

CAT. NO.	UPC NO.	DESCRIPTION
K210	783310108726	Crimping Tool with 10873, 10874 and 10875 die sets
<b>R</b> 10873	783310108733	Die Set, 22-10 AWG Insulated Terminals
<b>R</b> 10874	783310108740	Die Set, 22-10 AWG Uninsulated Terminals
<b>R</b> 10875	783310108757	Die Set, 26-8 AWG Wire Ferrules
<b>A</b> 10876	783310108764	Die Set, RG 58/59/62/71
<b>A</b> 10877	783310108771	Die Set, 20-10 AWG Open Barrel Connectors

## Terminal Crimping



KP1022

- Two die positions permit the KP1022 to crimp both insulated and uninsulated terminals and splices
- Forged steel and hardened design provides long life
- Smooth pivot action allows tool to easily be used with one hand
- Double-cushioned handle grips on the KP1022 are easy on the hands
- Standard handle grips on the KP1022D make it easy to slip in/out of tool pouches
- Precision machined and hardened cutter blades make wire cutting easy

### SPECIFICATIONS

Overall Length	9-1/2" (241 mm)
Weight	1.05 lb (.48 kg)
Capacity	Insulated Terminals & Splices – 10-22 AWG Uninsulated Terminals & Splices – 10-22 AWG



KP1022D

CAT. NO.	UPC NO.	DESCRIPTION
KP1022	783310021551	Terminal Crimping Tool with Molded Grip
KP1022D	783310106333	Terminal Crimping Tool with Dipped Grip



K2-1BGL

### Kwik Cycle® Crimping Tool

- For non-insulated terminals
- Includes ratchet mechanism which releases only after full crimp cycle is completed

#### SPECIFICATIONS

Capacity	22-6 AWG
Length	12.8" (325 mm)
Weight	.3 lb (136 g)

CAT. NO.	UPC NO.	DESCRIPTION
K2-1BGL	783310026327	Kwik Cycle® Crimping Tool

## WIRE FERRULE CRIMPING TOOLS



K1GL

### Wire Ferrule Crimping Tool 26 – 13 AWG

- Makes trapezoidal crimps
- Includes cutter and replaceable stripper blade set

#### SPECIFICATIONS

Range	26-13 AWG (.14-2.5 mm <sup>2</sup> )
Length	6.9" (175 mm)
Weight	.4 lb (0.2 kg)

CAT. NO.	UPC NO.	DESCRIPTION
K1GL	783310026334	Wire Ferrule Crimper



K32GL

### Wire Ferrule Crimping Tool 26 – 10 AWG

- Makes trapezoidal crimps with full-cycle ratchet mechanism to assure complete crimps
- Crimps single and twin cable wire ferrules
- Adjusts automatically to correct crimp size

#### SPECIFICATIONS

Range	Single cable wire ferrules: 26-10 AWG (.14-6 mm <sup>2</sup> ) Twin wire ferrules: 2 x 20-2 x 13 AWG (2 x .5-2 x 2.5 mm <sup>2</sup> )
Length	8.4" (213 mm)
Weight	1.1 lb (.4 kg)

CAT. NO.	UPC NO.	DESCRIPTION
K32GL	783310026372	Wire Ferrule Crimper

## MANUAL CRIMPING



K05-SYNCRO



### K05-SYNCRO K-Series Crimping Tool

#### SPECIFICATIONS

Crimping Range	8 to 1/0 AWG
Length	16"
Weight	2.6 lb (1.18 kg)

CAT. NO.	UPC NO.	DESCRIPTION
K05-SYNCRO	783310064404	Crimping Tool

UL and cUL classified with Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts® and Penn-Union® copper connectors.



K09-SYNCRO



### K09-SYNCRO K-Series Crimping Tool

#### SPECIFICATIONS

Capacity	1 AWG to 250 kcmil
Length	23.62" - 29.52"
Weight	5.7 lb (2.6 kg)

CAT. NO.	UPC NO.	DESCRIPTION
K09-SYNCRO	783310064411	Crimper (1 AWG - 250 kcmil)

UL and cUL classified with Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts® and Penn-Union® copper connectors.