

CONSTRUCTION



K 2628 H

25 KG CLASS 28 MM HEX BREAKING HAMMER

- Heavy Duty breaker provides 64 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Additional third handle gives maximum control when lifting the breaker between applications
- 1200 BPM provides maximum productivity in all applications
- Brushless motor allows for maximum run time in-between service intervals
- 10 m cable allows for a working area of up to 314 m²
- 28 mm Hex reception
- Separately available trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite



K 2628 H

Power input (W)	2400
Blow energy (EPTA)(J)	64
Full load hammer action (bpm)	1200
Tool reception	K-Hex
Vibration chiseling (m/s ²)	6.2
Weight (kg)	25.7
Supplied in	No kitbox or bag supplied
Article Number	4933471695

28 MM HEX 400 X 35 MM FLAT CHISEL

Article Number 4932459775



Floating body anti-vibration technologies



Additional third handle



28 mm Hex reception for chisels with and without ring

K 2000 H | 20 KG CLASS 28 MM HEX BREAKING HAMMER

- Compact and powerful breaker provides 42 blow Joules of impact energy for toughest demolition applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- Additional third handle gives maximum control when lifting the breaker between applications
- 1300 BPM provides maximum productivity in all applications
- 10 m cable allows for a working area of up to 314 m²
- 28 mm Hex reception
- Separately available trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite



K 2000 H

Power input (W)	2200
Blow energy (EPTA)(J)	42
Full load hammer action (bpm)	1300
Tool reception	K-Hex
Vibration chiseling (m/s ²)	4.7
Weight (kg)	24.2
Supplied in	No kitbox or bag supplied
Article Number	4933459604

28 MM HEX 400 MM POINTED CHISEL

Article Number 4932459774



BRT | BREAKER TROLLEY

- Breaker trolley with 4 chisel location and cable management makes it easy to transport breaker on the jobsite
- 100 kg loading capacity
- Powder coated finish protects against jobsite abuse
- Compatible with K 2000 H and K 2500 H



BRT

Loading capacity (kg)	100
Weight (kg)	14.3
Supplied in	No kitbox or bag supplied
Article Number	4933459794

K 1530 H | 16 KG CLASS 30 MM HEX BREAKING HAMMER

- Powerful and compact breaker delivering up to 39 blow Joules of impact energy for challenging applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1560 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Dedicated brush window for easy maintenance
- 30 mm Hex reception
- Service reminder light to indicate when service will be needed
- BMC with wheels for ease of transport on site



K 1530 H

Power input (W)	2100
Blow energy (EPTA)(J)	39
Full load hammer action (bpm)	1560
Tool reception	K-Hex
Vibration chiseling (m/s ²)	6.4
Weight (kg)	16.8
Supplied in	Plastic case
Article Number	4933464117

30 MM HEX POINTED CHISEL

Article Number 4932464162



K 1528 H | 16 KG CLASS 28 MM HEX BREAKING HAMMER

- Powerful and compact breaker delivering up to 39 blow Joules of impact energy for challenging applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1560 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Dedicated brush window for easy maintenance
- 28 mm Hex reception
- Service reminder light to indicate when service will be needed
- BMC with wheels for ease of transport on site



	K 1528 H
Power input (W)	2100
Blow energy (EPTA(J))	39
Full load hammer action (bpm)	1560
Tool reception	K-Hex
Vibration chiseling (m/s ²)	8.8
Weight (kg)	17.2
Supplied in	Plastic case
Article Number	4933464118

28 MM HEX 400 X 35 MM FLAT CHISEL

Article Number 4932459775



K 1000 S | 10 KG CLASS SDS-MAX BREAKING HAMMER

- Compact chiseling hammer delivering up to 26 blow Joules of impact energy for a wide variety of applications
- Floating body anti-vibration technologies allows the user to work all day without reaching dangerous exposure levels
- 1400 – 1950 BPM provides maximum productivity in all applications
- 6 m cable allows for working area over 110 m²
- Variolock (12 positions) for selecting the most appropriate chisel angle
- SDS-Max tool reception
- Service reminder light to indicate when service will be needed
- Dedicated brush window for easy maintenance
- BMC with wheels for ease of transport on site



	K 1000 S
Power input (W)	1750
Blow energy (EPTA(J))	26
Full load hammer action (bpm)	1400 - 1950
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	6.7
Weight (kg)	12.7
Supplied in	Plastic case
Article Number	4933464120

PCHDE DUST EXTRACTOR WITH 400 MM LONG SDS-MAX POINTED CHISEL

Article Number 4932455290



K 950 | 10 KG CLASS DRILLING AND BREAKING HAMMER

- 20 J blow energy for hard hitting performance
- 1700 watt motor - best in class with plenty in reserve for the toughest applications
- DIGITRONIC™ - fullwave electronics for precise power adjustment to application
- 3 Handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- All metal gearcase - optimum seating of the gears for enhanced service life
- Service indicator light
- Automatic lubrication system for longer life time
- In-Line motor design for more comfort in below waist applications
- Ideal for usage with generators
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



	K 950 S
Power input (W)	1700
No load speed (rpm)	125 - 250
Blow energy (EPTA(J))	20
Full load hammer action (bpm)	975 - 1950
Full load speed (soft hammer) (rpm)	125 - 250
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	12.5
Vibration chiseling (m/s ²)	11
Weight (kg)	11.8
Supplied in	Kitbox
Article Number	4933375710

K 850 8 KG CLASS DRILLING AND BREAKING HAMMER

- Powerful SDS max rotary hammer with AUTOSTOP™ delivering 11 Joules of blow energy whilst maximising user safety
- AUTOSTOP™ shuts down the tool to protect the user after 45° of sharp movement in bind up situations
- Redesigned electronic package delivers constant power and maximum productivity in the most challenging of applications
- Trigger lock-on to prevent user having to hold trigger during long periods of chipping applications
- Large AVS back handle supports two handed drilling applications whilst minimising vibration exposure
- Service light indicator illuminates when tool requires servicing
- Anti-vibration side handle minimising user exposure
- 6 m cable for 110m² working area



AUTOSTOP™ - maximum control, advanced safety



Trigger lock on for chiseling



Large AVS back and side handle minimises vibration exposure

	K 850 S
Power input (W)	1400
No load speed (rpm)	380
Blow energy (EPTA(J))	11
Full load hammer action (bpm)	1600 - 2900
Full load speed (soft hammer) (rpm)	210 - 380
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	9.4
Vibration chiseling (m/s ²)	7.8
Weight (kg)	9.6
Supplied in	Kitbox
Article Number	4933464996

K 900 | 10 KG CLASS BREAKING HAMMER

- 20 J blow energy for hard hitting performance
- 1600 watt motor - best in class with plenty in reserve for the toughest applications
- DIGITRONIC™ - fullwave electronics for precise power adjustment to application
- 3 Handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use
- Service indicator light
- Automatic lubrication system for longer life time
- In-Line motor design for more comfort in below waist applications
- Ideal for usage with generators
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



	K 900 S	K 900 K
Power input (W)	1600	1600
Blow energy (EPTA(J))	20	20
Full load hammer action (bpm)	975 - 1950	975 - 1950
Tool reception	SDS-Max	K-Hex
Vibration chiseling (m/s ²)	11	11
Weight (kg)	11.0	11.0
Supplied in	Kitbox	Kitbox
Article Number	4933375720	4933375650

PCHDE DUST EXTRACTOR WITH 400 MM LONG SDS-MAX POINTED CHISEL

Article Number 4932455290



K 750 S | 7 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 11.9 J impact energy
- Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Fullwave electronics for precise power adjustment to application
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 750 S	
Power input (W)	1550
No load speed (rpm)	300
Blow energy (EPTA(J))	11.9
Full load hammer action (bpm)	2740
Full load speed (soft hammer) (rpm)	240
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	9.5
Vibration chiseling (m/s ²)	9.1
Weight (kg)	8.2
Supplied in	Kitbox
Article Number	4933398600

K 545 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for drilling/chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 545 S	
Power input (W)	1300
No load speed (rpm)	450
Blow energy (EPTA(J))	8.5
Full load hammer action (bpm)	2840
Full load speed (soft hammer) (rpm)	350
Max. drilling solid bit (mm)	45
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	100
Tool reception	SDS-Max
Vibration drilling (m/s ²)	13
Vibration chiseling (m/s ²)	9
Weight (kg)	6.7
Supplied in	Kitbox
Article Number	4933398200

K 540 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 6.3 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of drilling/chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 540 S	
Power input (W)	1100
No load speed (rpm)	450
Blow energy (EPTA(J))	7.5
Full load hammer action (bpm)	3000
Full load speed (soft hammer) (rpm)	430
Max. drilling concrete (mm)	40
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	105
Tool reception	SDS-Max
Vibration drilling (m/s ²)	16.8
Vibration chiseling (m/s ²)	16.7
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933418100

K 500 ST | 5 KG CLASS TRADESMAN BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 5.9 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 500 ST	
Power input (W)	1100
Blow energy (EPTA(J))	7.5
Full load hammer action (bpm)	3000
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	16.7
Weight (kg)	5.9
Supplied in	Kitbox
Article Number	4933443180

K 500 S | 5 KG CLASS BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 500 S	
Power input (W)	1300
Blow energy (EPTA(J))	8.5
Full load hammer action (bpm)	2840
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	11.5
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933398220

REPLACEMENT 400 MM LONG SDS-MAX POINTED CHISEL

Article Number 4932455144



PCE 3/K | 3 KG SDS-PLUS CHIPPING HAMMER

- Over sized heavy weight striker delivers 3.6 joules of impact energy
- 720 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Fully insulated metal gearbox for maximum stability
- Lightweight, ergonomic front handle is fully adjustable and can be securely fixed in the best position to suit the required drilling angle
- AVS (Anti-Vibration-System) and soft grip for less tiring operation
- Lock-on switch for more comfortable extended use
- Variolock (35 positions) for setting the face of the chisel
- 4 m cable



PCE 3/K	
Power input (W)	720
Blow energy (EPTA(J))	3.6
Full load hammer action (bpm)	0 - 3650
Tool reception	SDS-Plus
Weight (kg)	3.7
Supplied in	Kitbox
Article Number	4933384300

K 750 S | 7 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 11.9 J impact energy
- Powerful 1550 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Fullwave electronics for precise power adjustment to application
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 750 S	
Power input (W)	1550
No load speed (rpm)	300
Blow energy (EPTA(J))	11.9
Full load hammer action (bpm)	2740
Full load speed (soft hammer) (rpm)	240
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
Max. drilling core bit (mm)	150
Tool reception	SDS-Max
Vibration drilling (m/s ²)	9.5
Vibration chiseling (m/s ²)	9.1
Weight (kg)	8.2
Supplied in	Kitbox
Article Number	4933398600

K 545 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of drilling/chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for drilling/chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 545 S	
Power input (W)	1300
No load speed (rpm)	450
Blow energy (EPTA(J))	8.5
Full load hammer action (bpm)	2840
Full load speed (soft hammer) (rpm)	350
Max. drilling solid bit (mm)	45
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	100
Tool reception	SDS-Max
Vibration drilling (m/s ²)	13
Vibration chiseling (m/s ²)	9
Weight (kg)	6.7
Supplied in	Kitbox
Article Number	4933398200

K 540 S | 5 KG CLASS DRILLING AND BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 6.3 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of drilling/chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 540 S	
Power input (W)	1100
No load speed (rpm)	450
Blow energy (EPTA(J))	7.5
Full load hammer action (bpm)	3000
Full load speed (soft hammer) (rpm)	430
Max. drilling concrete (mm)	40
Max. drilling tunnel bit (mm)	65
Max. drilling core bit (mm)	105
Tool reception	SDS-Max
Vibration drilling (m/s ²)	16.8
Vibration chiseling (m/s ²)	16.7
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933418100

K 500 ST | 5 KG CLASS TRADESMAN BREAKING HAMMER

- Best power to weight ratio in its class - 7.5 J and 5.9 kg
- Powerful 1100 watt ensures maximum power, guarantees maximum possible durability
- Soft start for precise start of chiselling
- Low vibration construction enhances usage time per day
- Robust magnesium gear housing for tough environments, exact seat fitting of gear components and better cooling
- Roto-stop and multi position chisel function gives 12 different positions to optimise working angle
- Safety clutch protects operator and machine if drill bit jams
- Soft grip main side handle
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 4 m cable



K 500 ST	
Power input (W)	1100
Blow energy (EPTA(J))	7.5
Full load hammer action (bpm)	3000
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	16.7
Weight (kg)	5.9
Supplied in	Kitbox
Article Number	4933443180

K 500 S | 5 KG CLASS BREAKING HAMMER

- Large, heavy weight striker delivers maximum 8.5 J impact energy
- Powerful 1300 watt ensures maximum power yet due to better heat dissipation, guarantees maximum possible durability
- Constant electronic for keeping the speed uniform even under load
- Soft start for precise start of chiselling
- AVS (Anti-Vibration-System) and soft grip on front and back handle
- Additional handle can be fixed in 3 different positions
- Soft hammer mode reduces blow energy for chiselling in sensitive materials
- Roto-stop and multi-position chisel function
- Service indicator light
- Variolock (12 positions) for selecting the most appropriate chisel angle
- 6 m cable



K 500 S	
Power input (W)	1300
Blow energy (EPTA(J))	8.5
Full load hammer action (bpm)	2840
Tool reception	SDS-Max
Vibration chiseling (m/s ²)	11.5
Weight (kg)	6.3
Supplied in	Kitbox
Article Number	4933398220

REPLACEMENT 400 MM LONG SDS-MAX POINTED CHISEL

Article Number 4932455144



PCE 3/K | 3 KG SDS-PLUS CHIPPING HAMMER

- Over sized heavy weight striker delivers 3.6 joules of impact energy
- 720 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Fully insulated metal gearbox for maximum stability
- Lightweight, ergonomic front handle is fully adjustable and can be securely fixed in the best position to suit the required drilling angle
- AVS (Anti-Vibration-System) and soft grip for less tiring operation
- Lock-on switch for more comfortable extended use
- Variolock (35 positions) for setting the face of the chisel
- 4 m cable



PCE 3/K	
Power input (W)	720
Blow energy (EPTA(J))	3.6
Full load hammer action (bpm)	0 - 3650
Tool reception	SDS-Plus
Weight (kg)	3.7
Supplied in	Kitbox
Article Number	4933384300

DD 3-152 | 3-SPEED COMBI DIAMOND DRILL

- Powerful 1900 watt motor
- Optimum speed range to drive small and large core bits
- Soft start with stepless speed control
- LED thermal motor temperature protection indicator
- Safety clutch
- Quick-in connection - secure motor fixing connection for ease of use and minimum vibration
- L shaped handle for better weight distribution
- 3-speed gearbox
- 5 m cable with PRCD
- Supplied with dust extraction connector, 32 mm and 41 mm spanners



DD 3-152	
Power input (W)	1900
Full load speed (rpm)	590 / 1250 / 2700
Max. drilling concrete (mm)	152
Max. drilling masonry (mm)	202
Tool reception	1/2" G + 1 3/8" UNC
Weight (kg)	6.5
Supplied in	Kitbox
Article Number	4933428000

DR 152 T | DIAMOND DRILL STAND FOR DD 3-152

- Cast aluminium base for easy transportation
- 45° tilt for angle drilling
- Quick-in connection - precise and quick connection of tool and rig
- Compact base - saves space for drilling in confined spaces
- 4 leveling screws for fast adjustment
- Horizontal and vertical spirit levels
- Transport handle
- Locking knob locks unit at highest position to aid fixing of machine and core bit
- Two spoke wheel feed for left and right hand operation
- Vacuum plate is available as accessory (4932352676)



DR 152 T	
Max. drilling core bit (mm)	152
Base size (mm)	330 x 210
Angle capacity (°)	45
Weight (kg)	10
Supplied in	No kitbox or bag supplied
Article Number	4933428020

VACUUM PLATE

Article Number	4932352676
----------------	------------



DCM 2-350 C | DIAMOND DRILLING MOTOR

- Two-speed diamond coring motor
- Internal slip clutch
- Triple-reduction gearing
- Soft start switch
- Motor overload protection
- PRCD residual current device
- Built-in water swivel
- Dual-mount switch box
- Supplied with open end wrench, Hex keys and strap with switch box



DCM 2-350 C	
Power input (W)	2800
No load speed gear 1 (rpm)	300
No load speed gear 2 (rpm)	600
Max. drilling core bit (mm)	350
Tool reception	1 1/4" UNC
Weight (kg)	9.0
Supplied in	No kitbox or bag supplied
Article Number	40044

DR 350 T | DIAMOND DRILL STAND FOR DCM 2-350 C

- Light weight drilling rig from aluminium
- Tilting (0 - 45°)
- Drill angle and depth display
- Quick-connect motor plate
- Fine adjustment of feed speed
- Vertical and horizontal water level
- Drill hole centering device
- Leveling screws
- Feed handle attachable to both sides of rig
- Transportable handle & wheels
- Supplied with 3/16" Hex key, 6 mm Hex key, 17 x 19 wrench, quick-connect motor plate, 4 pcs. M8 x 25 mm screws, centering device



DR 350 T	
Max. drilling core bit (mm)	350
Stroke length (mm)	610
Height (mm)	1042
Base size (mm)	391 x 523
Angle capacity (°)	45
Weight (kg)	19.5
Supplied in	No kitbox or bag supplied
Article Number	4933400600

DCM 2-250 C | DIAMOND DRILLING MOTOR

- Two-speed diamond coring motor
- Internal slip clutch
- Triple-reduction gearing
- Soft start switch
- Motor overload protection
- PRCD residual current device
- Built-in water swivel
- Dual-mount switch box
- Supplied with open end wrench, Hex keys and strap with switch box



DCM 2-250 C	
Power input (W)	2800
No load speed gear 1 (rpm)	450
No load speed gear 2 (rpm)	900
Max. drilling core bit (mm)	250
Tool reception	1 1/2" UNC
Weight (kg)	9.0
Supplied in	No kitbox or bag supplied
Article Number	40964

DR 250 TV | DIAMOND DRILL STAND FOR DCM 2-250 C

- Light weight drilling rig from aluminium
- Tilting (0 - 45°)
- Drill angle and depth display
- Quick-connect motor plate
- Integrated vacuum base plate (use with and without vacuum possible)
- Fine adjustment of feed speed
- Vertical and horizontal water level
- Drill hole centering device
- Leveling screws
- Feed handle attachable to both sides of rig
- Supplied with 3/16" Hex key, 6 mm Hex key, 17 x 19 wrench, quick-connect motor plate, 4 pcs. M8 x 25 mm screws, centering device, vacuum rubber seal



DR 250 TV	
Max. drilling core bit (mm)	250
Stroke length (mm)	520
Height (mm)	834
Base size (mm)	276 x 467
Angle capacity (°)	45
Weight (kg)	10.0
Supplied in	No kitbox or bag supplied
Article Number	4933400590

PLH 32 | 32 MM SDS-PLUS 3-MODE L-SHAPED HAMMER

- Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 3.9 joule single blow energy
- 900 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Electronics with accelerator switch
- Good balance and easy handling from the compact L-shape design with AVS (Anti-Vibration-System) and soft grip handle
- Fast tool changing from the FIXTEC™ system with keyless chuck
- Heavy Duty magnesium gear casing for optimum seating of gears for a longer operational life
- Reliable safety clutch protects machine and user
- Roto-stop and variolock for maximum control when doing light chiselling work
- 4 m cable



	PLH 32 XE	
Power input (W)	900	
Blow energy (EPTA)(J)	3.8	
Full load hammer action (bpm)	0 - 4500	
Full load speed (rpm)	0 - 800	
Max. drilling concrete (mm)	32	
Max. drilling steel (mm)	16	
Max. drilling wood (mm)	40	
Tool reception	SDS-Plus	
Vibration drilling (m/s ²)	22	
Vibration chiselling (m/s ²)	20	
FIXTEC™	Yes	
Weight (kg)	3.6	
Supplied in	Kitbox	
Article Number	4933400069	

PLH 28 | 28 MM SDS-PLUS 3-MODE L-SHAPED HAMMER

- Hardest hitting corded SDS hammer in its class. Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 4.1 joule single blow energy
- 800 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Low vibration 10.6 m/s² due to patented dual anti-vibration™ handle
- Good balance and easy handling from the compact L-shape design with dual patented AVS (Anti-Vibration-System) and soft grip handle
- Reliable safety clutch protects machine and user
- Roto-stop and variolock for maximum control when doing light chiselling work
- XE version comes with fast changing FIXTEC™ adaptor and 13 mm keyless chuck
- 4 m durable rubber cable
- Patent pending



	PLH 28 E	PLH 28 XE
Power input (W)	800	800
Blow energy (EPTA)(J)	4.1	4.1
Full load hammer action (bpm)	0 - 4000	0 - 4000
Full load speed (rpm)	0 - 1000	0 - 1000
Max. drilling concrete (mm)	28	28
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	40	40
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	10.6	10.6
Vibration chiselling (m/s ²)	6.8	6.8
FIXTEC™	No	Yes
Weight (kg)	3.4	3.6
Supplied in	Kitbox	Kitbox
Article Number	4933446790	4933446800

PH 30 | 30 MM SDS-PLUS 3-MODE HAMMER

- Over sized heavy weight striker delivers 3.6 joules of impact energy
- 1030 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Soft start for precise start of drilling/chiselling
- Low vibration due to ergonomic soft grip on main and side handle
- Soft hammer mode for drilling in sensitive materials
- Fast tool changing from FIXTEC™ system with keyless chuck
- Greatest durability in class is achieved by utilising integrated metal block technology in the gearing mechanism
- Brush rotation ring (for same power in forward & reverse action)
- Safety clutch protects machine and user if drill bit jams
- 4 m cable



	PH 30 POWER X	
Power input (W)	1030	
Blow energy (EPTA)(J)	3.6	
Full load hammer action (bpm)	0 - 3800	
Full load speed (rpm)	0 - 850	
Max. drilling concrete (mm)	30	
Max. drilling steel (mm)	13	
Max. drilling wood (mm)	40	
Tool reception	SDS-Plus	
Vibration drilling (m/s ²)	22	
Vibration chiselling (m/s ²)	14	
FIXTEC™	Yes	
Weight (kg)	2.9	
Supplied in	Kitbox	
Article Number	4933396420	

PH 28 | 28 MM SDS-PLUS 3-MODE HAMMER

- Over sized heavy weight striker delivers 3.4 joules of impact energy
- 820 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Soft start for precise start of drilling/chiselling
- Low vibration due to ergonomic soft grip on main and side handle
- Soft hammer mode for drilling in sensitive materials
- Greatest durability in class is achieved by utilising integrated metal block technology in the gearing mechanism
- Brush rotation ring (for same power in forward & reverse action)
- Safety clutch protects machine and user if drill bit jams
- X version comes with fast changing FIXTEC™ adaptor with keyless chuck
- 4 m cable



	PH 28	PH 28 X
Power input (W)	820	820
Blow energy (EPTA)(J)	3.4	3.4
Full load hammer action (bpm)	0 - 4000	0 - 4000
Full load speed (rpm)	0 - 900	0 - 900
Max. drilling concrete (mm)	28	28
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	22	22
Vibration chiselling (m/s ²)	16	16
FIXTEC™	No	Yes
Weight (kg)	2.7	2.9
Supplied in	Kitbox	Kitbox
Article Number	4933396396	4933396392

PH 26 T 26 MM SDS-PLUS 3-MODE HAMMER

- Tough, durable and compact hammer for drilling applications in masonry and concrete
- 2.4 J of impact energy delivering premium drill rate
- 800 W motor providing power for toughest applications
- Optimised for drilling 6 - 16 mm
- Safety clutch protects user if drill bit jams
- X version comes with FIXTEC™ adaptor and additional keyless chuck
- 4 m cable



3-mode selection



Safety clutch protects user if drill bit jams



Soft grip main side handle

	PH 26 T	PH 26 TX
Power input (W)	800	800
Blow energy (EPTA)(J)	2.4	2.4
Full load hammer action (bpm)	0 - 4500	0 - 4500
Full load speed (rpm)	0 - 1500	0 - 1500
Max. drilling concrete (mm)	26	26
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Tool reception	SDS-Plus	SDS-Plus
Vibration drilling (m/s ²)	13.6	13.6
Vibration chiselling (m/s ²)	11.9	11.9
FIXTEC™	No	Yes
Weight (kg)	2.4	2.6
Supplied in	Kitbox	Kitbox
Article Number	4933464580	4933464579

PFH 26 T | 26 MM SDS-PLUS 2-MODE FIXING HAMMER

- Tough, durable and compact hammer for drilling applications in masonry and concrete
- 2.4 J of impact energy delivering premium drill rate
- 800 W motor providing power for toughest applications
- Optimised for drilling 6 - 16 mm
- Safety clutch protects user if drill bit jams
- 4 m cable



	PFH 26 T
Power input (W)	800
Bow energy (EPTA(J))	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1500
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	13.6
FIXTEC™	No
Weight (kg)	2.4
Supplied in	Kitbox
Article Number	4933464581

PFH 26 | 26 MM SDS-PLUS 2-MODE FIXING HAMMER

- Most compact, slimline fixing hammer available in its class
- Unmatched performance with 2.4 J blow energy and 4500 bpm
- Lowest vibration at drilling into concrete: only 13.5 m/s²
- Extreme durability thanks to integrated metal block technology
- Innovative and patented internal weight reduction technology
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal
- Brush rotation ring (for same power in forward & reverse action)
- 4 m cable



	PFH 26
Power input (W)	725
Bow energy (EPTA(J))	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	13.5
FIXTEC™	No
Weight (kg)	2.4
Supplied in	Kitbox
Article Number	4933428230

PLH 20 | 20 MM SDS-PLUS 2-MODE L-SHAPED FIXING HAMMER

- Best power to weight ratio in its class - 2.0 J and 1.9 kg
- 820 watt motor combined with optimised drilling speed results in unsurpassed drilling performance
- Motor cooling airflow is designed in a way that blows drilling debris away from user when drilling overhead
- AVS (Anti-Vibration-System) for more comfortable use and less strain on the user
- Optimised hammer drilling 5 - 12 mm
- Safety clutch protects user and machine if drill bit jams
- Forward and reverse mechanism
- Soft grip handle for comfort
- 4 m cable



	PLH 20
Power input (W)	820
Bow energy (EPTA(J))	2.0
Full load hammer action (bpm)	0 - 4400
Full load speed (soft hammer) (rpm)	0 - 2700
Max. drilling concrete (mm)	20
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Tool reception	SDS-Plus
Vibration drilling (m/s ²)	10.2
FIXTEC™	No
Weight (kg)	1.9
Supplied in	Kitbox
Article Number	4933408070

DD 2-160 XE 2-SPEED DRY DIAMOND DRILL

- Powerful robust motor delivers constant high torque
- Dual protection from the interlocked mechanical and electronic clutches to protect both user and tool
- Robust construction with metal gearbox
- Safe handling from the long AVS side handle and "D-shaped" back handle
- 2-speed gear box
- M16 FIXTEC™ adaptor for fast core bit changing
- Soft hammer action - when activated allows the core bit to cut faster and easier
- Soft start via accelerator switch for precision and controlled drilling
- FIXTEC™ Cleanline rotor (additional accessory) the best solution for dust extraction
- 4 m cable
- Supplied with quick change adaptor for M16 diamond cores, SDS-plus pilot drill bit (6 x 140 mm)



	DD 2-160 XE
Power input (W)	1500
No load speed (rpm)	0 - 1500 / 0 - 3000
Full load speed (rpm)	0 - 850 / 0 - 1770
No load hammer stroke (rpm)	24,000 / 48,000
Max. drilling masonry (mm)	162
Max. static stalling torque (Nm)	50
Tool reception	M18 x 2.5
Weight (kg)	4.2
Supplied in	Kitbox
Article Number	4933368690

82 MM M16 DIAMOND CORE

Article Number **4932371976**



Safe handling from the long AVS side handle and „D-shaped“ back handle



M16 FIXTEC™ adaptor for fast core bit changing



FIXTEC™ Cleanline rotor (additional accessory) the best solution for dust extraction

SYSTEM ATTACHMENTS - WET DIAMOND DRILLING

Description	Fits DD3-152	Fits DCM2-250C & DCM2-350C	Fits MXF DCD150	Article Number	
Fixing kit. For exclusive use in concrete. Ø 16 mm drill bit is required to set the drop anchor	✓	✓	✓	4932399731	
Stud bolt, setting tool, wing nut, washer and 5 pcs M12 drop anchor					
1 1/4" open ended spanner. For holding the motor output spindle while removing a core bit					
32 mm ended spanner. For holding the motor output spindle while removing a core bit.					
41 mm open ended spanner. For removing the core bit from the motor spindle.					
Fixtec release. Suitable for all diamond motors with 1 1/4" spindle reception. Prevents the core bit from locking itself too tight onto the machine spindle. The core bits can then be released and removed with minimum effort	✓	✓		4932352053	
1 1/4" female to 1/2" female adaptor. To enable the connection of <50 mm diamond core bits on a 1 1/4" machine spindle thread	✓	✓		4932352627	
1 1/4" female / male extension rod, length 300 mm	✓	✓	✓	4932399724	
1 1/4" female / male extension rod, length 500 mm	✓	✓	✓	4932399725	
Telescopic extension. Extension pole used to fix drill rig to the ground instead of anchor bolts. Maximum load of 500 kg and adjustable extension height from 1.8-2.9 m	✓	✓	✓	4932399732	
Vacuum pump VP6: For fastening of the diamond drill rig on smooth and even surfaces. Suction capacity: 650 mbar. Max. vacuum pressure: 6 m³/h / 100 l/min. Rated voltage: 220-240 V	✓	✓	✓	4932352094	
Vacuum plate. Replacement rubber seal 4931428665	✓			4932352676	
WT 10 water tank. 10 liters capacity, steel, water tank with inside and outside polyester coating. Reliable brass pump with a max. pressure bar of Ø bar. 2.5 m hose with quick connection system fits direct to Milwaukee® diamond drills	✓	✓	✓	4932399726	
Water collection ring. For use with drill rig DR 152 T. For use with max. Ø 152 mm core bits				4932352677	
Replacement rubber ring for DR 152 T				4932352678	
Water collection ring. For use with drill rig DR 250 T. For use with max. Ø 180 mm core bits			✓	4932399727	
Replacement rubber ring for DR 250 T			✓	4932399729	
Water collection ring. For use with drill rig DR 350 T. For use with max. Ø 300 mm core bits				4932399728	
Replacement rubber ring for DR 350 T				4932399730	

SYSTEM ATTACHMENTS - WET DIAMOND DRILLING

Description	Fits DD3-152	Fits DCM2-250C & DCM2-350C	Fits MXF DCD150	Article Number	
Spacer block T = 50 mm. Needs to be mounted between drill rig and motor cores > 250 mm and max. 350 mm. Included in drill rig DR 350 T		✓		4932399736	
Quick connection motor mounting plate. Included in both drill rigs DR 250 TY and DR 350 T		✓		4932399733	
Water collection ring. For universal use with diamond drilling tools. For use with max. Ø 152 mm core bits	✓	✓	✓	4932478073	

FIXTEC™ SOLUTION WITH DUST EXTRACTION

Description	Tool reception	Core reception	Article Number	
FIXTEC Clean Line Rector (CLR)	M16 x 2.5	1 1/4" UNC	4932352172	

FIXTEC™ SOLUTION WITHOUT DUST EXTRACTION

Description	Tool reception	Core reception	Article Number	
FIXTEC adaptor. Tool changing in seconds. No extra tool required	M16 x 2.5	M16	4932399174	
	11 mm Hex	M16	4932399220	

GUIDE ROD FOR DD3-152. REQUIRES SDS-PLUS PILOT DRILL BIT (Ø 8 X 110 MM)

Description	Article Number	
Guide rod for DD2-160. Supplied with locking screw (4931622432). Requires allen key (4931616044) and SDS-plus pilot drill bit (Ø 8 x 160 mm, 4932367071)	4932399173	
Guide rod for DD3-152. Requires SDS-plus pilot drill bit (Ø 8 x 110 mm, 4932307070)	4932352679	

AS 42 MAC

42 L M-CLASS DUST EXTRACTOR

- Compact 42 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class M, Standard MAK-factor > 0.1 mg/m³; mineral dust, wood dust (oak, beech)
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Airflow and filter monitoring with visual LED and acoustic warning signal
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Trolley handle for convenient transportation onto the job site
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 42 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	42
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	17.5
Supplied in	No kitbox or bag supplied
Article Number	4933459418



Durable PTFE filter



Power take off for auto switching of powertools



Trolley handle for convenient transportation onto the job site

AS 30 MAC | 30 L M-CLASS DUST EXTRACTOR

- Compact 30 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class M, Standard MAK-factor > 0.1 mg/m³; mineral dust, wood dust (oak, beech)
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Airflow and filter monitoring with visual LED and acoustic warning signal
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 30 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933459415

AS 30 LAC | 30 L L-CLASS DUST EXTRACTOR

- Compact 30 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class L, Standard MAK-factor > 1 mg/m³
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 36 mm



AS 30 LAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	36
Hose length (m)	4
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933459411

AS 2-250 ELCP | 25 L L-CLASS DUST EXTRACTOR

- Large 25 litre tank capacity ideal for workshop use
- 1000 W motor power with over 210 mbar suction - 10% more efficient
- Power take off with auto switching for powertools
- 2600W power take off capacity allows for use with high wattage tools
- Clear press filter cleaning system maintains suction efficiency
- Washable PET filter provides longer filter life
- Dust class L, Standard MAK-factor > 1 mg/m³
- Wet and dry capability
- Hose and cable storage enables easy transportation
- Dust blower function
- 7.5 m rubber cable
- Supplied with 3.5 m hose with floor cleaning kit, PET filter, 2x powertool connection adaptor, 1x disposable bag, 1x fleece bag & 1x crevice nozzle



AS 2-250 ELCP	
Power input (W)	1000
Air volume (l/min)	3600
Max. vacuum (mbar)	210
Capacity (l)	25
Hose diameter (mm)	32
Weight (kg)	10.4
Supplied in	No kitbox or bag supplied
Article Number	4933447480

METALWORKING



AGVM 26 | 2600 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- B-Guard protects both operator and machine from "kickback effect"
- Powerful, 2600 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- FIXTEC™ flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGVM 26-230 GEX	AGVM 26-230 GEX DMS
Power input (W)	2600	2600
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.8	5.8
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	Yes	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402365	4933402495

AGV 26 | 2600 W ANGLE GRINDER WITH AVS

- Powerful, 2600 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGV 26-230 GE	AGV 26-230 GE DMS
Power input (W)	2600	2600
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.5	5.5
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	No	No
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402360	4933402490

AGVM 24 | 2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- B-Guard protects both operator and machine from "kickback" effect
- Powerful, 2400 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- 7 position rotatable main handle
- FIXTEC™ flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGVM 24-230 GEX	AGVM 24-230 GEX DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.8	5.8
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	Yes	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402340	4933402475

AGVKB 24

2400 W ANGLE GRINDER WITH BRAKE, KICKBACK PROTECTION AND AVS

- Powerful 2400W large angle grinder with only 5.9 kg of weight for outstanding performance and handling
- RAPIDSTOP™ braking system: stops all accessories up to 50% faster than grinders without braking function
- Safety clutch to protect the user from kickback injuries
- AVS equipped motor housing, with 7 position rotatable main handle and additional AVS side handle for more comfortable handling and less strain on body joints
- Line lock out function to prevent automatic start up after power breakdown
- Removable dust screen to prevent debris entrance and to prolong motor life
- Soft start for smooth start up
- FIXTEC™ flange nut for fast and easy change of discs
- Keyless guard for fast guard adjustment without using a key
- External brush doors for easy access to the brushes and fast servicing
- Overload protection to prevent overheating

	AGVKB 24-230 EKK	AGVKB 24-230 EKK DMS	AGVKB 24-230 EKK DMS KIT
Power input (W)	2400	2400	2400
No load speed (rpm)	6500	6500	6500
Disc diameter (mm)	230	230	230
Max. cutting depth (mm)	68	68	68
Braking time (s)	< 0.5	< 0.5	< 0.5
Spindle size	M 14	M 14	M 14
Weight (kg)	5.9	5.9	5.9
Brake	Yes	Yes	Yes
Switch type	Trigger lock-on switch	Deadman switch	Deadman switch
FIXTEC™ flange nut	Yes	Yes	Yes
Line lock out function	Yes	Yes	Yes
AVS Anti-Vibration System	Yes	Yes	Yes
AVS side handle	Yes	Yes	Yes
Rotatable main handle	Yes	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	Kitbox
Article Number	4933471464	4933471463	4933471465



RAPID STOP



RAPIDSTOP™ braking system



FIXTEC™ flange nut



Removable dust screen

DUST GUARD FOR CUTTING

Article Number **4932459341**



AGVK 24 | 2400 W ANGLE GRINDER WITH AVS AND KICKBACK PROTECTION

- Powerful, 2400 W motor with powder field coating for increased life time and outstanding performance in all applications
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to protect the user from kickback injuries
- Overload protection to prevent overheating
- Soft start for smooth start up
- Extremely compact design with an overall length of 485 mm and 5.4 kg for most comfortable handling
- 2-position Anti-vibration side handle for less vibration and more comfortable work
- Burst resistant quick release safety guard for easy adjustment
- External brush doors for easy access to the brushes and fast servicing
- 4 m rubber cable



	AGVK 24-230 EK	AGVK 24-230 EK DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.4	5.4
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	No	No
Deadman switch	No	Yes
Line lock out function	Yes	Yes
AVS side handle	Yes	Yes
Rotatable main handle	No	No
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933451413	4933451414

AGV 24 | 2400 W ANGLE GRINDER WITH AVS

- Powerful, 2400 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints
- Lowest vibration in it's class with only 2.5 m/s²
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AGV 24-230 E	AGV 24-230 GE	AGV 24-230 GE DMS
Power input (W)	2400	2400	2400
No load speed (rpm)	6600	6600	6600
Disc diameter (mm)	230	230	230
Max. cutting depth (mm)	68	68	68
Spindle size	M 14	M 14	M 14
Weight (kg)	5.5	5.5	5.5
Brake	No	No	No
Switch type	Trigger lock-on switch	Trigger lock-on switch	Paddle (Deadman)
FIXTEC™ flange nut	No	No	No
Line lock out function	Yes	Yes	No
Autobalancer system	Yes	Yes	Yes
AVS Anti-Vibration System	Yes	Yes	Yes
Rotatable main handle	No	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402335	4933402330	4933402520

AG 24 | 2400 W ANGLE GRINDER

- Powerful, 2400 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Ergonomically designed motor housing for best user comfort
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AG 24-230 E	AG 24-230 E DMS
Power input (W)	2400	2400
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.3	5.3
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	No	No
Line lock out function	Yes	No
Autobalancer system	No	No
AVS Anti-Vibration System	No	No
Rotatable main handle	No	No
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402325	4933402450

DUST GUARD FOR CUTTING

Article Number: 4932459341



AGV 22 | 2200 W ANGLE GRINDER WITH AVS

- Powerful, 2200 W motor with powder field coating for long life time and outstanding performance in all applications
- Extreme compact design with an overall short length of 485 mm and 5.4 kg for most comfortable handling
- Soft start for smooth start up
- Burst resistant quick release safety guard for easy adjustment
- 2-positions Anti-vibration side handle for less vibrations to the user and more comfortable work
- External brush doors for easy access to the brushes for fast servicing
- 4 m rubber cable



	AGV 22-180 E	AGV 22-230 E	AGV 22-230 DMS
Power input (W)	2200	2200	2200
No load speed (rpm)	8500	6600	6600
Disc diameter (mm)	180	230	230
Max. cutting depth (mm)	43	68	68
Spindle size	M 14	M 14	M 14
Weight (kg)	5.3	5.4	5.4
Brake	No	No	No
Switch type	Trigger lock-on switch	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	No	No	No
Line lock out function	Yes	Yes	No
Autobalancer system	No	No	No
AVS side handle	Yes	Yes	Yes
Rotatable main handle	No	No	No
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933431820	4933431850	4933431860

DUST GUARD FOR CUTTING

Article Number: 4932459341



AG 22 | 2200 W ANGLE GRINDER

- Powerful, 2200 W motor with powder field coating for long life time and outstanding performance in all applications
- Extreme compact design with an overall short length of 485 mm and 5.2 kg for most comfortable handling
- Burst resistant keyed safety guard
- External brush doors for easy access to the brushes for fast servicing



DUST GUARD FOR CUTTING, DELIVERED WITH KEYPED GUARD RECEPTION AND QUICK DUST CONNECTOR. FITS MILWAUKEE® AG 22.

Article Number:

4932459340



AGV 21 GEX | 2100 W ANGLE GRINDER WITH AVS

- Powerful, 2100 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Autobalancer for greatly reduced vibration of bad discs
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain on body joints
- 7 position main handle
- Soft start for smooth start up
- FIXTEC™ flange nut for fast and easy change of discs
- Burst resistant quick release safety guard for easy adjustment
- Automatic cut-off carbon brushes
- 4 m rubber cable



	AG 22-180 DMS	AG 22-230 DMS
Power input (W)	2200	2200
No load speed (rpm)	8500	6600
Disc diameter (mm)	180	230
Max. cutting depth (mm)	43	68
Spindle size	M 14	M 14
Weight (kg)	5.1	5.2
Brake	No	No
Switch type	Deadman switch	Deadman switch
FIXTEC™ flange nut	No	No
Line lock out function	No	No
Autobalancer system	No	No
AVS side handle	No	No
Rotatable main handle	No	No
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933431830	4933433630

	AGV 21-230 GEX	AGV 21-230 GEX DMS
Power input (W)	2100	2100
No load speed (rpm)	6600	6600
Disc diameter (mm)	230	230
Max. cutting depth (mm)	68	68
Spindle size	M 14	M 14
Weight (kg)	5.5	5.5
Brake	No	No
Switch type	Trigger lock-on switch	Deadman switch
FIXTEC™ flange nut	Yes	Yes
Line lock out function	Yes	No
Autobalancer system	Yes	Yes
AVS Anti-Vibration System	Yes	Yes
Rotatable main handle	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933402304	4933402525

AGV 17 INOX | 1750 W LOW SPEED GRINDER WITH AVS

- Powerful, 1750 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- 7 position variable speed selection from 2000 - 7600 RPM's for best results on stainless steel
- Constant power electronics with soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Thermal overload protection to prevent overheating
- Safety clutch to protect the user from kickback injuries
- FIXTEC™ nut for tool-free disc change
- Burst resistant and tool-free safety guard for best user protection and fast adjustment
- Anti-vibration side handle for lower vibration
- 4 m rubber cable



	AGV 17-125 INOX
Power input (W)	1750
No load speed (rpm)	2000 - 7600
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2.8
Variable speed	Yes
Brake	No
Switch type	Trigger lock-on switch
FIXTEC™ flange nut	Yes
Line lock out function	Yes
Supplied in	No kitbox or bag supplied
Article Number	4933449870

AGV 13 XSPDE | 1250 W ANGLE GRINDER WITH AVS AND SLIM PADDLE SWITCH

- Powerful, 1250 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Most compact design with only 160 mm body size for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to protect the user from kickback injuries
- Integrated and innovative FIXTEC™ tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue



AGV 13-125 XSPDE	
Power input (W)	1250
No load speed (rpm)	12,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2,5
Brake	No
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Line lock out function	Yes
AVS side handle	Yes
Supplied in	No kitbox or bag supplied
Article Number	4932451578

DUST GUARD FOR CUTTING Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.

Article Number: 4932430467



AG 13 XSPD | 1250 W ANGLE GRINDER WITH SLIM PADDLE SWITCH

- Powerful, 1250 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Most compact design with only 160 mm body size for comfortable handling
- Integrated and innovative FIXTEC™ tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- 4 m rubber cable



AG 13-125 XSPD	
Power input (W)	1250
No load speed (rpm)	12,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2,3
Brake	No
Switch type	Paddle (Deadman) switch
FIXTEC™	Yes
Line lock out function	No
Supplied in	No kitbox or bag supplied
Article Number	4933451577

DUST GUARD FOR CUTTING Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.

Article Number: 4932430467



AGV 12 | 1200 W ANGLE GRINDER WITH AVS

- Powerful, 1200 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Soft start for smooth start up
- Line lock out function to prevent automatic start up after power breakdown
- Overload protection to prevent overheating
- Safety clutch to protect the user from kickback injuries
- New integrated and innovative FIXTEC™ tool-free disc change system
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Anti-vibration side handle for less user fatigue
- 4 m rubber cable



ADV 12-125 X	
Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2,4
Brake	No
Switch type	Slide lock-on switch
FIXTEC™	Yes
Line lock out function	Yes
Supplied in	No kitbox or bag supplied
Article Number	4933428095

DUST GUARD FOR CUTTING Ø115 - 125 MM AG(V) 12, AGV 13, AGV 15 SERIES AND FUEL™ GRINDERS.

Article Number: 4932430467



AGV 10 EK | 1000 W ANGLE GRINDER WITH AVS

- Powerful, 1000 W motor for strong performance in all applications
- Extreme compact design with an overall short length of 276 mm and 2.2 kg for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Anti-vibration side handle for less fatigue
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Ramped slide switch for easy start up, even when wearing gloves
- 4 m cable



AGV 10-125 EK	
Power input (W)	1000
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	33
Spindle size	M 14
Weight (kg)	2,2
Brake	No
Switch type	Slide lock-on switch
FIXTEC™ flange nut	No
Line lock out function	Yes
Supplied in	No kitbox or bag supplied
Article Number	4933451222

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

Article Number: 4932451487



AG 10 EK | 1000 W ANGLE GRINDER

- Powerful, 1000 W motor for strong performance in all applications
- Extreme compact design with an overall short length of 276 mm and 2.1 kg for most comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Soft start for smooth start up
- Burst resistant and tool-free quick release safety guard for fast adjustment
- Ramped slide switch for easy start up, even when wearing gloves
- 4 m cable



AG 10-115 EK	AG 10-125 EK	
Power input (W)	1000	1000
No load speed (rpm)	11,000	11,000
Disc diameter (mm)	115	125
Max. cutting depth (mm)	28	33
Spindle size	M 14	M 14
Weight (kg)	2,1	2,1
Brake	No	No
Switch type	Slide lock-on switch	Slide lock-on switch
FIXTEC™ flange nut	No	No
Line lock out function	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933451219	4933451220

THIN METAL CUTTING DISC PRO+, SCS 41 / 125, 1 MM THICKNESS, 22.2 MM BORE SIZE

Article Number: 4932451487



AG 9 | 850 W ANGLE GRINDER

- Powerful, 850 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Light weight, slim and compact: a versatile all-purpose angle grinder
- New digital electronic pack offers constant speed, soft start, motor overload protection and no-load speed limitation
- Flat metal gear head for excellent visibility of work piece and optimised cutting depth
- Die-cast magnesium alloy gear case
- Dust protected bearings and switch
- Effective cooling fan keeps the motor cool even under heavy duty conditions
- FIXTEC™ nut for fast and easy disc change
- Burst resistant quick release safety guard for easy adjustment
- Automatic off-carbon brushes
- 4 m rubber cable



AG 9-125 XC	AG 9-125 XE	
Power input (W)	850	850
No load speed (rpm)	10,000	2,700 - 10,000
Disc diameter (mm)	115	125
Max. cutting depth (mm)	33	33
Spindle size	M 14	M 14
Weight (kg)	1,8	1,8
Variable speed	No	Yes
Brake	No	No
Switch type	Slide lock-on switch	Slide lock-on switch
FIXTEC™ flange nut	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	No kitbox or bag supplied	No kitbox or bag supplied
Article Number	4933403200	4933403206

HOBL 7000 | HIGH OUTPUT BAY LIGHT

- TRUEVIEW™ high definition lighting - 7700 Lumens of even light output for best jobsite illumination (110 Lumens / Watt)
- Impact resistant polycarbonate lens withstands drops from up to 2.7 m
- Integrated wiring terminal accepts voltages from 90 - 277 V, allows easy wiring and stringing of multiple lights
- Wire strain relief accepts cables up to H07RNF 3 x 2.5 mm²
- Spring-loaded cable retention allows easy adjustment of installation height with 1.2 m steel hanging cable
- 4 m AC power cord for out of the box operation
- Conical lens design and small footprint allow simple storage and safe stacking of up to 3 units



TRUEVIEW™

HOBL 7000

Voltage (AC) (V)	90 - 277
Bulb type	LED
Weight (kg)	3.7
Supplied in	No kitbox or bag supplied
Article Number	4933464126

MXF TL MX FUEL™ TOWER LIGHT



- TRUEVIEW™ high definition light output with up to 27,000 Lumens in AC and up to 20,000 Lumens in DC mode for both task and area lighting
- Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed
- Low weight of 48 kg with the two big all-terrain wheels, this tower light is easy to transport across wet and uneven job site terrains with minimum effort
- Due to the motorised mast, the tower light is capable to be set up in less than 10 sec. The mast is extendable up to 3.10 meter and can withstand up to 55 km/h of wind
- To withstand the toughest conditions on the toughest job sites, the MX FUEL™ Tower Light is built with a durable, high impact polycarbonate lenses that delivers superior impact durability
- A sealed battery box ensures batteries are kept protected from the elements at all times
- Integrated ONE-KEY™ application for customise, track, and manage from your mobile device. Easy to set the run time which will adjust the output to give constant illumination for the job at hand, and check the remaining battery charge to know when it's time to change the battery

TRUEVIEW™ ONE-KEY™

UNLOCKING THE DIGITAL JOBSITE.™



Due to the motorised mast, the tower light is capable to be set up in less than 10 sec



Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed



A sealed battery box ensures batteries are kept protected from the elements at all times

MXF TL-601

System	MX FUEL™
Battery compatibility	All MX FUEL™ batteries
Bulb type	LED
Max. AC light output High/Medium/Low/ Strobe (Lumens)	27,000/ 14,000/ 7000/ -
Max. DC light output High/Medium/Low/ Strobe (Lumens)	20,000/ 10,000/ 5000/ -
Max. run time AC mode (h)	Endless
Max. run time DC mode (h)	3/ 6/ 12
Max. mast height (m)	3.1
Weight with battery pack (kg)	48.0
Kit included	1 x MXF XC406 Battery pack, Integrated Charger, No kitbox or bag supplied
Article Number	4933471844

CS 60 | 184 MM CIRCULAR SAW (61 MM DOC)

- 1600 W powerful motor with 5800 rpm for fast cutting through tough materials
- Large cutting capacity of 61 mm
- 0 - 56° bevel capacity and 45° positive stop
- Quick release locking lever design for fast bevel adjustments
- Integrated dust blower keeps cut line clear
- Large, ergonomic handles and levers for improved ergonomics and control
- Long side fence for straight cuts and precise guidance
- Supplied with a carbide tipped 24 tooth saw blade, parallel guide and 4 m cable



CS 60	
Power input (W)	1600
No load speed (rpm)	5800
Blade diameter (mm)	184
Max. cutting depth 45° (mm)	49
Max. cutting depth 90° (mm)	61
Bore size (mm)	30
Weight (kg)	4.8
Supplied in	No kitbox or bag supplied
Article Number	4933419225

184 X 30 MM 40 TOOTH CIRCULAR SAW BLADE WITH 2.1 MM CUTTING WIDTH

Article Number 4932471298



BS 100 LE | 4" (100 MM) BELT SANDER

- Compact design, ideal for sanding close to edges
- Sanding surface 100 x 160 mm, for fast smooth sanding
- Variable preselection of belt speed for versatile use
- Control wheel for precise adjustment of belt alignment
- Integrated dust extraction and dust bag for dust free work and less sanding belt wear
- Easy changing of sanding belt
- Stationary work possible
- Supplied with 100 x 620 mm sanding belt (grit 100) and 4 m cable



BS 100 LE	
Power input (W)	1150
Belt speed (rpm)	230 - 400
Belt length (mm)	620
Belt width (mm)	100
Sanding surface (mm)	100 x 160
Weight (kg)	5.3
Supplied in	No kitbox or bag supplied
Article Number	4933385150

SANDING BELT - 5 PCS, 100 X 610 MM, 60 GRIT

Article Number 4932355067



ROS 125 E | 5" (125 MM) RANDOM ORBIT SANDER

- Ideal for sanding of wood, metal and plastics within confined spaces
- 300 Watt powerful motor with 2,4 mm orbital action
- Variable speed (7000-12,000 rpm) - especially needed for heat-sensitive materials
- Hook & Loop paper fitment
- Excellent dust extraction - 90% dust collection efficiency with larger dust bag
- Easy to clean dust bag
- On board vac adaptor- fits standard 36 mm vacuum hoses
- Supplied with textile dust bag and sanding paper set (60, 80, 120 grit)



ROS 125 E	
Power input (W)	300
No load speed (rpm)	7000 - 12,000
Oscillation rate (rpm)	14,000 - 26,000
Oscillation diameter (mm)	2.4
Sanding pad size (mm)	125
Weight (kg)	1.7
Supplied in	Tool bag
Article Number	4933433180

Ø 125 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932367741



ROS 150 E-2 6" (150 MM) RANDOM ORBIT SANDER

- Random orbital sander with unmatched sanding properties through simultaneous rotation and oscillation of sanding disc
- Reduction gear makes full, efficient use of the powerful 440 W motor
- 6.4 / 3.2 mm orbits for fast removal & finishing
- Variable speed (4000-10,000 rpm) - especially needed for heat-sensitive materials
- Fast and easy change of sandpaper with hook and loop system
- Removable dustbag and also fits standard 26 mm vacuum hose
- Through body sealed slide switch
- Additional handle for a balanced and even weight distribution over the work piece
- Supplied with a dust bag, sanding disc and 4 m cable



ROS 150 E-2	
Power input (W)	440
No load speed (rpm)	4000 - 10,000
Oscillation diameter (mm)	6.4 / 3.2
Sanding pad size (mm)	150
Weight (kg)	2.3
Supplied in	No kitbox or bag supplied
Article Number	4933431170

Ø 150 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932371691



Variable speed selection (4000-10,000 rpm)



Hook and loop change system



Additional handle for weight distribution

SPS 140 | 1/4" SHEET SANDER

- Powerful 260 W motor for sustained use
- 1.6 mm oscillation movement allows for fine sanding
- Quick connection to dust extractor or dust bag
- Sanding paper is attached by hook and loop or by a clamping system
- 4 m of durable rubber cable allows the user to move easily around his work piece



SPS 140	
Power input (W)	260
No load speed (rpm)	14,700
Oscillation rate (rpm)	28,000
Oscillation diameter (mm)	1.6
Sanding pad size (mm)	113 x 105
Weight (kg)	1.6
Supplied in	No kitbox or bag supplied
Article Number	4933447015

M18 FBS85

M18 FUEL

M18 FUEL™ COMPACT BAND SAW

- o 20% faster cutting compared to previous model
- o Large cutting capacity up to a diameter of 85 mm
- o Variable speed trigger for quick & easy speed adjustments
- o Band saw cover protects user from injuries by preventing any access to the blade - tool-free installation and removal within seconds
- o Tool-free blade locking mechanism for quick and easy saw blade changes
- o Dual action trigger to prevent accidental trigger actuation
- o Tool-free & lockable adjustable shoe
- o Solid metal rafter hook for easy jobsite storage
- o Integrated LED light for workspace illumination
- o Supplied with band saw covers and 12/14 TPI premium blade
- o Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- o Flexible battery system: works with all MILWAUKEE® M18™ batteries



Variable speed trigger for quick & easy speed adjustments



Tool-free installation and removal of the band saw cover




Tool-free blade locking mechanism for quick and easy saw blade changes

	M18 FBS85-0C	M18 FBS85-202C
No load speed (m/min)	0 - 165	0 - 165
Cutting capacity rect. stock (mm)	85	85
Blade length (mm)	898.52	898.52
Weight with battery pack (kg)	-	3.9
Kit included	No batteries supplied, No charger supplied, Kitbox	2 x M18 B2 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933471496	4933471497

PREMIUM 898.52 MM WITH TOOTH PITCH 12/14 BANDSAW BLADE (3 PCS) FOR MATERIALS 4 - 8 MM THICK

Article Number

48390619



M18 CBS125 | M18 FUEL™ DEEP CUT BAND SAW

M18 FUEL

- o Brushless POWERSTATE™ motor provides corded cutting performance with up to 10x more motor life and up to 2x more run time compared to other cordless solutions
- o REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- o REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- o Largest cutting capacity up to 125 x 125 mm material diameter
- o 5 step variable speed selection from 0 - 116 m/min
- o Tool-free blade locking mechanism for quick and easy saw blade changes
- o Solid metal rafter hook for quick and easy jobsite storage
- o Slim full metal motor housing design and LED work surface illumination for best cut visibility
- o Flexible battery system: works with all MILWAUKEE® M18™ batteries



	M18 CBS125-0	M18 CBS125-502C
No load speed (m/min)	0 - 116	0 - 116
Cutting capacity rect. stock (mm)	125 x 125	125 x 125
Blade length (mm)	1139.83	1139.83
Weight with battery pack (kg)	-	7.3
Kit included	No batteries supplied, No charger supplied, No kitbox or bag supplied	2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox
Article Number	4933447150	4933448195

BAND SAW COVER FOR M18 CBS125 & BS 125

Article Number

4932471459



M18 FMCS66

M18 FUEL™ 66 MM METAL CIRCULAR SAW

- First 18V cordless metal circular saw with 66 mm cutting depth and 1800 W corded performance
- Faster cutting speed compared to corded unit
- Shoe designed to connect directly on MILWAUKEE® guide rail (sold separately). This allows the user to make straight and accurate cuts with minimum setup time
- Performance light indicates when the device is pushed to hard
- Electric break stops blade in under 1 sec
- Large metal chip collector captures debris produced while cutting and provides needed visibility
- Dry-cutting technology provides fast, clean and burr-free metal cutting
- Dual-action trigger prevents any accidental start up
- Tool-free cutting depth adjustment and plunge lever for fast and effective plunge cuts
- Exclusive chip-release shield latch for fast waste disposal and blade changing
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



Performance light indicates when the device is pushed to hard



Large metal chip collector captures debris produced while cutting and provides needed visibility



Tool-free cutting depth adjustment and plunge lever for fast and effective plunge cuts

	M18 FMCS66-0C	M18 FMCS66-121C
No load speed (rpm)	4000	4000
Blade diameter (mm)	203	203
Bore size (mm)	15.87	15.87
Max. cutting depth (mm)	66	66
Weight with battery pack (kg)	-	7.5
Kit included	No batteries supplied, No charger supplied, Kitbox	1 x M18 HB12 Battery pack, M12-18 FC Charger, Kitbox
Article Number	4933472110	4933472111

GRU 1400, 1400 MM GUIDE RAIL, SUPPLIED WITH CARRY BAG

Article Number **4932451265**



M18 FMCS | M18 FUEL™ 57 MM METAL CIRCULAR SAW

- Brushless POWERSTATE™ motor for fast cutting, longest tool life and up to 370 cuts in 3/4" EMT
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Cold cuts - reduces sparks for increased jobsite safety
- Tool-free depth adjustment, quickly and easily adjusts cutting depth from 0 to 57 mm
- Compact and light weight design for most comfortable use
- Integrated rafter hook for easy storage between uses
- On board allen key storage for easy access and preventing losing the key
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 150 mm 34 teeth metal cutting blade



	M18 FMCS-0X	M18 FMCS-502X
No load speed (rpm)	3900	3900
Blade diameter (mm)	150	150
Bore size (mm)	20	20
Max. cutting depth (mm)	57	57
Weight with battery pack (kg)	-	2.8
Kit included	No batteries supplied, No charger supplied, HD Box	2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box
Article Number	4933459192	4933459193

150 X 20 MM 34 TOOTH METAL CUTTING BLADE WITH 1.6 MM CUTTING WIDTH

Article Number **48404215**



SSPE 1500 X 1500 W SUPER SAWZALL™

- 1500 W motor - highest overload protection in the industry; prevents motor burn up/failure
- Constant power technology - maintains constant speed under load for unmatched cutting performance
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC™ blade clamp system - provides fast and easy blade changes
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL™ blade, additional keyed blade clamp and 4 m cable



SSPE 1500 X	
Power input (W)	1500
No load stroke rate (spm)	0 - 2800
Stroke length (mm)	32
Weight (kg)	4.5
Supplied in	Kitbox
Article Number	4933428900

AX™ CARBIDE TEETH DEMOLITION BLADE, 230 MM BLADE LENGTH, 5 TPI

Article Number **48005226**



FIXTEC™ blade clamp system & adjustable shoe



Counter balance mechanism ensures low vibrations - 12.5 m/s²



Orbital action

SSPE 1300 RX | 1300 W SAWZALL™ WITH ROTATING HANDLE

- High cutting performance due to powerful 1300 watt motor combined with a 32 mm saw stroke
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- 360° rotating handle for optimal user comfort
- FIXTEC™ blade clamp system - provides fast and easy blade changes
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 12.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL™ blade and 4 m cable



SSPE 1300 RX	
Power input (W)	1300
No load stroke rate (spm)	0 - 3000
Stroke length (mm)	32
Weight (kg)	4.2
Supplied in	Kitbox
Article Number	4933440590

AX™ CARBIDE TEETH DEMOLITION BLADE, 230 MM BLADE LENGTH, 5 TPI

Article Number **48005226**



SSPE 1300 SX | 1300 W SAWZALL™

- High cutting performance due to powerful 1300 watt motor combined with a 32 mm saw stroke
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups
- FIXTEC™ blade reception as well as change kit to keyed blade change
- Patented AVS Anti-Vibration-System ensures unsurpassed low-vibration running at 14.5 m/s²
- Variable speed trigger and dial speed control - maximum speed control
- Adjustable shoe for optimised use of saw blades
- Supplied with a SAWZALL™ blade, additional keyed blade clamp and 4 m cable



SSPE 1300 SX	
Power input (W)	1300
No load stroke rate (spm)	0 - 2800
Stroke length (mm)	32
Weight (kg)	3.9
Supplied in	Kitbox
Article Number	4933428520

SAWZALL® BLADE SET

Article Number **49222229**



SSD 1100 X | 1100 W SAWZALL™

- High cutting performance due to powerful 1100 watt motor combined with a 28 mm saw stroke
- FIXTEC™ blade clamp for fast and easy blade changes without any key
- Water & finger protection nose for safer work and better rust protection
- Variable speed trigger switch
- Durable long lasting slider mechanism
- Supplied with a SAWZALL™ blade and 4 m cable



SSD 1100 X	
Power input (W)	1100
No load stroke rate (spm)	0 - 2900
Stroke length (mm)	28
Weight (kg)	3.2
Supplied in	Kitbox
Article Number	4933416710

SAWZALL® BLADE SET

Article Number **49222229**



FSPE 110 X | HEAVY DUTY BODY GRIP JIGSAW

- Very slim motor housing for easy grip in any application and excellent view on the cutting line
- Powerful 710 W motor
- Precision blade guidance for precise cuts
- Patented FIXTEC™ system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Electronic with variable speed pre-selection, soft start and constant speed under load
- Four-stage pendulum action adjustment for even more powerful cutting performance and longer saw blade life
- Adjustable chipping blower to the front and rear
- Low vibration and smooth operation due to anti-vibration technology
- Supplied with 5 saw blades, anti-splintering device, dust cap, absorption adaptor, sliding shoe and 4 m cable



FSPE 110 X	
Power input (W)	710
No load stroke rate (spm)	500 - 3000
Max. cutting capacity wood (mm)	120
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.5
Supplied in	Kitbox
Article Number	4933357990

75 X 2.5 MM T 101 B JIGSAW BLADE, 5 PCS

Article Number **4932254061**



JSPE 135 | HEAVY DUTY TOP HANDLE JIGSAW

- Robust and powerful top handle jig saw for fast cutting action in wood, aluminium, steel or ceramics
- Powerful 750 W motor
- Precision blade guidance for precise cuts
- Patented FIXTEC™ system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Electronic with variable speed preselection, soft start and constant speed under load
- Four-stage pendulum action adjustment for even more powerful cutting performance and longer saw blade life
- Adjustable chipping blower to the front and the rear
- LED light for illumination of cutting area
- Supplied with 5 saw blades, anti-splintering device, dust cap, absorption adaptor, sliding shoe and 4 m cable



JSPE 135 TX	
Power input (W)	750
No load stroke rate (rpm)	800 - 3000
Max. cutting capacity wood (mm)	135
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.5
Supplied in	Kitbox
Article Number	4933361230

5 PCS JIGSAW BLADE SET SUITABLE FOR APPLICATIONS IN WOOD AND METAL

Article Number 4932345825



JS 120 X | HEAVY DUTY BODY GRIP JIGSAW

- Slim, streamlined motor housing design and optimised weight for easy handling
- Powerful 710 W motor
- Patented FIXTEC™ system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°
- Digital electronics with variable speed preselection, soft start and constant speed under load
- 4 stage pendulum action for increased performance
- Excellent visibility of saw blade and cutting area
- Integrated-Metal-Block technology - robust metal casing for bearings, gears and base plate for maximum durability and stability
- Anti-vibration mechanism for lowest possible vibration
- Integrated dust extraction
- Supplied with 5 saw blades, anti-splintering device, dust cap, sliding shoe and 4 m cable



JS 120 X	
Power input (W)	710
No load stroke rate (rpm)	500 - 2800
Max. cutting capacity wood (mm)	120
Max. cutting capacity steel (mm)	10
Max. cutting capacity aluminium (mm)	30
Mitre capacity (°)	45
Stroke length (mm)	26
Weight (kg)	2.3
Supplied in	Kitbox
Article Number	4933361680

5 PCS JIGSAW BLADE SET SUITABLE FOR APPLICATIONS IN WOOD AND METAL

Article Number 4932345825



CS 85 SB | 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- Soft start minimises the tripping of circuit breakers
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw
- Aluminium stamped base for strength and durability
- Spindle lock for easy and quick blade change



CS 85 SB	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	50
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	6.6
Supplied in	No kitbox or bag supplied
Article Number	4933451117

235 X 30 MM 36 TOOTH CIRCULAR SAW BLADE WITH 2.4 MM CUTTING WIDTH

Article Number 4932471306



CS 85 CBE 235 MM CIRCULAR SAW (85 MM DOC)

- 2200 Watt motor allows smooth cutting at full depth of cut
- 60° bevel capacity gives the saw the ability to achieve a wide range of roofing cuts
- Sprung loaded riving knife allows the saw to be plunged into the material without the removal of the riving knife
- Guide rail compatible, the saw can be used in conjunction with a guide rail
- Soft start minimises the tripping of circuit breakers
- Brake stops the saw in 3.5 seconds
- Double fence is anchored at the front and the back of the saw allowing for greater accuracy
- Dust extraction DEK26 compatible
- Integrated cable hatch, the cable can be replaced easily without the need to dismantle the whole saw



CS 85 CBE	
Power input (W)	2200
No load speed (rpm)	4500
Blade diameter (mm)	235
Bevel capacity (°)	60
Max. cutting depth 45° (mm)	67
Max. cutting depth 90° (mm)	85
Bore size (mm)	30
Weight (kg)	7.7
Supplied in	Kitbox
Article Number	4933451116

235 X 30 MM 48 TOOTH CIRCULAR SAW BLADE WITH 2.4 MM CUTTING WIDTH

Article Number 4932471307



60° bevel capacity



Sprung loaded riving knife



Double fence is anchored at the front and the back of the saw

SCS 65 Q | 190 MM CIRCULAR SAW (65 MM DOC)

- 1900 watt motor with large power reserves
- Unrivaled balance and comfort due to the adjustable TILT-LOK™ handle with soft grip
- Large cutting capacity of 65 mm
- Ideally positioned levers for depth and bevel cut adjustments
- Good visibility of blade at the cutting edge for improved control
- Robust aluminium base plate
- Supplied with a carbide tipped 20 tooth saw blade, parallel guide and 4 m QUIK-LOK™ cable



SCS 65 Q	
Power input (W)	1900
No load speed (rpm)	5800
Blade diameter (mm)	190
Max. cutting depth 45° (mm)	52
Max. cutting depth 90° (mm)	65
Bore size (mm)	30
Weight (kg)	5.5
Supplied in	Kitbox
Article Number	638051

190 X 30 MM 48 TOOTH CIRCULAR SAW BLADE WITH 2.1 MM CUTTING WIDTH

Article Number 4932471380



CS 60 | 184 MM CIRCULAR SAW (61 MM DOC)

- 1600 W powerful motor with 5800 rpm for fast cutting through tough materials
- Large cutting capacity of 61 mm
- 0 - 56° bevel capacity and 45° positive stop
- Quick release locking lever design for fast bevel adjustments
- Integrated dust blower keeps cut line clear
- Large, ergonomic handles and levers for improved ergonomics and control
- Long side fence for straight cuts and precise guidance
- Supplied with a carbide tipped 24 tooth saw blade, parallel guide and 4 m cable



CS 60	
Power input (W)	1600
No load speed (rpm)	5800
Blade diameter (mm)	184
Max. cutting depth 45° (mm)	49
Max. cutting depth 90° (mm)	61
Bore size (mm)	30
Weight (kg)	4.8
Supplied in	No kitbox or bag supplied
Article Number	4933419225

184 X 30 MM 40 TOOTH CIRCULAR SAW BLADE WITH 2.1 MM CUTTING WIDTH

Article Number 4932471298



BS 100 LE | 4" (100 MM) BELT SANDER

- Compact design, ideal for sanding close to edges
- Sanding surface 100 x 160 mm, for fast smooth sanding
- Variable preselection of belt speed for versatile use
- Control wheel for precise adjustment of belt alignment
- Integrated dust extraction and dust bag for dust free work and less sanding belt wear
- Easy changing of sanding belt
- Stationary work possible
- Supplied with 100 x 620 mm sanding belt (grit 100) and 4 m cable



BS 100 LE	
Power input (W)	1150
Belt speed (rpm)	230 - 400
Belt length (mm)	620
Belt width (mm)	100
Sanding surface (mm)	100 x 160
Weight (kg)	5.3
Supplied in	No kitbox or bag supplied
Article Number	4933385150

SANDING BELT - 5 PCS, 100 X 610 MM, 60 GRIT

Article Number 4932355067



ROS 125 E | 5" (125 MM) RANDOM ORBIT SANDER

- Ideal for sanding of wood, metal and plastics within confined spaces
- 300 Watt powerful motor with 2,4 mm orbital action
- Variable speed (7000-12,000 rpm) - especially needed for heat-sensitive materials
- Hook & Loop paper fitment
- Excellent dust extraction - 90% dust collection efficiency with larger dust bag
- Easy to clean dust bag
- On board vac adaptor- fits standard 36 mm vacuum hoses
- Supplied with textile dust bag and sanding paper set (60, 80, 120 grit)



ROS 125 E	
Power input (W)	300
No load speed (rpm)	7000 - 12,000
Oscillation rate (rpm)	14,000 - 26,000
Oscillation diameter (mm)	2.4
Sanding pad size (mm)	125
Weight (kg)	1.7
Supplied in	Tool bag
Article Number	4933433180

Ø 125 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932367741



ROS 150 E-2 6" (150 MM) RANDOM ORBIT SANDER

- Random orbital sander with unmatched sanding properties through simultaneous rotation and oscillation of sanding disc
- Reduction gear makes full, efficient use of the powerful 440 W motor
- 6.4 / 3.2 mm orbits for fast removal & finishing
- Variable speed (4000-10,000 rpm) - especially needed for heat-sensitive materials
- Fast and easy change of sandpaper with hook and loop system
- Removable dustbag and also fits standard 26 mm vacuum hose
- Through body sealed slide switch
- Additional handle for a balanced and even weight distribution over the work piece
- Supplied with a dust bag, sanding disc and 4 m cable



ROS 150 E-2	
Power input (W)	440
No load speed (rpm)	4000 - 10,000
Oscillation diameter (mm)	6.4 / 3.2
Sanding pad size (mm)	150
Weight (kg)	2.3
Supplied in	No kitbox or bag supplied
Article Number	4933431170

Ø 150 MM, 60 GRIT ABRASIVE DISC - 5 PCS, HOOK AND LOOP

Article Number 4932371691



Variable speed selection (4000-10,000 rpm)



Hook and loop change system



Additional handle for weight distribution

SPS 140 | 1/4" SHEET SANDER

- Powerful 260 W motor for sustained use
- 1.6 mm oscillation movement allows for fine sanding
- Quick connection to dust extractor or dust bag
- Sanding paper is attached by hook and loop or by a clamping system
- 4 m of durable rubber cable allows the user to move easily around his work piece



SPS 140	
Power input (W)	260
No load speed (rpm)	14,700
Oscillation rate (rpm)	28,000
Oscillation diameter (mm)	1.6
Sanding pad size (mm)	113 x 105
Weight (kg)	1.6
Supplied in	No kitbox or bag supplied
Article Number	4933447015

AS 42 MAC

42 L M-CLASS DUST EXTRACTOR

- Compact 42 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class M, Standard MAK-factor > 0.1 mg/m³; mineral dust, wood dust (oak, beech)
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Airflow and filter monitoring with visual LED and acoustic warning signal
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Trolley handle for convenient transportation onto the job site
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 42 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	42
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	17.5
Supplied in	No kitbox or bag supplied
Article Number	4933459418



Durable PTFE filter



Power take off for auto switching of powertools



Trolley handle for convenient transportation onto the job site

AS 30 MAC | 30 L M-CLASS DUST EXTRACTOR

- Compact 30 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class M, Standard MAK-factor > 0.1 mg/m³; mineral dust, wood dust (oak, beech)
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Airflow and filter monitoring with visual LED and acoustic warning signal
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 38 mm



AS 30 MAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	38
Hose length (m)	4
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933459415

AS 30 LAC | 30 L L-CLASS DUST EXTRACTOR

- Compact 30 litre tank for site/workshop use
- 4500 litres/min airflow with 250 mbar suction
- Dust class L, Standard MAK-factor > 1 mg/m³
- Power take off for auto switching of powertools
- Durable PTFE filter with high filtration efficiency and washable non-stick membrane
- Automatic filter cleaning with minimised performance loss
- Easy access filter hatch for convenient servicing and cleaning
- Super silent turbine for low noise
- Anti-static hose to prevent shocks caused by static build up
- Supplied with 2 x tool adaptor, hand tube, 2 x extension tube, floor / crevice nozzle, fleece filter bag, disposal bag, hose 4 m x 36 mm



AS 30 LAC	
Power input (W)	1200
Air volume (l/min)	4500
Filter type	PTFE
Max. vacuum (mbar)	250
Capacity (l)	30
Hose diameter (mm)	36
Hose length (m)	4
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933459411

AS 2-250 ELCP | 25 L L-CLASS DUST EXTRACTOR

- Large 25 litre tank capacity ideal for workshop use
- 1000 W motor power with over 210 mbar suction - 10% more efficient
- Power take off with auto switching for powertools
- 2600W power take off capacity allows for use with high wattage tools
- Clear press filter cleaning system maintains suction efficiency
- Washable PET filter provides longer filter life
- Dust class L, Standard MAK-factor > 1 mg/m³
- Wet and dry capability
- Hose and cable storage enables easy transportation
- Dust blower function
- 7.5 m rubber cable
- Supplied with 3.5 m hose with floor cleaning kit, PET filter, 2x powertool connection adaptor, 1x disposable bag, 1x fleece bag & 1x crevice nozzle



AS 2-250 ELCP	
Power input (W)	1000
Air volume (l/min)	3600
Max. vacuum (mbar)	210
Capacity (l)	25
Hose diameter (mm)	32
Weight (kg)	10.4
Supplied in	No kitbox or bag supplied
Article Number	4933447480

MS 304 DB

12" (305 MM) DUAL BEVEL SLIDING MITRE SAW

- 1800 Watt direct drive motor ensures a quick, clean cut even in hardwood materials
- Dual integral jobsite lights illuminate the cut line
- Integral dust channel captures 75% of all dust by capturing dust near the cut on both sides of the blade and directing it to the back of the saw
- Unique mitre motor design - for excellent visibility from both sides to the work piece and better balanced transport
- Mitre capacity 55° to the left and 60° to the right - for maximum versatility. Mitre detents L & R at: 0°, 15°, 22.5°, 31.6°, 45°, 60°
- Dual-bevel design - to incline the saw head left and right 0° - 48° with bevel detents L & R at: 0°, 22.5°, 33.85°, 45°, 48°
- Fast and accurate bevel adjustment
- Supplied with Work piece clamp, saw blade (60 teeth), vacuum adaptor Ø35 / 58 mm, wrench and 3 m cable



MS 304 DB	
Power input (W)	1800
No load speed (rpm)	3900
Blade diameter (mm)	305
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	55
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre/ 45° bevel (mm)	241 x 57
Max. cutting capacity 45° mitre/ 90° bevel (mm)	241 x 102
Max. cutting capacity 90° mitre/ 45° bevel (mm)	342 x 57
Max. cutting capacity 90° mitre/ 90° bevel (mm)	342 x 102
Weight (kg)	29.5
Supplied in	No kitbox or bag supplied
Article Number	4933471052

305 X 30 MM 60 TOOTH CIRCULAR SAW BLADE WITH 3.0 MM CUTTING WIDTH

Article Number **4932471321**



Dual-bevel design



Micro mitre adjustment for accurate mitre cuts



Rebate stop

MSL 1000 | MITRE SAW STAND EXTENDABLE UP TO 2 M

- Light weight aluminium, easy to transport onto the job site
- 1.06 m total length, will fit into most small vans and cars
- Extendable each side - 2.08 m extended
- Will hold up to 180 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design



MSL 1000	
Height (mm)	850
Base size (mm)	1065
Extendable up to (mm)	2125
Collapsed size (mm)	1065
Bearing force (kg)	180
Weight (kg)	17.0
Supplied in	No kitbox or bag supplied
Article Number	4933428970

MSL 2000 | MITRE SAW STAND EXTENDABLE UP TO 2.5 M

- Light weight aluminium, easy to transport onto the job site
- 1.09 m total length, will fit into most small vans and cars
- Extendable each side - 2.54 m extended
- Will hold up to 227 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design with quick release latches



MSL 2000	
Height (mm)	860
Base size (mm)	1093
Extendable up to (mm)	2542
Collapsed size (mm)	1093
Bearing force (kg)	227
Weight (kg)	14.0
Supplied in	No kitbox or bag supplied
Article Number	4933459617

WORK TABLE FOR MSL 2000

Article Number **4932459713**



MS 216 | 8 1/2" (216 MM) SLIDING MITRE SAW

- 1800 Watt motor for high performance cutting in hard timber
- Durability - dual vertical steel rails with linear bearings deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of cutting orientation
- Integral LED jobsite light
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp



MS 216 SB	
Power input (W)	1800
No load speed (rpm)	6000
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Base size (mm)	30
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933471055

MSL 3000 | MITRE SAW STAND EXTENDABLE UP TO 3 M

- Lightweight construction and wheel set - provides portability on the jobsite
- Folds down to 1200 mm - thanks to the collapsible legs and compact design
- Extendable up to 3 m - makes it easy to cut large workpieces to length
- Heavy Duty - carries up to 250 kg
- One point leg adjustment for leveling on uneven ground
- Comfortable working height at 81 cm
- Fully adjustable work piece rests - provide support for long lengths of material - single knob adjustment
- Quick to assemble - set up within seconds
- Roller supports - for effective material support



MSL 3000	
Height (mm)	810
Base size (mm)	1100
Extendable up to (mm)	3000
Collapsed size (mm)	1200
Bearing force (kg)	250
Weight (kg)	23.0
Supplied in	No kitbox or bag supplied
Article Number	4933411565

MS 304 DB

12" (305 MM) DUAL BEVEL SLIDING MITRE SAW

- 1800 Watt direct drive motor ensures a quick, clean cut even in hardwood materials
- Dual integral jobsite lights illuminate the cut line
- Integral dust channel captures 75% of all dust by capturing dust near the cut on both sides of the blade and directing it to the back of the saw
- Unique mitre motor design - for excellent visibility from both sides to the work piece and better balanced transport
- Mitre capacity 55° to the left and 60° to the right - for maximum versatility. Mitre detents L & R at: 0°, 15°, 22.5°, 31.6°, 45°, 60°
- Dual-bevel design - to incline the saw head left and right 0° - 48° with bevel detents L & R at: 0°, 22.5°, 33.85°, 45°, 48°
- Fast and accurate bevel adjustment
- Supplied with Work piece clamp, saw blade (60 teeth), vacuum adaptor Ø35 / 58 mm, wrench and 3 m cable



MS 304 DB	
Power input (W)	1800
No load speed (rpm)	3900
Blade diameter (mm)	305
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Mitre capacity left (°)	55
Mitre capacity right (°)	60
Max. cutting capacity 45° mitre/ 45° bevel (mm)	241 x 57
Max. cutting capacity 45° mitre/ 90° bevel (mm)	241 x 102
Max. cutting capacity 90° mitre/ 45° bevel (mm)	342 x 57
Max. cutting capacity 90° mitre/ 90° bevel (mm)	342 x 102
Weight (kg)	29.5
Supplied in	No kitbox or bag supplied
Article Number	4933471052

305 X 30 MM 60 TOOTH CIRCULAR SAW BLADE WITH 3.0 MM CUTTING WIDTH

Article Number **4932471321**



Dual-bevel design



Micro mitre adjustment for accurate mitre cuts



Rebate stop

MSL 1000 | MITRE SAW STAND EXTENDABLE UP TO 2 M

- Light weight aluminium, easy to transport onto the job site
- 1.06 m total length, will fit into most small vans and cars
- Extendable each side - 2.08 m extended
- Will hold up to 180 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design



MSL 1000	
Height (mm)	850
Base size (mm)	1065
Extendable up to (mm)	2125
Collapsed size (mm)	1065
Bearing force (kg)	180
Weight (kg)	17.0
Supplied in	No kitbox or bag supplied
Article Number	4933428970

MSL 2000 | MITRE SAW STAND EXTENDABLE UP TO 2.5 M

- Light weight aluminium, easy to transport onto the job site
- 1.09 m total length, will fit into most small vans and cars
- Extendable each side - 2.54 m extended
- Will hold up to 227 kg
- One point leg adjustment for leveling on uneven ground
- Quick release brackets
- Height adjustable length stops
- Compact foldable design with quick release latches



MSL 2000	
Height (mm)	860
Base size (mm)	1093
Extendable up to (mm)	2542
Collapsed size (mm)	1093
Bearing force (kg)	227
Weight (kg)	14.0
Supplied in	No kitbox or bag supplied
Article Number	4933459617

WORK TABLE FOR MSL 2000

Article Number **4932459713**



MS 216 | 8 1/2" (216 MM) SLIDING MITRE SAW

- 1800 Watt motor for high performance cutting in hard timber
- Durability - dual vertical steel rails with linear bearings deliver smooth sliding action
- Rail lock - the saw head locks in the back position automatically
- Adjustable laser - for perfect and quick alignment to cut line
- Steel detent plate with preset angles - gives repeatable accurate cuts
- Lock lever/handle over mold - allows the user to make repeated cuts comfortably and without fatigue
- Mitre release system - for quick and smooth change of cutting orientation
- Integral LED jobsite light
- Spindle lock - for quick and easy blade change
- Heavy duty cast base and fence ensures durability and accuracy
- 48°/2° bevel capacity
- Supplied with saw blade (48 teeth), blade spanner and work clamp



MS 216 SB	
Power input (W)	1800
No load speed (rpm)	6000
Blade diameter (mm)	216
Bevel capacity left (°)	48
Bevel capacity right (°)	2
Mitre capacity left (°)	50
Mitre capacity right (°)	50
Max. cutting capacity 45° mitre/ 45° bevel (mm)	190 x 48
Max. cutting capacity 45° mitre/ 90° bevel (mm)	190 x 60
Max. cutting capacity 90° mitre/ 45° bevel (mm)	270 x 48
Max. cutting capacity 90° mitre/ 90° bevel (mm)	270 x 60
Base size (mm)	30
Weight (kg)	14.5
Supplied in	No kitbox or bag supplied
Article Number	4933471055

MSL 3000 | MITRE SAW STAND EXTENDABLE UP TO 3 M

- Lightweight construction and wheel set - provides portability on the jobsite
- Folds down to 1200 mm - thanks to the collapsible legs and compact design
- Extendable up to 3 m - makes it easy to cut large workpieces to length
- Heavy Duty - carries up to 250 kg
- One point leg adjustment for leveling on uneven ground
- Comfortable working height at 81 cm
- Fully adjustable work piece rests - provide support for long lengths of material - single knob adjustment
- Quick to assemble - set up within seconds
- Roller supports - for effective material support



MSL 3000	
Height (mm)	810
Base size (mm)	1100
Extendable up to (mm)	3000
Collapsed size (mm)	1200
Bearing force (kg)	250
Weight (kg)	23.0
Supplied in	No kitbox or bag supplied
Article Number	4933411565

AGV 15 DEC | 1550 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)

- Powerful, 1550 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to protect the user from kickback injuries
- Keyless depth adjustment from 5 – 28 mm
- Keyless opening for easy and fast blade change
- Cutting guide with cutting indication line to prevent twisting and best control during work
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the MILWAUKEE® M-Class cleaners with unique "click-system" adaptor supplied with the MILWAUKEE® EMAC vacuum cleaner
- Anti-vibration side handle for reduced user fatigue
- Supplied with 4 m rubber cable, dust extraction cutting shroud, diamond cutting wheel DUH 125 mm



AGV 15-125 XC DEC-SET

Power input (W)	1550
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2,6
Variable speed	No
FKTEC™	Yes
Line lock out function	Yes
AVS side handle	Yes
Supplied in	HD Box
Article Number	4933448025

AGV 12 DEC | 1200 W ANGLE GRINDER WITH DUST MANAGEMENT (28 MM DOC)

- Powerful, 1200 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Safety clutch to protect the user from kickback injuries
- Keyless depth adjustment from 5 – 28 mm
- Keyless opening for easy and fast blade change
- Cutting guide with cutting indication line to prevent twisting and best control during work
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the MILWAUKEE® M-Class cleaners with unique "click-system" adaptor supplied with the MILWAUKEE® EMAC vacuum cleaner
- Anti-vibration side handle for reduced user fatigue
- Supplied with 4 m rubber cable, dust extraction cutting shroud, diamond cutting wheel DUH 125 mm



AGV 12-125 X DEC-SET

Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2,4
FKTEC™	Yes
Line lock out function	Yes
AVS side handle	Yes
Switch type	Slide lock-on switch
Supplied in	HD Box
Article Number	4933448020

AGV 15 DEG | 1550 W ANGLE GRINDER WITH DUST MANAGEMENT

- Powerful, 1550 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased tool life time and best performance in all applications
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Magnetic, tool-free interface for optimum work in corners and closed to walls
- On-board storage of front cover, when removed for work in restricted areas
- Flexible height adjustment allows for complete use of diamond segments on grinding wheel
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the MILWAUKEE® M-Class cleaners with unique "click-system" adaptor supplied with the MILWAUKEE® EMAC vacuum cleaner
- Angled bale handle design to allow for more pressure to be applied in all positions
- Brushes are replaceable when worn
- Supplied with 4 m rubber cable, bale handle, dust extraction grinding shroud, diamond cup wheel 125 mm



Magnetic, tool-free interface



Dust shroud can be easily mounted to the MILWAUKEE® M-Class cleaners with unique „click-system“ adaptor



100% keyless

	AGV 15-125 XC DEG-SET	AGV 15-125 XE DEG-SET
Power input (W)	1550	
No load speed (rpm)	11,000	2600 - 11,000
Disc diameter (mm)	125	125
Max. cutting depth (mm)	28	28
Spindle size	M 14	M 14
Weight (kg)	2,6	2,6
Variable speed	No	Yes
FKTEC™	Yes	Yes
Line lock out function	Yes	Yes
Supplied in	HD Box	HD Box
Article Number	4933448035	4933448030

UNIVERSAL WHEEL FOR GRINDING AND LEVELLING APPLICATIONS, HIGH STOCK REMOVAL

Article Number 4932451186



AGV 12 DEG | 1200 W ANGLE GRINDER WITH DUST MANAGEMENT

- Powerful, 1200 W PROTECTOR-MOTOR with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool
- Very compact and slim design for comfortable handling
- Line lock out function to prevent automatic start up after power breakdown
- Magnetic, tool-free interface for optimum work in corners and close to walls
- On-board storage of front cover, when removed for work in restricted areas
- Flexible height adjustment allows for complete use of diamond segments on grinding wheel
- Tool-free quick release guard for fast and easy adjustment
- Dust shroud can be easily mounted to the MILWAUKEE® M-Class cleaners with unique "click-system" adaptor supplied with the MILWAUKEE® EMAC vacuum cleaner
- Angled bale handle design to allow for more pressure to be applied in all positions
- Brushes are replaceable when worn
- Supplied with 4 m rubber cable, bale handle, dust extraction grinding shroud, diamond cup wheel 125 mm



AGV 12-125 X DEG-SET

Power input (W)	1200
No load speed (rpm)	11,000
Disc diameter (mm)	125
Max. cutting depth (mm)	28
Spindle size	M 14
Weight (kg)	2,4
FKTEC™	Yes
Line lock out function	Yes
Switch type	Slide lock-on switch
Supplied in	HD Box
Article Number	4933448030

WCS 45 | 1900 W 150 MM (45 MM DOC) WALL CHASER

- Powerful 1900 W motor
- Overload protection
- Variable adjustable cutting depth and variable cutting width
- TILT-LOK™ handle
- Soft grip
- Dust extraction connection
- Supplied with 2 diamond discs, special chisel, keys



WCS 45

Power input (W)	1900
No load speed (rpm)	5800
Disc diameter (mm)	150
Cutting width (mm)	45
Max. cutting depth (mm)	45
Spindle size	M 14
Weight (kg)	6,6
Supplied in	Kitbox
Article Number	4933383350

150 X 22.23 MM DIAMOND BLADE WITH 2.4 MM CUTTING WIDTH, 10 MM SEGMENT HEIGHT IDEAL FOR GENERAL MASONRY

Article Number

4932373148



WCE 30 | 1500 W 125 MM (30 MM DOC) WALL CHASER

- Powerful 1500 watt motor
- Ideal for the installation of conduit for electrical cables
- High performance electronics with overload protection
- Current limitation for soft start
- Easily adjustable cutting width
- In-line dust extraction connection
- Supplied with 2 diamond discs, special chisel, keys, bayonet adaptor



	WCE 30
Power input (W)	1500
No load speed (rpm)	9500
Disc diameter (mm)	125
Cutting width (mm)	26
Max. cutting depth (mm)	30
Spindle size	M 14
Weight (kg)	4.3
Supplied in	Kitbox
Article Number	4933383855