

BUY AN M18" BATTERY & CHARGER KIT AND RECEIVE A FREE M12" BATTERY.

FREE M12





TWO

ONE CHARGER

DUAL M12 + M18 COMPATIBILITY

CHARGES ALL M12" & M18" BATTERIES

PROMOTION VALID UNTIL 31.12.2021











| | | Voltage (V) | Battery type | Battery pack capacity (Ah) | No. of batteries supplied | Charger supplied | Article Number |
|----|--------------|-------------|--------------|----------------------------|---------------------------|------------------|----------------|
| 1. | M18 HNRG-122 | 18 | Li-ion | 12.0 | 2 | M12-18 FC | 4933464261 |
| 2. | M18 HNRG-802 | 18 | Li-ion | 8.0 | 2 | M12-18 FC | 4933471073 |
| 3. | M18 HNRG-552 | 18 | Li-ion | 5.5 | 2 | M12-18 FC | 4933464713 |
| 4. | M18 HNRG-302 | 18 | Li-ion | 3.0 | 2 | M12-18 FC | 4933471071 |
| 5. | M18 NRG-503 | 18 | Li-ion | 5.0 | 3 | M12-18 FC | 4933451423 |
| 6. | M18 NRG-502 | 18 | Li-ion | 5.0 | 2 | M12-18 FC | 4933459217 |

BATTERIES AND CHARGER KITS





























| | | Voltage (V) | Battery type | Battery pack capacity (Ah) | No. of batteries supplied | Charger supplied | Article Number |
|-----|-------------|-------------|--------------|----------------------------|---------------------------|------------------|----------------|
| 1. | M18 NRG-402 | 18 | Li-ion | 4.0 | 2 | M12-18 FC | 4933459215 |
| 2. | M18 NRG-202 | 18 | Li-ion | 2.0 | 2 | M12-18 C | 4933459213 |
| 3. | M12 NRG-603 | 12 | Li-ion | 6.0 | 3 | C12 C | 4933459208 |
| 4. | M12 NRG-602 | 12 | Li-ion | 6.0 | 2 | C12 C | 4933451903 |
| 5. | M12 NRG-402 | 12 | Li-ion | 4.0 | 2 | C12 C | 4933459211 |
| 6. | M12 NRG-303 | 12 | Li-ion | 3.0 | 3 | C12 C | 4933459207 |
| 7. | M12 NRG-302 | 12 | Li-ion | 3.0 | 2 | C12 C | 4933451902 |
| 8. | M12 NRG-202 | 12 | Li-ion | 2.0 | 2 | C12 C | 4933459209 |
| 9. | M12 NRG-201 | 12 | Li-ion | 2.0 | 1 | C12 C | 4933451900 |
| 10. | L4 NRG-201 | 4 | Li-ion | 2.5 | 1 | L4 C | 4932459448 |



M18 FPP4F2

M18 FUEL" POWERPACK

- · M18 FPD2 M18 FUEL" percussion drill
- M18 FID2 M18 FUEL™ ¼ Hex impact driver
- · M18 FBJS M18 FUEL" body grip jigsaw
- · M18 BMT M18" multi-tool

M18 FPP6C3

M18 FUEL" POWERPACK

M18 FPD2 - M18 FUEL™ percussion drill

∘ M18 FSZ - M18 FUEL™ SAWZALL™

· M18 TLED - M18" LED torch

M18 FID2 - M18 FUEL* ¼ Hex impact driver

.º M18 CCS55 - M18 FUEL™ 55 mm circular saw for wood and plastics

- M18 CAG125X - M18 FUEL™ 125 mm angle grinder with slide switch

- 5 m slim tape measure



M18 FPP4F2-502B

| Kit included | 2 x M18 B5 Battery packs, M12-18 FC Charger, Tool bag |
|----------------|---|
| Article Number | 4933471208 |

M18 FUEL M18 FPP5K

M18" POWERPACK

- · M18 CBLDD M18" compact brushless drill driver
- · M18 CBLID M18" compact brushless 1/4" Hex impact driver
- = M18 CCS55 M18 FUEL** 55 mm circular saw for wood and plastics · M18 BMT - M18" multi-tool
- + M18 FBJS M18 FUEL" body grip jigsaw



| M1 | | | | |
|----|--|--|--|--|
| | | | | |

| Kit included | 2 x M18 B5 Battery packs, M12-18 FC Charger, Tool bag | |
|----------------|---|--|
| Article Number | 4933471209 | |

M18 FPP6H2

M18 FUEL

M18 FUEL" POWERPACK

- M18 FPD2 M18 FUEL™ percussion drill
- *M18 FIW2F12 M18 FUEL" 1/2" compact impact wrench with friction ring
- M18 CCS55 M18 FUEL™ 55 mm circular saw for wood and plastics
- M18 FSZ M18 FUEL" SAWZALL"
- M18 CAG125X M18 FUEL" 125 mm angle grinder with slide switch
- M18 TLED M18" LED torch

Kit included Article Number



M18 FPP6C3-502B

| Kit included | 2 x M18 B5 Battery packs, M12-18 FC Charger, Tool bag |
|----------------|---|
| Article Number | 4033479800 |

M18 FUEL

M18 FUEL

M₁₈ BLPP₂A₂

M18" BRUSHLESS POWERPACK

- M18 BLPD2 M18[™] brushless percussion drill
- · M18 BLID2 M18" brushless 1/4" Hex impact driver



M18 BLPP2A2-502X

| Kit included | 2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box | |
|----------------|---|--|
| Article Number | 4933464522 | |

M18 BLPP2B2

M18™ BRUSHLESS POWERPACK

- · M18 BLDD2 M18" brushless drill driver
- M18 BLID2 M18" brushless 1/4" Hex impact driver



MILE DI DOODO ECOV

| included | 2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box | |
|-------------|---|--|
| icle Number | 4933464594 | |

M₁₈ CBLPP₂A

M18" COMPACT BRUSHLESS POWERPACK

- «M18 CBLPD M18™ compact brushless percussion drill
- *M18 CBLID M18" compact brushless 1/4" Hex impact driver





M18 CBLPP2A-402C

| Kit included | 2 x M18 B4 Battery packs, M12-18 C Charger, Kitbox |
|----------------|--|
| Article Number | 4022464526 |

M₁₈ CBLPP₂B

M18

M18

M18" COMPACT BRUSHLESS POWERPACK

- M18 CBLDD M18[™] compact brushless drill driver
- " M18 CBLID M18" compact brushless 1/4" Hex impact driver



| | M18 CBLPP2B-402C | M18 CBLPP2B-502C |
|----------------|------------------------------------|------------------------------------|
| Kit included | 2 x M18 B4 Battery packs, M12-18 C | 2 x M18 B5 Battery packs, M12-18 C |
| Kit included | Charger, Kitbox | Charger, Kitbox |
| Article Number | 4933464593 | 4933464718 |

M18 FPP6H2-502B

2 x M18 B5 Battery packs, M12-18 FC Charger, Tool bag

M18 FDCPF8-0C



M18 FFSDC13 M18 FUEL" FREE STANDING DRAIN CLEANER 13 MM

M18 FUEL

M18 FLIEL

- . World's first free standing drum machine on a 18V battery, with electronic footpedal and integrated drum brake that electronically slows drum superfast for more control and safety · M18 FUEL" SWITCH PACK" tool-free sectional drum connection system
- allows users to quickly interchange between cable sizes, 8 mm, 10 mm, 13 mm inner core and 16 mm open wind spirals, or add a second drum to reach 30 m down the line
- Built-in backpack straps allow the user to carry their drive unit seperate from their drum(s) for easier transport to any roof, drain, crawl space, or
- · Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and
- REDLINK PLUS" intelligence hardware and software which deliver outstanding power, run time and durability on the jobsite • The M18™ SWITCH PACK™ incorporates fully enclosed drums to eliminate
- free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries



| | M18 FFSDC13-0 |
|-------------------------------|--|
| No load speed (rpm) | 250 |
| Drain capacity (mm) | 75 - 110 |
| Spiral diameter (mm) | 13 |
| Spiral length (m) | 15 |
| Weight with battery pack (kg) | 13.4 |
| Standard equipment | 1 x backpack assembly, 2 x drum assem- bly's, 2 x 13 mm x 15 m cables, 1 x cutter set & removal tool |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933459708 |
| | |

M18 FFSDC10 M18 FUEL" FREE STANDING DRAIN CLEANER 10 MM

- World's first free standing drum machine on a 18V battery, with electronic footpedal and integrated drum brake that electronically slows drum superfast for more control and safety
- . M18 FUEL" SWITCH PACK" tool-free sectional drum connection system allows users to quickly interchange between cable sizes. 8 mm. 10 mm. 13 mm inner core and 16 mm open wind spirals, or add a second drum to reach 30 m down the line
- . Built-in backpack straps allow the user to carry their drive unit seperate from their drum(s) for easier transport to any roof, drain, crawl space, or clean out
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- "The M18" SWITCH PACK" incorporates fully enclosed drums to eliminate free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst uncloaging drains
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries



| | M18 FFSDC10-0 |
|-------------------------------|--|
| No load speed (rpm) | 250 |
| Drain capacity (mm) | 40 - 75 |
| Spiral diameter (mm) | 10 |
| Spiral length (m) | 15 |
| Weight with battery pack (kg) | 13.4 |
| Standard equipment | 1 x backpack assembly, 1 x drum assem- bly, 1 x 10 mm x 15 m cables, 1 x cutter set & removal tool |
| Kit included | No batteries supplied, No charger supplied. No kitbox or bag supplied |
| Article Number | 4933459707 |

M18 FDCPF10 M18 FUEL" DRAIN CLEANER - POWER FEED 10 MM

M18 FUEL


- World's first hand held drain cleaner on a 18V battery with automatic feed. and retract that can be used with 6 mm, 8 mm and 10 mm spirals from both MILWAUKEE® and other manufacturers, in pipes from 32 mm up to 75 mm, up to 15 m down the line, eliminating all electrocution hazards users encounter today with their corded tools
- . Flat base enables user to put tool down and have one hand free to guide the cable in and out of the drain giving the user more control whilst
- unclogging drains · CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when
- feeding and working the clog . Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclooging drains
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- LED light illuminates work area undemeath sinks and other dark spaces
- Flexible battery system: works with all MILWAUKEE® M18™ batteries

| | Drain c |
|--|----------|
| | Spiral o |
| N. Company | Spiral I |
| The Person of th | Bucket |
| Marie Sales | Weight |
| | Standa |
| | Kit incl |
| | Article |

| | M18 FDCPF10-0C | M18 FDCPF10-201C |
|-------------------------------|---|--|
| No load speed (rpm) | 0 - 600 | 0 - 600 |
| Drain capacity (mm) | 32 - 75 | 32 - 75 |
| Spiral diameter (mm) | 10 | 10 |
| Spiral length (m) | 10.6 | 10.6 |
| Bucket capacity (I) | 23 | 23 |
| Weight with battery pack (kg) | 6.9 | 6.9 |
| Standard equipment | | 1 x 10 mm x 10.6 m cable (48532675), 5 pc cutter set (48532685), removal pin |
| Kit included | No batteries supplied, No charger supplied, Bucket | 1 x M18 B2 Battery pack, M12-18 FC Charger, Bucket |
| Article Number | 4933459684 | 4933459685 |

M18 FDCPF8 M18 FUEL" DRAIN CLEANER - POWER FEED 8 MM

- . World's first hand held drain cleaner on a 18V battery with automatic feed and retract that can be used with 6 mm, 8 mm and 10 mm spirals from both MILWAUKEE® and other manufacturers, in pipes from 32 mm up to 75 mm, up to 15 m down the line, eliminating all electrocution hazards users encounter today with their corded tools
- · Flat base enables user to put tool down and have one hand free to guide the cable in and out of the drain giving the user more control whilst unclogging drains
- · CABLE-DRIVE locking feed system maintains selected feed speed, and auto-adjusts to compatible cable sizes for the best cable grip when feeding and working the clog
- Fully enclosed drum eliminates free spinning parts, providing the user with more protection whilst working in and around fragile fixtures as well as better mess containment whilst unclogging drains
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS" intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- LED light illuminates work area underneath sinks and other dark spaces
- * Flexible battery system: works with all MILWAUKEE® M1811 batteries



M12 BDC8 M12" SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 8 MM



- · Lightest professional drain cleaner on the market
- Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine
- . Best user flexibility and manoeuvrability due to the independence of electric power supply
- Tool includes a tough 8 mm spiral for strong blockages in pipes up to 50 mm. It can also be used with all standard Ø 6 & 8 mm spirals, from both MILWAUKEE® and other manufacturers
- · Robust drum shield protects user & fixtures from spinning drum during use
- · Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum
- . Quick cable lock mechanism for manual feeding and releasing the spiral . Integrated LED light illuminates work area underneath sinks and other dark
- * REDLINK** overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more
- work over pack life ◆ Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BDC8-0C | M12 BDC8-202C |
|-------------------------------|---|--|
| No load speed (rpm) | 0 - 500 | 0 - 500 |
| Drain capacity (mm) | 32 - 50 | 32 - 50 |
| Spiral diameter (mm) | 8 | 8 |
| Spiral length (m) | 7.6 | 7.6 |
| Bucket capacity (f) | 22.5 | 22.5 |
| Weight with battery pack (kg) | | 4.8 |
| Standard equipment | 8 mm x 7.6 m inner core bulb head | 8 mm x 7.6 m inner core bulb head |
| Kit included | No batteries supplied, No charger supplied, Bucket | 2 x M12 B2 Battery packs. C12 C Charger, Bucket |
| Article Number | 4933451632 | 4933451633 |

M12 BDC6 | M12" SUB COMPACT DRAIN CLEANER WITH SPIRAL DIAMETER 6 MM

· Lightest professional drain cleaner on the market

- Versatile design, provides benefits of both handheld and floor based drain

cleaners in one machine · Best user flexibility and manoeuvrability due to the independence of

electric power supply . Tool includes a highly flexible 6 mm spiral for easy access in drainpipes up

- to 50 mm. It can also be used with all standard Ø 6 & 8 mm spirals, from both MILWAUKEE® and other manufacturers Robust drum shield protects user & fixtures from spinning drum during use
- . Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum . Quick cable lock mechanism for manual feeding and releasing the spiral
- Integrated LED light illuminates work area underneath sinks and other dark. snaces
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- REDLITHIUM[®] battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- . Flexible battery system: works with all MILWAUKEE® M12" batteries



| | M12 BDC6-0C | M12 BDC6-202C |
|-------------------------------|---|---|
| No load speed (rpm) | 0 - 500 | 0 - 500 |
| Drain capacity (mm) | 32 - 50 | 32 - 50 |
| Spiral diameter (mm) | 6 | 6 |
| Spiral length (m) | 7.6 | 7.6 |
| Bucket capacity (f) | 22.5 | 22.5 |
| Weight with battery pack (kg) | | 4.2 |
| Standard equipment | 6 mm x 7.6 m inner core bulb head | 6 mm x 7.6 m inner core bulb head |
| Kit included | No batteries supplied, No charger supplied, Bucket | 2 x M12 B2 Battery packs C12 C Charger, Bucket |
| Article Number | 4933451634 | 4933451635 |



M12 FLIEL M12 CH

M12 FUEL™ SUB COMPACT SDS-PLUS HAMMER

M12 CH-202C M12 CH-602X

SDS-Plus

0 - 900

0 - 6575

2 x M12 B6

Battery packs

C12 C Charger

SDS-Plus

0 - 6575

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day
- Will drill over 60 50 mm x 6 mm holes per battery charge
- Superior power to weight ratio in its class with brushless POWERSTATE" motor for up to 3x longer motor life and up to 2x
- REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM[®] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Optimised hammer drilling up to 6 10 mm (max 13 mm)
- 43 mm neck size compatible with M12 DE dust extractor

M12 CH-0

SDS-Plus

0 - 900

Flexible battery system: works with all MILWAUKEE[®] M12[™] batteries







Exceptionally low vibration value



Article Number



M12 H M12" SUB COMPACT SDS-PLUS HAMMER

4933441947 4933441997 4933451510

 Ergonomically designed, compact and light weight allows for work in tight spaces and reduces fatique during all day use

No batteries sup- 2 x M12 B2

plied, No charger Battery packs,

supplied, No kitboxC12 C Charger,

or bag supplied Kitbox

- REDLINK[®] overload protection electronics in tool and battery pack deliver
- best in class system durability L-shape, 2 mode hammer drill for hammer & rotary drilling for maximum.
- versatility Low vibration at 6.7 m/s²

Blow energy (EPTA)(J)

No load speed (rpm)

Kit included

Article Number

Full load hammer action (bpm) 0 - 6575

Max. drilling wood (mm) 13

Max, drilling steel (mm) 10

Max. drilling concrete (mm) 13

Vibration drilling (m/s²) 4.4

Weight with battery pack (kg)

- Optimised hammer drilling up to 4 8 mm (max 13 mm)
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light added user convenience and
- illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 H-0 | M12 H-202C | M12 H-402C |
|--|---|--|--|
| Tool reception | SDS-Plus | SDS-Plus | SDS-Plus |
| Blow energy (EPTA)(J) | 0.9 | 0.9 | 0.9 |
| No load speed (rpm) | 0 - 800 | 0 - 800 | 0 - 800 |
| Full load hammer action (bpm) | 0 - 5350 | 0 - 5350 | 0 - 5350 |
| Max. drilling wood (mm) | 10 | 10 | 10 |
| Max. drilling steel (mm) | 8 | 8 | 8 |
| Max, drilling concrete (mm) | 13 | 13 | 13 |
| Vibration drilling (m/s ²) | 6.7 | 6.7 | 6.7 |
| Weight with battery pack (kg) | - | 1.6 | 1.8 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag | 2 x M12 B2 Battery packs, C12 C Charger, | 2 x M12 B4 Battery packs, C12 C Charger, |

4933431355 4933431340 4933441164

M12 UDEL M12" UNIVERSAL DUST EXTRACTOR - L CLASS RATED

- * Fits all MILWAUKEE® SDS-plus and the majority of competitor's hammers between 41-61 mm neck size with just one adjustable side handle which can be mounted right or left of the hammer
- Delivering more than 40 min run time on a single M12 B2 2.0 Ah battery . Due to telescopic nozzle capable of operating with up to 210 mm long SDS-plus drill bits
- Adjustable drilling depth gauge for a perfect adjustment to the task *2 exchangeable nozzles with brushes to cover drilling diameters up to
- Ø30 mm (Ø5-16 mm, Ø16-30 mm) *2 different vacuum modes to switch the unit either permanently on or activate it automatically when the actual drilling starts
- . Automatic 5 sec switch off time delay to ensure a clean drill hole
- Equipped with a HEPA H13 class filter as well as a filter cleaning mechanism for best performance and a longer filter life time
- * Equipped with a transparent tank for full capacity visibility as well as a Ø32 mm vacuum connector to empty the dust bin without any dust exposure
- . Fuel gauge displays remaining charge



| | M12 UDEL-0B | M12 UDEL-201B |
|-------------------------------|---------------------------|--------------------------|
| Max. drill bit diameter (mm) | 30 | 30 |
| Max, drilling depth (mm) | 203 | 203 |
| Air volume (l/min) | 466 | 466 |
| Airflow speed (m3/h) | 28 | 28 |
| Capacity liquids (I) | 0.31 | 0.31 |
| Capacity solids (f) | 0.31 | 0.31 |
| Filter type | HEPA H13 | HEPA H13 |
| Max. vacuum (mbar) | 23.4 | 23.4 |
| Weight with battery pack (kg) | 3 | 2.2 |
| Kit included | No batteries supplied, No | 1 x M12 B2 Battery pack, |

charger supplied, Tool bag C12 C Charger, Tool bag

M₁₂ FPD

M12 FUEL™ SUB COMPACT PERCUSSION DRILL

- Brushless POWERSTATE* motor delivers more power in a more compact size
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- · REDLITHIUM battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 13 mm metal chuck for quick bit changes and bit retention
- Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- Fuel gauge displays remaining charge
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12® batteries





M12 FUEL

13 mm metal chuck



Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling

M12 FPD-202X M12 FPD-602X M12 FPD-0 No load speed gear 1 (rpm) 0 - 450 No load speed gear 2 (rpm) 0 - 1700 Max. drilling wood (mm) Max. drilling steel (mm) Max, drilling masonry (mm) 13 Max. percussion rate (bpm) 0 - 25,500 0 - 25.500 Max. torque (Nm) Weight with battery pack (kg) No batteries sup- 2 x M12 B2 2 x M12 B6

plied, No charger Battery packs. Battery packs. Kit included supplied, No kitbox C12 C Charger, C12 C Charger or bag supplied HD Bax 4933459801 4933459802 4933459806 Article Number

SHOCKWAVE" IMPACT DUTY Article Number 4932430904

PUCK BIT SET (15 PC)

6 o.



For further technical specifications, including noise and vibration data, please visit our website; www.mi/waukeetool.eu

M12

For further technical specifications, including noise and vibration data, please visit our website; www.milwaukeetool.eu



M12 BDD M12" SUB COMPACT DRILL DRIVER

- High performance sub compact drill driver measures 187 mm in length making it ideal for working within confined spaces
- REDLINK" overload protection electronics in tool and battery pack deliver best in class system durability
- 10 mm metal chuck for quick bit changes and bit retention
- · Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- · On board fuel gauge and LED light added user convenience and illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



Article Number

| | M12 BDD-0 | M12 BDD-202C | M12 BDD-4020 |
|-------------------------------|---|--|--|
| No load speed gear 1 (rpm) | 0 - 400 | 0 - 400 | 0 - 400 |
| No load speed gear 2 (rpm) | 0 - 1500 | 0 - 1500 | 0 - 1500 |
| Chuck capacity (mm) | 10 | 10 | 10 |
| Max. drilling wood (mm) | 22 | 22 | 22 |
| Max. drilling steel (mm) | 10 | 10 | 10 |
| Max. torque (Nm) | 30 | 30 | 38 |
| Weight with battery pack (kg) | (*) | 1.2 | 1.4 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag | 2 x M12 B2 Battery packs, C12 C Charger, Kithox | 2 x M12 B4 Battery packs, C12 C Charger, Kithox |

4933441930 4933441915

4933441925

M12 FLIEL

C12 RAD M12" SUB COMPACT RIGHT ANGLE DRILL

- . Heavy Duty full metal gearbox and gears for superior durability and
- maximum torque
- REDLINK' overload protection electronics in tool and battery pack deliver best in class system durability
- Variable speed paddle switch trigger for comfortable working in any situation
- 10 mm chuck for guick bit changes and bit retention
- Electronic clutch with indicator light for complete control
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . On board fuel gauge and LED light added user convenience and
- illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | C12 RAD-0 | C12 RAD-202B |
|-------------------------------|---|---|
| No load speed (rpm) | 0 - 800 | 0 - 800 |
| Chuck capacity (mm) | 10 | 10 |
| Max. drilling wood (mm) | 22 | 22 |
| Max. drilling steel (mm) | 10 | 10 |
| Max. torque (Nm) | 12 | 12 |
| Weight with battery pack (kg) | - | 1.1 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B2 Battery packs C12 C Charger, Tool bag |
| Author Missohov | 10001110000 | 10001111015 |

M12 CD M12 FUEL" SUB COMPACT DRIVER

- . Brushless POWERSTATE" motor for up to 10x longer motor life, up to 2x more power and up to 2x more run time
- REDLINK PLUS[™] intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more
- work over pack life Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- 4 1/4" Hex chuck for quick easy one handed bit change
- Fuel gauge displays remaining charge Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.



| | M12 CD-0 |
|-------------------------------|--|
| No load speed gear 1 (rpm) | 0 - 450 |
| No load speed gear 2 (rpm) | 0 - 1700 |
| Tool reception | ½" Hex |
| Max. drilling wood (mm) | 25 |
| Max, drilling steel (mm) | 10 |
| Max. torque (Nm) | 37 |
| Weight with battery pack (kg) | 1.2 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933440450 |

M12 BD M12" SUB COMPACT DRIVER

- High performance sub compact screw driver measures 175 mm in length making it ideal for working within confined spaces
- REDLINK[®] overload protection electronics in tool and battery pack delivered. best in class system durability
- 1/4" Hex chuck for quick easy one handed bit change
- · Optimised handle for better control and improved grip
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- · On board fuel gauge and LED light added user convenience and illumination in low lit working conditions
- REDLITHIUM[™] battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more
- work over pack life Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BD-0 | M12 BD-202C |
|-------------------------------|---|--|
| No load speed gear 1 (rpm) | 0 - 400 | 0 - 400 |
| No load speed gear 2 (rpm) | 0 - 1500 | 0 - 1500 |
| Tool reception | 1/ii" Hex | %" Hex |
| Max. drilling wood (mm) | 22 | 22 |
| Max. drilling steel (mm) | 10 | 10 |
| Wood screws to (mm) | 6 | 6 |
| Max, torque (Nm) | 30 | 30 |
| Weight with battery pack (kg) | | 1.0 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B2 Battery packs, C12 C Charger, Kittxox |
| Article Number | 4933441910 | 4933441900 |

M12 BSD | M12" SUB COMPACT SINGLE SPEED DRIVER

- . High performance compact screw driver measures 169 mm in length
- making it ideal for working within confined spaces
- . Metal planetary gears for superior durability and maximum torque up to
- * 1/c Hex chuck for quick easy one handed bit change
- REDLINK[®] overload protection electronics in tool and battery pack deliver
- best in class system durability * 15 stage torque adjustment plus additional drilling for maximum flexibility
- · Slimline soft grip handle · Built in LED light illuminates the work surface
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BSD-0 |
|-------------------------------|--|
| No load speed (rpm) | 0 - 500 |
| Max, drilling wood (mm) | 16 |
| Max, drilling steel (mm) | 10 |
| Max, torque (Nm) | 20 |
| Tool reception | 74" Hex |
| Weight with battery pack (kg) | 0.9 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933447135 |
| | |

M12 FID M12 FUEL" SUB COMPACT 1/4" HEX IMPACT DRIVER

- · Brushless POWERSTATE" motor with faster speed in a more compact size of 130 mm
- * REDLINK PLUS* intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- + 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility
- * REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- . Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- "/4" Hex chuck for guick and easy bit change
- On board fuel gauge and LED light
- . Flexible battery system: works with all MILWAUKEE® M12" batteries



| | M12 FID-0 | M12 FID-202X |
|-------------------------------|---|---|
| No load speed (rpm) | 0-1300 / 0-2400 / 0-3300 / 0-3300 | 0-1300 / 0-2400 / 0-3300 / 0-3300 |
| Tool reception | 34" Hex | 16" Hex |
| Impact rate (ipm) | 0 - 4000 | 0 - 4000 |
| Max. torque (Nm) | 147 | 147 |
| Weight with battery pack (kg) | - | 1.1 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B2 Battery packs, C12 C Charger, HD Box |
| Article Number | 4933459822 | 4933459823 |

M12 FUEL



M12 FQID | M12 FUEL" SURGE" 1/4" HEX HYDRAULIC IMPACT DRIVER

- The M12 FUEL™ SURGE™ ¼" Hex hydraulic impact driver is Milwaukee Tool's quietest 12V impact driver, delivers best in class sound at only
- 76 dB(A) in wood fastening applications FLUID-DRIVE™ hydraulic powertrain reduces metal on metal contact within the tool, delivering guieter operation, smoother performance and increased
- durability over a standard impact · 4-Mode DRIVE CONTROL allows the user to shift into four different speed
- and torque settings to maximise application versatility POWERSTATE[®] brushless motor delivers up to 0 - 3,200 rpm with
- constant power output to drive screws faster
- REDLINK PLUS" intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM" battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- ¼" Hex chuck for quick and easy bit change
- Flexible battery system: works with all MILWAUKEE® M12[™] batteries



4933464974

M12

M12



4933464972



Article Number

M12 BID M12" SUB COMPACT 1/4" HEX IMPACT DRIVER

- . High performance sub compact impact driver measures 165 mm in length making it ideal for working within confined spaces
- REDLINK" overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and
- maximum torque ¼" Hex chuck for quick and easy bit change
- Optimised handle for better control and improved grip
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . On board fuel gauge and LED light added user convenience and
- illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BID-0 | M12 BID-202C |
|-------------------------------|---|--|
| No load speed (rpm) | 0 - 2500 | 0 - 2500 |
| Impact rate (ipm) | 0 - 3300 | 0 - 3300 |
| Tool reception | 34" Hex | 16" Hex |
| Max. torque (Nm) | 112 | 112 |
| Weight with battery pack (kg) | | 1.0 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B2 Battery packs, C12 C Charger, Kitbox |
| Article Number | 4933441955 | 4933441960 |

M12 BRAID M12" SUB COMPACT RIGHT ANGLE IMPACT DRIVER

- Compact right angle impact driver measures 287 mm in length making it ideal for working within confined spaces
- REDLINK[®] overload protection electronics delivers best in class system. durability
- · Full metal gearbox and gears for superior durability and maximum torque of 68 Nm
- Compact head design with diameter of 35.6 mm
- · Multi-handle design for multiple hand positions and maximum comfort
- ¼ Hex chuck for quick easy one handed bit change
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light REDLITHIUM" battery pack provides superior pack construction,
- electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12® batteries



| | M12 BRAID-0 |
|-------------------------------|--|
| No load speed (rpm) | 0 - 2425 |
| Impact rate (ipm) | 0 - 3300 |
| Tool reception | 36" Hex |
| Max. torque (Nm) | 68 |
| Weight with battery pack (kg) | 1.2 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933451247 |

M12 FIWF12

M12 FUEL™ SUB COMPACT 1/2" IMPACT WRENCH

- More power, more compact, more control
- Up to 339Nm of maximum torque
- 9 1/2" anvil with friction ring for quick and easy socket changes
- o Brushless POWERSTATE" motor delivers more power in a more
- REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM" battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- Better access in tight spaces with an overall length of only 124.5 mm 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user
- Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12® batteries





1/s" SHOCKWAVE" IMPACT DUTY SOCKET SET (11 PC), INCLUDES 9 X IMPACT SOCKETS, 1 X 150 MM EXTENSION, 1 X 1/4" HEX - 1/8" SQ ADAPTOR

Article Number



4932478290







Better access in tight spaces with an overall length of only 124.5 mm



4-Mode DRIVE CONTROL with auto-

M12 FUEL

M12 FIW38 M12 FUEL" SUB COMPACT 3/6" IMPACT WRENCH

- · More power, more compact, more control
- Up to 339 Nm of maximum torque
- +3/s anvil with friction ring for quick and easy socket changes.

4933464615

- · Brushless POWERSTATE" motor delivers more power in a more compact
- "REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- * Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . Better access in tight spaces with an overall length of only 121,9 mm
- * 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise
- · Bright LED workspace illumination
- Flexible battery system: works with all MILWAUKEE® M12th batteries



| | M12 FTW38-0 | M12 FIW38-422X |
|-------------------------------|---|---|
| No load speed (rpm) | 1200/1800/2700/2700 | 1200/1800/2700/2700 |
| Tool reception | 16" square | ₩ square |
| Impact rate (ipm) | 1100/2100/3200 | 1100/2100/3200 |
| Max, torque (Nm) | 339 | 339 |
| Max, bolt diameter | M16 | M16 |
| Weight with battery pack (kg) | 14 | 1.1 |
| Kit included | No batteries supplied, No charger supplied, No kithox or bag supplied | 1 x M12 B4, 1 x M12 B2 Battery packs, C12 C Charger, HD Box |
| Article Number | 4933464612 | 4933464613 |
| | | |

| 3/8" SHO | CKWAVE" II | MPACT DUTY |
|----------|------------|------------|
| SOCKET | SET DEEP | (8 PC) |

| Article Number | 4932478289 |
|----------------|------------|





M18-28 CPDEX | M18-28 FUEL" SDS-PLUS DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- Compatible with M18 CHPX & M28 CHPX
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



M28 FUEL M18 FUEL

| | M18-28 CPDEX-0 |
|----------------------------------|---|
| Max. drill bit diameter (mm) | 16 |
| Max. drilling depth (mm) | 90 |
| Max. drill bit length (mm) | 160 |
| Stroke length (mm) | 100 |
| Weight without battery pack (kg) | 1.6 |
| Kit included | No batteries supplied, No charger supplied, |
| Kit ilicidded | No kitbox or bag supplied |
| Article Number | 4933446810 |

M18 FUEL" HIGH PERFORMANCE SDS-PLUS HAMMER WITH DEDICATED DE





M18 CDEX | M18 FUEL" SDS-PLUS DUST EXTRACTOR

- Designed to collect dust effectively with automatic operation from the tools on/off trigger switch
- HEPA Filter: widely regarded as the ultimate filter that traps all sizes of particles with an efficiency rating of 99.75%
- · Large dust collection box
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length 16 mm max and 90 mm depth
- · Compatible with M18 CHX
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 CDEX-0 |
|--|---|
| Max. drill bit diameter (mm) | 16 |
| Max. drilling depth (mm) | 90 |
| Max. drill bit length (mm) | 160 |
| Stroke length (mm) | 100 |
| Weight without battery pack (kg) | 1.6 |
| Kit included | No batteries supplied, No charger supplied, |
| Kit iliciaaea | No kitbox or bag supplied |
| Article Number | 4933447450 |
| The state of the s | 1000111100 |

M18 FUEL™ SDS-PLUS HAMMER WITH DEDICATED DE







Capacity solids (I)

Hose diameter (mm)

Max. vacuum (mbar)

Weight with battery pack (kg)

Filter type

Kit included

M₁₈ FCVL

M18 FUEL COMPACT VACUUM

- Powerful POWERSTATE* brushless motor with dual cyclonic debris separation for larger jobsite debris
- More efficient clean up thanks to an additional powered floor tool for residential and workshop floors
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns
- Removable 0.95 I canister for easy emptying of debris on or off tool Delivers up to 17 minutes of run time on a M18" 5.0 Ah battery pack
- Quick change accessories for upright use at ground level, waist level, or for use overhead with ease
- On-board accessory holder provided for flexible hose, crevice tool, utility tool, and brush tool
- Extendable hose up to 1.2 m for extra reach and versatility
- Flexible battery system; works with all MILWAUKEE® M18" batteries

M18 FCVL-0

Dry HEPA

No batteries supplied. No charger supplied.

No kithex or bag supplied





M18 FLIEL

5 dedicated solutions



First MILWAUKEE® vacuum supplied



Dual cyclonic debris separation

M18

49334781RF

- Excellent suction power for wood, metal and common debris
- HEPA filter will collect 99.97% of airborne particles down to 0.3 microns
- Lock on switch reduces fatigue during sustained use
- Versatile accessories for small or large clean up areas
- Secure canister lock quards against unwanted spillage

M18 CV M18" HAND VAC

- . Clear viewing window gives the user the ability to see debris build up
- Up to 23 minutes continuous run time on a 5.0 Ah battery
- » Flexible battery system: works with all MILWAUKEE® M18™ batteries.



| | M18 CV-0 |
|-------------------------------|---|
| Capacity solids (I) | 2.5 |
| Hose diameter (mm) | 32 |
| Hose length (m) | 1.2 |
| Max. vacuum (mbar) | 84.8 |
| Air volume (l/min) | 1019.33 |
| Filter type | Dry |
| Weight with battery pack (kg) | 1.98 |
| Kit included | No batteries supplied, No charger supplied, Tool bag |
| Article Number | 4933459204 |
| | |

C18 PCG/600 M18" CAULK GUN WITH 600 ML TUBE

- Up to 4500 N of force. Min 40% higher than previous MILWAUKEE® caulk
- REDLINK** overload protection electronics in tool and battery pack deliver best in class system durability
- · Optimised performance with all adhesives and cool temperatures
- · Anti-drip feature prevents unwanted dripping when trigger is released
- . Dial control with 6 speed settings allows for maximum bead control
- . Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- . Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . On board fuel gauge and LED light
- · REDLITHIUM" battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18th batteries



| | C18 PCG/600A-201B | C18 PCG/600T-201B |
|-------------------------------|---|---|
| Max. pushing force (N) | 4500 | 4500 |
| Speed settings | 6 | 6 |
| Standard equipment | 600 ml alum, tube | 600 ml transp, tube |
| Weight with battery pack (kg) | 2.3 | 2.3 |
| Kit included | 1 x M18 B2 Battery pack, M12-18 C Charge | 1 x M18 B2 Battery er, pack, M12-18 C Charger, |
| | Tool bag | Tool bag |
| Antinto Marsolina | 4000 AA100E | 4000444000 |

C18 PCG/400 M18" CAULK GUN WITH 400 ML TUBE

- Up to 4500N of force. Min 40% higher than previous MILWAUKEE® caulk
- . REDLINK" overload protection electronics in tool and battery pack deliver best in class system durability
- Optimised performance with all adhesives and cool temperatures
- Anti-drip feature prevents unwanted dripping when trigger is released
- Dial control with 6 speed settings allows for maximum bead control
- Large robust plunger design ensures constant flow, reduces blow back
- and expels all sealant from cartridge
- . Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . On board fuel gauge and LED light
- . REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- · Flexible battery system: works with all MILWAUKEE® M18" batteries



| | C18 PCG/400T-201B | |
|-------------------------------|--|--|
| Voltage (V) | 18 | |
| Battery type | Li-ion | |
| Max. pushing force (N) | 4500 | |
| Speed settings | 6 | |
| Standard equipment | 400 ml transparent tube | |
| Weight with battery pack (kg) | 2.3 | |
| Kit included | 1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag | |
| Article Number | 4933441812 | |

C18 PCG/310 M18" CAULK GUN WITH 310 ML CANISTER

- Up to 4500 N of force, Min 40% higher than previous MILWAUKEE® caulk
- REDLINK** overload protection electronics in tool and battery pack deliver best in class system durability
- · Optimised performance with all adhesives and cool temperatures Anti-drip feature prevents unwanted dripping when trigger is released.
- . Dial control with 6 speed settings allows for maximum bead control
- . Large robust plunger design ensures constant flow, reduces blow back and expels all sealant from cartridge
- . Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light
- REDLITHIUM** battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18th batteries



| | C18 PCG/310C-0B | C18 PCG/310C-201B |
|-------------------------------|--|---|
| Max. pushing force (N) | 4500 | 4500 |
| Speed settings | 6 | 6 |
| Standard equipment | 310 ml canister cartrid; holder | ge 310 ml canister cartridge holder |
| Weight with battery pack (kg) | | 2.3 |
| Kit included | No batteries supplied, No charger supplied, Tool bag | 1 x M18 B2 Battery pack, M12-18 C Charger, Tool bag |
| Article Number | 4933459637 | 4933441310 |

M18 GG | M18" GREASE GUN

- Powerful 18V motor delivers over 690 bar max, operating pressure
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability
- Extreme long run time dispenses up to 7 cartridges per charge
- Strong handle balance and ergonomics only 355 mm long and 3.9 kg
- · Air bleeder valve priming mechanism for quick flow
- Integrated hose storage, shoulder strap loop & LED fuel gauge added user convenience and reducing down time
- . Three way loading bulk, cartridge and suction capable
- Grease capacity 400 ml cartridge, 473 ml bulk
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Supplied with 1219 mm high pressure flex hose with spring guard



| | M18 GG-0 | M18 GG-201C |
|-------------------------------|---|---|
| Pressure (bar) | 690 | 690 |
| Weight with battery pack (kg) | - | 3.9 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox |
| Article Number | 4933440493 | 4933440490 |

M18 BBL M18" BATTERY BLOWER

- · Compact body clears dirt and debris in tight spaces
- · Power control 3 speed settings with variable speed trigger
- Versatile attachments nozzle extension (228.6 mm), universal inflator/ deflator attachment
- · Removable nozzle for easy, convenient storage
- Lock-on switch
- 9 Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 BBL-0 |
|-------------------------------|---|
| Air volume (m³/min) | 0 - 2.9 |
| Airflow speed (km/h) | 0 - 42.8 |
| Fan speed (rpm) | 0 - 18,700 |
| Length without nozzle (mm) | 375 |
| Weight with battery pack (kg) | 1.2 |
| Kit included | No batteries supplied, No charger supplied, |
| KIT INCIDIOEU | No kitbox or bag supplied |
| Article Number | 4933446216 |

M18 AF M18" AIR FAN

- AC/DC, allows the user to run on M18[™] REDLITHIUM[™] or AC power when available
- o Three speed settings for optimised air flow up to 1290 meters per hour
- Efficient air circulation circulates the air within a 3.6 m x 4 m room
- $^{\circ}$ Adjustable head allows the user to utilise the fan in various heights and positions over a range of 120 $^{\circ}$
- Three hours run time on speed three with a M18™ REDLITHIUM™ 4.0 Ah battery pack
- · Compact design with integrated carry handle to maximise portability
- Rubber feet provide stability and no surface scratches
- · Fixing points gives the user the option to wall mount the fan if needed
- AC adaptor supplied
- Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 AF-0 |
|-------------------------------------|--|
| Airflow speed 1 (m ³ /h) | 760 |
| Airflow speed 2 (m ³ /h) | 1000 |
| Airflow speed 3 (m3/h) | 1290 |
| Weight with battery pack (kg) | 2.7 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933451022 |

M18

M18

M18

For further technical specifications, including noise and vibration data, please visit our website: www.milwaukeetool.eu



M12 FIW14 M12 FUEL" SUB COMPACT 1/4" IMPACT WRENCH

- . More power, more compact, more control
- Up to 115 Nm of maximum fastening torque
- Up to 136 Nm of maximum nut busting torque
- " 1/4" anvil with friction ring for quick and easy socket changes · Brushless POWERSTATE* motor delivers more power in a more compact
- AREDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- · Better access in tight spaces with an overall length of only 129.5 mm · 4-Mode DRIVE CONTROL with auto-shut off mode, offers the user precise
- · Bright LED workspace illumination
- ∘ Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

M12

M12

| | M12 FIW14-0 |
|-------------------------------|--|
| No load speed (rpm) | 1300/1900/3200/3200 |
| Tool reception | 1/4" square |
| Impact rate (ipm) | 1300/2000/4300 |
| Max. torque (Nm) | 136 |
| Max. bolt diameter | M12 |
| Weight with battery pack (kg) | 0.9 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933464611 |
| | |

M12 BIW12 M12" SUB COMPACT 1/2" IMPACT WRENCH

- · High performance sub compact impact wrench measures 171 mm in length making it ideal for working within confined spaces
- REDLINK' overload protection electronics in tool and battery pack deliver best in class system durability
- Heavy duty full metal gearbox and gears for superior durability and
- maximum torque
- "/2" square drive with pin detent for use with universal sockets Optimised handle for better control and improved grip
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . On board fuel gauge and LED light added user convenience and
- illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- ∘ Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BIW12-0 | M12 BIW12-202C |
|-------------------------------|---|---|
| No load speed (rpm) | 0 - 2550 | 0 - 2550 |
| Tool reception | 1/2" square | 15' square |
| Impact rate (ipm) | 0 - 3400 | 0 - 3400 |
| Max. torque (Nm) | 138 | 138 |
| Weight with battery pack (kg) | - | 1.0 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M12 B2 Battery packs C12 C Charger, Kitbox |
| Article Number | 4933447134 | 4933447133 |

M12 BIW38 M12" SUB COMPACT 3/6" IMPACT WRENCH

- . High performance sub compact impact wrench measures 165 mm in length making it ideal for working within confined spaces
- best in class system durability
- REDLINK[®] overload protection electronics in tool and battery pack deliver. . Heavy duty full metal gearbox and gears for superior durability and maximum torque
- a 3/s" square drive with friction ring for use with universal sockets
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light added user convenience and
- illumination in low lit working conditions
- REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 BIW38-0 |
|-------------------------------|---|
| No load speed (rpm) | 0 - 2500 |
| Tool reception | %" square |
| Impact rate (ipm) | 0 - 3300 |
| Max. torque (Nm) | 135 |
| Weight with battery pack (kg) | 1.0 |
| Kit included | No batteries supplied, No charger supplied, No kitto or bag supplied |
| Article Number | 4933441985 |

M₁₂ FRAIWF₁₂

M12 FUEL™ 1/2" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING

- Delivers up to 270 Nm fastening torque and 300 Nm nut-busting
- 4-Mode DRIVE CONTROL includes Auto Shut-Off Mode and Bolt Removal Mode which prevents over-tightening and provides more control after bolt breakaway
- The long body profile allows for more access in hard to reach spaces
- Only 71 mm head with anvil profile design allows for more access in tight spaces
- o 1/2 anvil with friction ring for quick and easy socket changes Bright LED workspace illumination
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use

Tool reception

Impact rate (ipm)

Max. torque (Nm)

Max, bolt diameter

Kit included

Weight with battery pack (kg)

- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" intelligence hardware and software - which deliver
- outstanding power, run time and durability on the jobsite Flexible battery system: works with all MILWAUKEE® M12[™] batteries

M12 FRAIWF12-0

0-1350/ 0-2700/ 0-3600

No kitbox or bag supplied

0-1150/ 0-2300/ 0-3000/ 0-3000

No batteries supplied. No charger supplied.





Article Number







Auto Shut-Off Mode and Bolt Removal



trigger to anvil) allows for more access



Only 71 mm head profile design allows for more access in tight spaces

M12 FUEL

M12 FRAIWF38 | M12 FUEL" 9/6" RIGHT ANGLE IMPACT WRENCH WITH FRICTION RING

- Delivers up to 270 Nm fastening torque and 300 Nm nut-busting torque
- 4-Mode DRIVE CONTROL includes Auto Shut-Off Mode and Bolt Removal Mode which prevents over-tightening and provides more control after bolt breakaway
- . The long body profile allows for more access in hard to reach spaces
- Only 71 mm head profile design allows for more access in tight spaces
- ∘ 3/e anvil with friction ring for quick and easy socket changes
- Bright LED workspace illumination . Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS" intelligence hardware and software - which deliver
- outstanding power, run time and durability on the jobsite Flexible battery system: works with all MILWAUKEE[®] M12[™] batteries



| | M12 FRAIWF38-0 |
|-------------------------------|--|
| No load speed (rpm) | 0-1550/ 0-2300/ 0-3000/ 0-3000 |
| Tool reception | % square |
| Impact rate (ipm) | 0-1350/ 0-2700/ 0-3600 |
| Max, torque (Nm) | 270 |
| Max, bolt diameter | M16 |
| Weight with battery pack (kg) | 1.7 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933471700 |



M₁₂ ONEFTR₁₂

M12 FLIEL

M12 FUEL ONE-KEY 1/2 DIGITAL TORQUE WRENCH

M12 ONEFTR38 M12 FUEL" ONE-KEY" 3/6" DIGITAL TORQUE WRENCH

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool
- Provides 16.9 203.4 Nm of torque range and accuracy within ±2% for torque critical fasteners
- Faster, more productive torque reporting with ONE-KEY" providing torque data and customisable reports for inspectors or owners
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm) and 15 available
- Durable design to withstand the most demanding jobsite. environments
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory
- Six pre-programmed languages including English, Spanish and
- Integrates three MILWAUKEE*-exclusive technologies the POWERSTATE* brushless motor, REDLITHIUM* battery pack and REDLINK PLUS" Intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M12" batteries





Replacing the hand tool or two tool installation process





M12 ONEFTR12-0C M12 ONEFTR12-201C Torque range (Nm) 16.9 - 203.4 16.9 - 203.4 CW ±2 %, CCW ±3% CW ±2 %, CCW ±3% Accuracy 15 square No load speed (rpm) 0 - 100 Weight with battery pack (kg) No batteries supplied. No 1 x M12 B2 Battery pack. Kit included charger supplied, Kitbox C12 C Charger, Kitbox 4933464969 4933464970

| 1/2" SHOCKWAVE SOCKET SET (10 | |
|----------------------------------|------------|
| Article Number | 4922252861 |





M12 FUEL

Milwaukee Tool's first digital torque wrench, delivers up to 50% faster

- installation by replacing the hand tool Provides 13.6 - 135.6 Nm of torque range and accuracy within ±2% for
- torque critical fasteners Faster, more productive torque reporting with ONE-KEY* providing torque
- data and customisable reports for inspectors or owners
- · Adjustable run-down torque to control the tools output torque via the motor to prevent over torque
- . Four measurement modes (ft-lb, in-lb, Nm, Kg-cm)
- Durable design to withstand the most demanding jobsite environments · Four notification modes that the tool is reaching, meeting or exceeding the
- torque target (audible, LED, LCD, and vibratory)
- · Six pre-programmed languages including English. Spanish and French
- Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and
- REDLINK PLUS" intelligence hardware and software which deliver
- outstanding power, run time and durability on the jobsite Flexible battery system: works with all MILWAUKEE® M12™ batteries

ONETKE



| | M12 ONEFTR38-00 | M12 ONEFTR38-201C |
|-------------------------------|---|---|
| Torque range (Nm) | 13.6 - 135.6 | 13.6 - 135.6 |
| Accuracy | CW ±2 %, CCW ±3% | CW ±2 %, CCW ±3% |
| Tool reception | % square | % square |
| No load speed (rpm) | 0 - 100 | 0 - 100 |
| Weight with battery pack (kg) | - | 2.5 |
| Kit included | No batteries supplied, No charger supplied, Kitbox | 1 x M12 B2 Battery pack, C12 C Charger, Kitbox |
| Article Number | 4933464966 | 4933464967 |

M12 FIR38LR | M12 FUEL" 3/6" EXTENDED REACH RATCHET

- * With up to 75 Nm of max torque and 200 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair
- The industry leading FUEL** technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- Extended reach ratchet adding additional 82 mm of length for access into tight spaces
- Variable speed trigger provides ultimate control of the tool
- . Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- . The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over nack life
- Supplied with 1/4" adaptor



1.4

Length (mm) Weight with battery pack (kg) Kit included Article Number

M12 FIR14LR M12 FUEL" 1/4" EXTENDED REACH RATCHET

- . With up to 54 Nm of max torque and 250 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- * The industry leading FUEL" technology combined with a reinforced mechanism and investment cast steel voke housing provides greater durability for the professional user
- Extended reach ratchet adding additional 82 mm of length for access into tight spaces
- . Variable speed trigger provides ultimate control of the tool
- · Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- . The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- REDLÍNK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Supplied with 3/6" adaptor

M12 FUEL M12 FIR14LR-0 Tool reception 4" square



| 1/4" SHO | CKWAVE" | IMPAC | T DUT |
|----------|-----------|-------|-------|
| | | | |
| SUCKE | T SET (21 | PG) | |



No batteries supplied, No charger supplied,

No kitbox or bag supplied

4933471500

M12 FIR12 M12 FUEL" SUB COMPACT 1/2" RATCHET

- . With up to 81 Nm of max torque and 175 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- Low profile head design allows users better access in tight spaces
- . The industry leading FUEL" technology combined with a reinforced mechanism and investment cast steel voke housing provides greater durability for the professional user
- * REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- . The LED light illuminates the work area while the on-board fuel gauge displays remaining run time - Supplied with 3/8" adaptor
- . Flexible battery system: works with all MILWAUKEE® M12" batteries



M12 FUEL

| | M12 FIR12-0 |
|------------------------------|--|
| ol reception | 1/2" square |
| ax. torque (Nm) | 81 |
| load speed (rpm) | 0 - 175 |
| ength (mm) | 290 |
| eight with battery pack (kg) | 1,5 |
| t included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| ticle Number | 4933459800 |
| | |

M12 FIR38 M12 FUEL™ SUB COMPACT 3/8" RATCHET

- With up to 75 Nm of max torque and 200 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- · Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- REDLINK PLUS[™] intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 1/4" adaptor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

| | M12 FIR38-0 | M12 FIR38-201B |
|-------------------------------|---|---|
| Tool reception | %" square | %" square |
| Max. torque (Nm) | 75 | 75 |
| No load speed (rpm) | 0 - 200 | 0 - 200 |
| Length (mm) | 281 | 281 |
| Weight with battery pack (kg) | 88 | 1.4 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 1 x M12 B2 Battery pack, C12 C Charger, Tool bag |
| Article Number | 4933459797 | 4933459798 |

M12 FIR14 M12 FUEL" SUB COMPACT 1/4" RATCHET

- With up to 54 Nm of max torque and 250 rpm's, this tool is the ideal fastening solution for automotive mechanics, maintenance and repair professionals
- · Low profile head design allows users better access in tight spaces
- The industry leading FUEL™ technology combined with a reinforced mechanism and investment cast steel yoke housing provides greater durability for the professional user
- REDLINÍK PLUS[™] intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM[®] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Variable speed metal trigger provides ultimate control of the tool
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The LED light illuminates the work area while the on-board fuel gauge displays remaining run time
- Supplied with 3/6" adaptor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12 FUEL

| | M12 FIR14-0 | M12 FIR14-201B |
|-------------------------------|---|---|
| Tool reception | ¼" square | 1/4" square |
| Max. torque (Nm) | 54 | 54 |
| No load speed (rpm) | 0 - 250 | 0 - 250 |
| Length (mm) | 266 | 266 |
| Weight with battery pack (kg) | | 1.1 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 1 x M12 B2 Battery pack, C12 C Charger, Tool bag |
| Article Number | 4933459795 | 4933459796 |

M12 IR | M12" SUB COMPACT RATCHET

- Pneumatic performance with cordless convenience, 47 Nm of torque and no load speed of 250 rpm
- REDLINK[™] overload protection electronics in tool and battery pack deliver best in class system durability
- Reinforced housing provides high durability similar to steel ratchets
- Compact design ideal for tight spaces and small engine bays
- Variable speed metal paddle switch trigger provides greater user control during application
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- On board fuel gauge and LED light added user convenience and illumination in low lit working conditions
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- ∘ Flexible battery system: works with all MILWAUKEE® M12™ batteries



M12

| | M12 IR-201B 1/4 | M12 IR-201B 3/8 |
|-------------------------------|---|---|
| Tool reception | 1/4" square | %" square |
| Max. torque (Nm) | 40 | 47 |
| No load speed (rpm) | 0 - 250 | 0 - 250 |
| Length (mm) | 274 | 274 |
| Weight with battery pack (kg) | 0.9 | 0.9 |
| Kit included | 1 x M12 B2 Battery pack, C12 C Charger, Tool bag | 1 x M12 B2 Battery pack, C12 C Charger, Tool bag |
| Article Number | 4933441725 | 4933441720 |



M18 HCC75R

MISIFORCE OGIC"

M18™ FORCE LOGIC™ HYDRAULIC REMOTE UNDERGROUND CABLE CUTTER

- FORCE LOGIC" hydraulic remote underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force
- Wireless remote communicates with the tool via a mutually exclusive Bluetooth® connection, removing any physical connection to the tool and allowing Linemen to make remote cuts WIRELESSLY
- Balanced design, handle and hang hook enable easiest set-up in vaults
- O Cuts aluminium & copper cables up to 75 mm
- Green LED light on wireless remote gives positive indication that the tool is done cutting
- tool is done cutting

 O Converts from Local to Remote cutting mode easily
 O Open jaw design provides easiest access in trenches
- POWERSTATE" brushless motor provides increased efficiency, lasts longer and delivers maximum power
- ONE-KEY" technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- ONE-KEY" tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- REDLINK" individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM[™] battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18st batteries



| | M18 HCC75R-502C |
|---|--|
| Cutting force (kN) | 77.8 |
| Max. cutting diameter (mm) | 75 |
| Cutting time (s) | <10 |
| Weight with battery pack (kg) | 7.9 |
| Kit included | 2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox |
| THE RESERVE AND ADDRESS OF THE PARTY OF THE | 1000120021 |



Article Number 49162774





Allowing Linemen to make remote cuts WIRELESSLY by removing any physical connection to the tool



Balanced design, handle and hang hook enable easiest set-up in yaults



Open jaw design provides easiest access in trenches

M18 HCC75 M18" FORCE LOGIC" HYDRAULIC UNDERGROUND CABLE CUTTER

 FORCE LOGIC[™] hydraulic underground cable cutter cuts cables in less than 10 seconds with 77.8 kN of force

Brushless POWERSTATE™ motor provides more power, more run time and longer life

· Cuts aluminium and copper cables up to 75 mm

 In-line design delivers easiest access in trenches and a secure stand during cable cuts

- Versatile top-handle can also be used as a stand and provides balanced cut alignment
- 340° rotatable head powered by a 77.8 kN hydraulic pump delivers best in class cut speed
- ONE-KEY^d technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- ONE-KEY" tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- REDLINK[™] individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18th batteries



4933459268

ONETKEY MIS FORCELOGIC

4933459269



Article Number

| Acres 644 | | | | | | | | 100 | | |
|-----------|----|----|----|----|----|---|----|-----|---|----|
| UND | ER | GR | ou | ND | CU | т | ER | В | ᄔ | DE |
| M18 | | | | | | | | | | |





ONE TKEY MIS FORCELOGIC

4933459266

M18 HCC45 M18" FORCE LOGIC" HYDRAULIC 44 MM CABLE CUTTER

- FORCE LOGIC™ hydraulic cable cutter cuts ACSR/ACSS cables in less
- than 9 seconds with 77.8 kN of force
- Patent pending jaw design enables opening with just two fingers,
- enhancing alignment while delivering easiest operation with Class 3 gloves - Wire automatically closes the jaw, providing hands-free jaw closure and
- the easiest mid-span cuts. Fully balanced design delivers the best control • Cuts ACSR and ACSS transmission line cables up to 44 mm
- 340° rotatable head powered by a 77.8 kN hydraulic pump delivers the fastest transmission wire cuts for enhanced productivity
- Brushless POWERSTATE™ motor provides more power, more run time and longer life
- ONE-KEY* technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information wirelessly to the cloud
- ONE-KEY** tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention
- REDLINK** individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM[™] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- * Flexible battery system: works with all MILWAUKEE® M18" batteries



| | M18 HCC45-0C | M18 HCC45-522C |
|-------------------------------|---|--|
| Cutting force (kN) | 77.8 | 77.8 |
| Max. cutting diameter (mm) | 44 | 44 |
| Cutting time (s) | <9 | <9 |
| Weight with battery pack (kg) | | 6.0 |
| Kit included | No batteries supplied, No charger supplied, Kitbox | 1 x M18 B5, 1 x M18 B2 Battery packs, M12-18 I Charger, Kitbox |

4933459265



Article Number 49162775





M18 ONEHCC | M18" FORCE LOGIC" HYDRAULIC 35 MM CABLE CUTTER



- FORCE LOGIC™ hydraulic cable cutter cuts cables in less than 3 seconds with 53 kN of force
- with 53 kN of force

 Brushless POWERSTATE" motor provides more power, more run-time and
- longer life
- · Fully balanced tool provides secure control during one hand operation
- One tool provides cutting solutions for ACSR wire, steel guy wire, fine
- stranded or standard copper and aluminium cable
- · Quick jaw reception enables user to retool for a complete new application
- in less than 15 seconds

 Compact in-line and slim jaw design with 350° rotatable head allows easy
- cuts, even in narrow spaces
- ONE-KEY[®] technology allows operator to view tool usage, receive notifications for recommended maintenance and sync information
- wirelessly to the Cloud



| | M18 ONEHCC-DC CWAL- SET | M18 ONEHCC-201C CU/AL-SET | M18 ONEHCC-OC ACSR SET | M18 ONEHCC-201C ACSR SET | M18 ONEHCC-OC FSW SET | M18 ONEHCC-201C FSW SET | M18 ONEHCC-OC SWA SET |
|-------------------------------|---|--|---|--|---|--|---|
| Cutting force (kN) | 53 | 53 | 53 | 53 | 53 | 53 | 53 |
| Max. cutting diameter (mm) | 35 | 35 | 22.5 | 22.5 | 35 | 35 | 35 |
| Cutting time (s) | <3 | <3 | <3 | <3 | <3 | <3 | -3 |
| Suitable for cutting material | Cu & AL cable (Class 1-4) | Cu & AL cable (Class 1-4) | AL conductor steel reinforc | edAL conductor steel reinforce | Flexible fine stranded cable (Class 5) | Flexible fine stranded cable (Class 5) | Steel wire armored Cu/ AL cable |
| Weight with battery pack (kg) | 17 - 11 | 3.7 | . #X | 3.7 | | 3.7 | |
| Standard equipment | Cu/AL jaw | Cu/AL jaw | ACSR jaw | ACSR jaw | FSW jaw | FSW jaw | SWA jaw |
| Kit included | No batteries supplied, No charger supplied, Kitbox | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox | No batteries supplied, No charger supplied, Kitbox | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox | No batteries supplied, No charger supplied, Kitbox | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox | No batteries supplied, No charger supplied, Kitbox |
| Article Number | 4933464300 | 4933464301 | 4933464303 | 4933464304 | 4933464308 | 4933464309 | 4933464306 |

M18 ONEHCC HYDRAULIC CABLE CUTTER JAWS AND BLADES

| | Description | Article Number | | F |
|----|---|----------------|----|----|
| 1. | Cable outlier jaw and blade set for outling copper/aluminium. Copper/ aluminium standard stranded cable up to 4 x 50 mm², 1 x 500 mm² in aluminium and 1 x 400 mm² in copper. Not satiable for fine stranded/ highly flexible cable. Max. cutting 035 mm | 4932430839 | ¥ | 3. |
| | Cu/A standard copper & aluminium cable cutting blades. The blades fit for the Cu/Al cutting javes for MT8HCC & OHEHCC cutters + M18 HCCT crimper cutting jave. | 4932464498 | 1. | |
| 2. | Cable cutter jaw and blade set for cutting aluminium-steel transmission cable. ACSS-aluminium conductor steel supported cable and ACSR-aluminium conductor steel supported cable and ACSR-aluminium conductor steel reinforced cable in s. 94-1.1 To STIM (EM 50182), Not suitable for armound cable or steel rods. Max. cutting Ø22.3 mm | 49162773 | W | 4. |
| | Replacement cable cutter blades for ACSR-jaw. Not suitable for armoured cable or steel rads. | 48440412 | L | 5. |

| _ | Description | Article Number | |
|-----|--|----------------|----|
| 3. | Cutling jaw and blades for EHS grade guy wire, stay wire & steel wire according to DM49201/3 guy wire of grade ST1/ST2/ST3. Not sustable for fine stranded steel ropes. Max. cutting Ø15 mm | 49162777 | 4 |
| 200 | EHS guy wire/steel wire cutting blades | 48442777 | T |
| 4 | Cable cutter jaw and biades for class 5 fine stranded wire and class 6 finest stranded wire according to IEC 00228/DIN VDE 0295 standards. Also suitable for high flexible data- and telecomoable. Not suitable for thick stranded cables. Max. cutting 635 mm | 49162778 | ¥ |
| | FSW fine stranded wire cutting blade | 48442778 | 11 |
| 5. | Armored cable cutting Jaw for M18 HCC | 4932464867 | ¥ |

M18 HKP M18" FORCE LOGIC" HYDRAULIC KNOCKOUT PUNCH

- FORCE LOGIC[™] hydraulic knockout punch is the most compact and lightweight tool on the market with 60 kN of force
- The easiest way to punch for fast, accurate, round, and burr free holes
- Highest accuracy due to industry's finest exact alignment system for dies
- Best balanced tool and easiest control due to one hand operation
 Quick connector allows easy set-up of punch and die without carrying the weight of the tool
- Tool punches up to Ø100 mm holes into 3.0 mm mild steel or 2.5 mm stainless steel
- Compatible with most common punches and dies available on market
- Easiest, less strenuous and nonexpendable way of making holes into sheet metal
- On board fuel gauge and LED light
- REDLINK[®] individual battery cell monitoring optimises tool run time and ensures long term pack durability
- REDLITHIUM[®] battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18th batteries





| | M18 HKP-201C | M18 HKP-201CA | |
|-------------------------------|--|---|--|
| Punching force (kN) | 60 | 60 | |
| Max. punching diameter (mm) | 100 | 100 | |
| Max. material thickness (mm) | 2.5 in stainless and 3.0 in mild steel | 2.5 in stainless and 3.0 in mild steel | |
| Standard equipment | 11.1mm (⁷ /si) draw stud, 19mm (⁹ /si) draw stud, quick connector, ball pull, adapter | 11.1mm ("/vi") draw stud, 19mm ("/vi") draw stud, quick connector, ball pull, adaptor, punches and die M16, M20, M25, M32, M4 | |
| Weight with battery pack (kg) | 2.3 | 2.3 | |
| Kit included | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox | 1 x M18 B2 Battery pack, M12-18 C Charger, Kitbox | |
| Article Number | 4933451202 | 4933451204 | |

M18 HKP HYDRAULIC KNOCKOUT PUNCH ACCESSORIES

| Article Number | Diameter (mm) | Description | | Article Number | Diameter (mm) | Description |
|----------------|---------------|-------------|-----|----------------|---------------|--------------|
| 4932430913 | 16.2 | Die M16 | | 4932430841 | 16.2 | Punch M16 |
| 4932430915 | 22.5 | Die PG16 | | 4932430843 | 22.5 | Punch PG16 |
| 4932430914 | 20.4 | Die M20 | | 4932430842 | 20.4 | Punch M20 |
| 4932430917 | 28.3 | Die PG21 | | 4932430845 | 28.3 | Punch PG21 |
| 4932430916 | 25.4 | Die M25 | | 4932430844 | 25.4 | Punch M25 |
| 4932430918 | 32.5 | Die M32 | | 4932430846 | 32.5 | Punch M32 |
| 4932430919 | 40.5 | Die M40 | | 4932430847 | 40.5 | Punch M40 |
| 4932430920 | 50.5 | Die M50 | | 4932430848 | 50.5 | Punch M50 |
| 4932430921 | 63.5 | Die M63 | 1 1 | 4932430849 | 63.5 | Punch M63 |
| | | | | 49162680 | 1.1 mm (//si) | Draw bolt 11 |
| | | | | 49162681 | 19 mm (%) | Draw bolt 1 |



Max. pressure (bar / PSI)

Consumable oil volume (I) Weight with battery pack (kg)

Coupler type

Kit included

Article Number

M18 HUP700

MIBIFORCELOGIC"

M18™ HYDRAULIC UTILITY PUMP

- FORCE LOGIC" hydraulic utility pump powers every single acting 700 bar crimping, cutting or punching head attachment
- Significantly faster work cycles due to a large 1.6 litre total oil reservoir and 2x higher flow rate compared to other pumps
- The pump is equipped with a industry standard CEJN Series 115, G1/4" female quick connection coupler to suit most common attachments
- 1.8 meter long corded controller enables user to work away from pump and can be extended up to 7 meters with accessory extension
- IP54 rated ingress protection with sealed battery door delivers best protection in harsh environments such as dirt, dust and moisture
- ONE-KEY technology allows linemen to view tool usage, receive notifications for recommended maintenance, and sync information
- wirelessly to the cloud Well balanced lifting handle provides even weight distribution for easy transportation from truck to bucket
- o PFM" (Predictive Force Monitoring) provides you with instant pressure verification via a green indicator
- Brushless POWERSTATE motor provides more power, more run time and longer life
- REDLINK* individual battery cell monitoring optimises tool run time and ensures long term pack durability

M18 HUP700-121 700 / 10.000

CEJN G1/4"

4933471813

1 x M18 HB12 Battery pack, M12-18 FC

Charger, No kitbox or bag supplied



ONETKEY



1.8 meter long corded controller enables user to work away from pump.



Well halanced lifting handle



ONE-KEY" technology allows linemen to view tool usage, receive notifications

M18 HUP700 HYDRAULIC PUMP SYSTEM ATTACHMENTS





| 1.8 m extension cord for M18 HUP controller | Bucket hanger for M18 HUP700 | Replacement oil M18 HUP700 |
|--|--|--|
| Compatible with M18" FORCE LOGIC" hydraulic pump IP 57 ingress protection for reliable use in the elements Male-lemale connectors for interconnectable extension up to 7.3 m of length | Competible with M18" FORCE LOGIC" hydraulic pump Extendable bar 8 rubber humpers allow for use with most existing buckets 8 steel baskets Symmetrical lift ring design enable use from both sides of the hanger Keeps pump in ideal, level operating position while freeing up space inside the bucket Standard size lift rings allow for use with existing bucket hooks | 1 Liter accessory oil for M18" FORCE LOGIC" HUP700 hydraulic pump |
| 40100775 | 10100770 | 1000170001 |



M₁₈ FPFT MIS FUEL

M18 FUEL™ POWERED FISH TAPE

- o The M18 FUEL" Fish Tape is the world's first professional battery powered cable pulling solution
- POWERSTATE" brushless motor that provides the ability to pull a maximum length of 72 m wire
- · AUTO-RUN" powered feeding and cable pulling is a fast and
- efficient solution providing higher productivity vs other solutions Less user fatigue due to powered wire pulling, especially when working on overhead installations
- Quick tool free drum exchange with 4 compatible interchangable drums, Steel Tape: 36 and 72 m / Non-conductive Tape: 30 and 60 m
- o Proprietary anti-binding drum design for smoother feeding and
- Variable speed trigger for maximum control during tape feeding and wire pulling
- Integrates three MILWAUKEE*-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18® batteries

Weight with battery pack (kg)

Kit included

Article Number





pulling solution



AUTO-RUN" powered feed & retract



No mess retracting cable, anti-binding

M18 FUEL™ FISH TAPE COMPATIBLE DRUMS

M18 FPFT-202 M18 FPFT-202

30m NC Set

36m ST Set

plied, No charger plied, No charger supplied, No kilbox kilbox or bag or bag supplied supplied supplied

4933471952 4933471953 4933471954

No batteries sup- Battery packs,

| | Description | Article Number | | | Description | Article Number | |
|------------------|--------------------------------|----------------|--|----------------------|---------------------------------------|----------------|---|
| Steel figh drums | 36 m x 3 mm steel fish drum | 48445176 | | Non-conductive drums | 30 m non-conductive polyester drum | 48445195 | 0 |
| | 72 m x 3 mm steel fish drum | 48445178 | | | 60 m non-conductive polyester drum | 48445197 | 0 |

M18 FLAG230XPDB

MIS ELIEL

M18 FUEL™ 230 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH

- The world's first single 18V battery operated large angle grinder that delivers the power to grind, lighter than corded tools and makes up to 68 cuts per charge in 42 mm stainless steel pipe
- Next generation POWERSTATE" brushless motor, REDLINK PLUS" electronics and REDLITHIUM" HIGH OUTPUT" 12.0 An battery pack deliver superior performance, durability and run time in high demand
- Disc brake slows the disc down faster for improved user protection Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Keyless guard for great cutting capacity and fast guard adjustment
- without using a key

 FIXTEC nut for tool-free disc change

No load speed (rpm)

FIXTEC™ flange nut

Article Number

Max. cutting depth (mm)

Weight with battery pack (kg)

- Anti-vibration side handle for lower vibration
- Removable dust screen to prevent debris entrance, prolonging motor life





Removable dust screen to prevent



| DUST GUARD FOR CUTTING | | |
|------------------------|------------|---|
| Article Number | 4932459341 | - |



M18 FLAG180XPDB M18 FUEL* 180 MM LARGE BRAKING GRINDER WITH PADDLE SWITCH M18 FUEL

- The world's first single 18V battery operated large angle grinder that delivers the power to grind, lighter than corded tools and makes up to 68 cuts per charge in 42 mm stainless steel pipe
- Next generation POWERSTATE™ brushless motor, REDLINK PLUS™ electronics and REDLITHIUM" HIGH OUTPUT" 12.0 Ah battery pack deliver superior performance, durability and run time in high demand applications
- Disc brake slows the disc down faster for improved user protection
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up
- Keyless guard for great cutting capacity and fast guard adjustment without using a key
- FIXTEC[®] put for tool-free disc change
- Anti-vibration side handle for lower vibration
- · Removable dust screen to prevent debris entrance, prolonging motor life



| M18 FLAG18UXPUB-0 |
|--|
| 6600 |
| 180 |
| 40 |
| M14 |
| 5.1 |
| Yes |
| Paddle (Deadman) switch |
| Yes |
| Yes |
| Yes |
| No batteries supplied, No charger supplied |
| No kitbox or bag supplied |
| 4933464112 |
| |



HD18 AG-125 M18" 125 MM ANGLE GRINDER WITH PADDLE SWITCH

High performance 4-pole motor delivers maximum power whilst

(optimising) maximising the power to weight ratio REDLINK[®] overload protection electronics in tool and battery pack deliver

best in class system durability

- Full metal gear case delivers heavy duty durability

- Reduced height of gear box and slim girth design deliver optimum

Non-lockable switch for best user protection and preventing automatic.

 Burst resistant and tool-free safety guard for best user protection and fast adjustment

· Multi position side handle for ease of use

 Individual battery cell monitoring optimises tool run time and ensures long term pack durability

· Fuel gauge displays remaining charge

· REDLITHIUM" battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life

• Flexible battery system: works with all MII WALIKEE® M18" batteries.



| | HD18 AG-125-0 | HD18 AG-125-402C |
|--------------------------------|---|--|
| No load speed (rpm) | 9000 | 9000 |
| Disc diameter (mm) | 125 | 125 |
| Max. cutting depth (mm) | 33 | 33 |
| Spindle size | M 14 | M 14 |
| Weight with battery pack (kg) | | 2.2 |
| Brake | No | No |
| Switch type | Paddle (Deadman) switch | Paddle (Deadman) switch |
| FIXTEC [™] flange nut | No | No |
| Line lock out function | No | No |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M18 B4 Battery packs M12-18 C Charger, Kitbox |
| Article Number | 4933441502 | 4933441507 |

HD18 AG-115 M18" 115 MM ANGLE GRINDER WITH PADDLE SWITCH

. High performance 4-pole motor delivers maximum power whilst

(optimising) maximising the power to weight ratio

REDLINK overload protection electronics in tool and battery pack deliver best in class system durability

Full metal gear case delivers heavy duty durability

Reduced height of gear box and slim girth design deliver optimum.

. Non-lockable switch for best user protection and preventing automatic

Burst resistant and tool-free safety guard for best user protection and fast

adjustment . Multi position side handle for ease of use

 Individual battery cell monitoring optimises tool run time and ensures long term pack durability

- Fuel gauge displays remaining charge REDLITHIUM" battery pack provides superior pack construction.

electronics and fade-free performance to deliver more run time and more work over pack life

» Flexible battery system: works with all MILWAUKEE® M18" batteries.



| | HD18 AG-115-0 | HD18 AG-115-402C |
|---------------------------------|---|---|
| No load speed (rpm) | 9000 | 9000 |
| Disc diameter (mm) | 115 | 115 |
| Max. cutting depth (mm) | 28 | 28 |
| Spindle size | M 14 | M 14 |
| Weight with battery pack (kg) | 1.5 | 2.4 |
| Brake | No | No |
| Switch type | Paddle (Deadman) switch | Paddle (Deadman) switch |
| FIXTEC TM flange nut | No | No |
| Line lock out function | No | No |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M18 B4 Battery packs, M12-18 C Charger, Kithox |
| Article Number | 4933411210 | 4933441300 |
| | | |

M18 FAP M18 FUEL" POLISHER

- Brushless POWERSTATE" motor to deliver the ultimate mobility in car polishina
- REDLINK PLUS" intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM³⁴ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life

 World's first cordless polisher with 8 position variable speed selection ranging from 360 - 2200 rpm

· Outstanding run time to polish one full size car per battery charge

Constant speed electronics with soft start for smooth start up

Maximum polishing accessory diameter of 180 mm

· Removable dust screen to prevent debris ingress, prolonging motor life Rubber overmold gear case for increased comfort, especially when working with the tool vertically

* Lock-on function provides more comfortable use when polishing for longer

3 position bale handle for improved tool control

MIS FLIEL



| Yes | TEIS |
|---|--|
| Yes | Yes |
| Polishing backing pad, dust screen, bale handle, AVS side handle | Polishing backing pad, polishing sponge white, polishing sponge orange, lambswool, dust screen, bale handle, AVS side handle |
| No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M18 B5 Battery packs M12-18 FC Charger, HD Box |
| 4933451549 | 4933451550 |
| | Polishing backing pad, dust screen, bale handle, AVS side handle No batteries supplied, No charger supplied, No kiltbox or bag supplied |

Paddle (Deadman) switch Paddle (Deadman) switch

No batteries supplied No. 1 x M18 HB12 Sattery pack

charger supplied, Kitbox M12-18 FC Charger, Kitbox

4933464115



M18 ONESLDP M18" ONE-KEY" LED COMPACT SITE LIGHT CHARGER

- Optimise brightness and run time by adjusting the light output from 0 - 9000 Lumens
- ONE-KEY[®] tool customisation allows user to control brightness and set light settings remotely
- ONE-KEY" tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft
- Program automatic schedules to decide during which days/times the light is running.
- Integrated M18" charger charges up to 2 batteries sequentially
 Dual power source, powered by either M18" REDLITHIUM" battery packs
- or use of 2.5 m hardwired cord

 AC outlet gives the possibility to string multiple lights together
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions.
 IPS4 rating in battery mode – light is protected from dust and splashing.
- water

 "TRUEVIEW" high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail



| | M18 ONESLDP-0 |
|--|--|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18™ batteries |
| Bulb type | LED |
| Max. light output High/Medium/Low/Stro (Lumens) | be 9000 / 4800 / 2500 / - |
| Max, run time with M18 B9 battery (h) | 3.5/7/14/- |
| Weight with battery pack (kg) | 12.1 |
| Kit included | No batteries supplied, No charger supplied. No kitbox or bag supplied |
| Article Number | 4933459160 |

ONE TRUEVEW

ONETKEY TRUEVEW

TRUEVEW M18

HOBL 7000 HIGH OUTPUT BAY LIGHT

| TRUEVIEW | high definition lighting - 7700 Lumens of even light output for | r |
|------------------------------|---|---|
| best jobsite | lumination (110 Lumens / Watt) | |

- Impact resistant polycarbonate lens withstands drops from up to 2.7 m
- Integrated wiring terminal accepts voltages from 90 277 V, allows easy wiring and stringing of multiple lights
- Wire strain relief accepts cables up to H07RNF 3 x 2.5 mm²
- Spring-loaded cable retention allows easy adjustment of installation height with 1.2 m steel hanging cable
- 4 m AC power cord for out of the box operation
- Conical lens design and small footprint allow simple storage and safe stacking of up to 3 units



TRUEVEW"

| | H0BL 7000 | |
|------------------|---------------------------|--|
| Voltage (AC) (V) | 90 - 277 | |
| Bulb type | LED | |
| Weight (kg) | 3.7 | |
| Supplied in | No kitbox or bag supplied | |
| Article Number | ticle Number 4933464126 | |

M18 ONESLSP M18" ONE-KEY" LED COMPACT SITE LIGHT

- ONE-KEY" tool customisation allows user to control brightness and set light settings remotely
- ONE-KEY^{is} tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft
- Optimise brightness and run time by adjusting the light output between 0 - 4400 Lumens
- Program automatic schedules to decide during which days/times the light is running
- * TRUEVIEW* high definition lighting solutions combine the most advanced LED technology
- 180° and 360° electronic light control for large area and task lighting
 Self-centering metal hook designed for hanging the light from studs or
- Self-centering metal hook designed for hanging the light from studs or pipes
 Dual power source, powered by either M18** REDLITHIUM** battery packs.
- or use of 2.5 m hardwired cord
- AC outlet gives the possibility to string multiple lights together
- Up to 8 hours of run time on low setting when powered by an M18" REDLITHIUM" 5.0 Ah battery pack



| | M18 ONESLSP-0 |
|--|--|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18" batteries |
| Buib type | LED |
| Max. light output High/Medium/Low/Stro (Lumens) | ^{be} 4400 / 2100 / 1000 / - |
| Max. run time with M18 B5 battery (h) | 2/4/8/- |
| Weight with battery pack (kg) | 5.4 |
| Kit included | No batteries supplied, No charger supplie No kitbox or bag supplied |
| Article Number | 4933459156 |

M18 TAL | M18" TRADESMAN AREA LIGHT

- TRUEVIEW" high definition lighting with 2,200 Lumens of light output in Area mode and 1,000 Lumens in Flood mode
- Advanced LED technology provides 360° of area light, while an independent array of LEDs on the side provide 90° of task lighting
- independent array of LEDs on the side provide 90" of task lighting.

 Compact design allowing for one-handed transport on the jobsite, with a built-in carry handle.
- Impact polycarbonate lens design that is impact and chemical resistant, delivering superior impact durability
- Equipped with a 10.8 cm self-centering metal hook, users can hang the light overhead on studs and piping
- Low battery indicator, light flashes when battery pack is low on charge
 Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 TAL-0 |
|---|--|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18" batteries |
| Builb type | LED |
| Max, light output Area Mode High/Medium Low (Lumens) | ^{1/} 2200 / 1100 / 550 |
| Max. light output Flood Mode High/ Medium/Low (Lumens) | 1000 / 500 / 250 |
| Max, run time with M18 B5 battery (h) | 4/8/16 |
| Weight with battery pack (kg) | 2.5 |
| Kit included | No batteries supplied, No charger supplied. No kitbox or bag supplied |
| Article Number | 4933464134 |

MXF TL MX FUEL™ TOWER LIGHT

- TRUEVIEW" high definition light output with up to 27,000 Lumens in AC and up to 20,000 Lumens in DC mode for both task and area lighting
- Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed
- Low weight of 48 kg with the two big all-terrain wheels, this tower light is easy to transport across wet and uneven job site terrains with minimum effort
- Due to the motorised mast, the tower light is capable to be set up in less than 10 sec. The mast is extendable up to 3.10 meter and can withstand up to 55 km/h of wind
- To withstand the toughest conditions on the toughest job sites, the MX FUEL" Tower Light is built with a durable, high impact polycarbonate lenses that delivers superior impact durability
- A sealed battery box ensures batteries are kept protected from the elements at all times
- Integrated ONE-KEY" application for customise, track, and manage from your mobile device. Easy to set the run time which will adjust the output to give constant illumination for the job at hand, and check the remaining battery charge to know when it's time to change the battery

| | MXFTL-601 |
|--|--|
| System | MX FUEL** |
| Battery compatibility | All MX FUEL" batteries |
| Bulb type | LED |
| Max, AC light output High/Medium/Low/ Strobe (Lumens) | 27,000/ 14,000/ 7000/ - |
| Max. DC light output High/Medium/Low/ Strobe (Lumens) | 20,000/ 10,000/ 5000/ - |
| Max, run time AC mode (h) | Endless |
| Max. run time BC mode (h) | 3/6/12 |
| Max. mast height (m) | 3.1 |
| Weight with battery pack (kg) | 48.0 |
| Kit included | 1 x MXF XC406 Battery pack, Integrated Charger, No kitbox or bag supplied |
| Article Number | 4933471844 |
| | |







Due to the motorised mast, the tower light is capable to be set up in less than 10 sec.



Has the ability to manoeuvre the light heads in multiple orientations, allowing the user to direct light to wherever it's needed



A sealed battery box ensures batter are kept protected from the elemen at all times



M18 ONERSAL | M18" ONE-KEY" LED REMOTE STAND LIGHT

- Optimise brightness and run time by adjusting the light output from
- 0 5400 Lumens ONE-KEY** tool customisation allows user to control brightness and set
- light settings remotely · ONE-KEY" tool tracking & security offers a cloud-based inventory
- management platform that supports both location tracking and theft prevention
- · IP67 allows use in all weather conditions (heavy rain, snow, dusty environments)
- Reinforced leg design with 3 different leg deployment options for best durability and stability
- Highly durable and impact resistant polycarbonate lens and all aluminium cam design to protect the light from rough working conditions
- TRUEVIEW* high definition light output delivers consistent beam,
- optimised colour temperature and true representation of colours and detail Sealed battery compartment for up to 2 packs to extend run time
- . Change height from 0.5 m to 1.65 m to cast light from overhead to limit
- Collapsible to only 55 cm for easy storage and transportation



ONE TRUEVEW

| | M18 ONERSAL-0 |
|---|--|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18" batteries |
| Bulb type | LED |
| Max. light output High/Medium/Low/Strobe (Lumens) | 5400 / 3000 / 1550 / - |
| Max. run time with M18 B9 battery (h) | 7/12.5/26/- |
| Weight with battery pack (kg) | 9.1 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933459431 |
| | |

M18 SAL M18" LED STAND LIGHT

- TRUEVIEW™ high definition lighting
- . Twelve high performance LEDs provide 2000 Lumens on high light output which is brighter than 250 Watt halogen
- Impact resistant adjustable head with highly durable polycarbonate lens can be rotated 230° vertically and pivoted 240° horizontally
- · Protective guard secures the head and lens when the light is collapsed for
- storage or transport Extendable mast which reaches from 1.10 m to over 2.20 m to light up
- work spaces from top without casting shadows
- . IP54 protected from dust and splashing water
- . Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- · Carry handles on two positions for easy one handed transport; weight is evenly balanced when compressed
- . Low battery indicator light flashes when battery pack is low



TRUEVEW MIS

TRUEVEW M12

| | M18 SAL-0 | M18 SAL-502B |
|---|---|--|
| System | M18 | M18 |
| Battery compatibility | All MILWAUKEE® M18™ batteries | All MILWAUKEE® M18" batteries |
| Bulb type | LED | LED |
| Max, light output High/Medium/ Low/Strobe (Lumens) | 2000 / 1300 / 850 / - | 2000 / 1300 / 850 / - |
| Max. run time with M18 B5 pattery (h) | 4/6/10/- | 4/6/10/- |
| Weight with battery pack (kg) | ie. | 7.3 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | 2 x M18 B5 Battery packs, M12-18 C Charger, Tool bag |
| Article Number | 4933451246 | 4933451896 |
| | | |

M18 HOSALC AVAILABLE SOON

M18™ HIGH OUTPUT STAND AREA LIGHT CHARGER

- 6000 Lumens TRUEVIEW of High Definition Output
- Up to 10 hours of run time on M18" REDLITHIUM" 8.0 Ah battery
- pack

 o 3 impact resistant adjustable heads with highly durable lens can be rotated 180° vertically and pivoted 240° horizontally to have the perfect workplace
- Integrated M18
- charging AC/DC versatili
- mains plug supp o IP34 rating, the I
- work engage for Compact footo
- reinforced nylon
- Full length carry available M18
- Low battery indi charge

Max run, time with M1 Kit included

| e illumination | voted 240 Horizontally to have the | |
|---|---|--|
| | 1 AMP USB output for USB device | |
| ight is protected which reaches to without cont with low cent legs to protect handle rail that REDLITHIUM" is | AlLWAUKEE® M18" batteries, or of from dust and spisashing waters from 1 m to over 2.2 m to light up sating shadows tre of gravity and impact resistant against abusive jobsite conditions allows balanced carry with all satiefries see when battery pack is low on | |
| | M18 HOSALC-0 | T T |
| | M18 | |
| | All MILWAUKEE® M18 " batteries | A CONTRACTOR OF THE CONTRACTOR |
| ledium/Low/Strobe | 6000 / 4000 / 1700 /- | //n/\ |
| HB8 battery (h) | 3.5/5/10 | // Alk W |
| k (kg) | 11.1 | |
| 111/16S | No batteries supplied, No charger supplied, No kitbox or bag supplied | |
| | 1000170110 | A SAN |





M18

Integrated 2.1 AMP USB output for



Twelve high performance LEDs that provide up to 6000 Lumens



M12 SAL M12" STAND LIGHT

- TRUEVIEW™ high definition lighting.
- = 12 high performance LEDs provide 1400 Lumens on high light output
- . Impact resistant adjustable head with highly durable polycarbonate lens to
- withstand drops up to 3 m
- Head can be rotated 210° vertically and pivoted 270° horizontally to have the best perfect workplace illumination
- · Protective guard secures the head and lens when the light is collapsed for
- storage or transport Extendable mast which reaches from 0.91 m to over 1.72 m to light up
- work spaces
- . Compact footprint with low center of gravity and impact resistant reinforced nylon legs to protect against abusive jobsite conditions
- . Carry handles on 2 positions for easy one handed transport; weight is evenly balanced when compressed
- . Low battery indicator light flashes when battery pack is low



M12 SAL-0 All MILWAUKEE® M12" batteries Battery compatibility

Bulb type Max. light output High/Medium/Low/Strobe 1400 / - / 700 / -(Lumens) Max. run time with M12 B4 battery (h) 4/-/10/-Weight with battery pack (kg) 3.4 No batteries supplied, No charger supplied, Kit included No kitbox or bag supplied Article Number 4933464823

M18 POALC | M18" PACKOUT" AREA LIGHT CHARGER

- . Three independent pivoting light heads provide 3000 Lumens of TRUVIEW" High Definition Output
- All three pivot light heads combined provide up to 12 hours of run time on
- a M18" REDLITHIUM" 5.0 Ah battery pack
- IP54: water and dust resistant *Built in charger function for quick and convenient charging of any M18" battery or electric devices via the 2.1 AMP USB output port
- * Full system compatibility with the PACKOUT " Modular Storage System lighting on and off the stack
- *AC/DC versatility: Powered by MILWAUKEE® M18" batteries, or mains plug supply
- . Storage compartment for devices and small items
- 9 total output modes to manage output or run time
- Low battery indicator, light flashes when battery pack is low on charge



TRUEVEW" M18

| | M18 POALC-0 |
|---|---|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18™ batteries |
| Bulb type | LED |
| Aax. light output High/Medium/Low/Stro Lumens) | ^{be} 3000 / 1500 / 1000/ - |
| Max. run time with M18 B5 battery (h) | 12/8/4 |
| Veight with battery pack (kg) | 5.9 |
| Cit included | No batteries supplied, No charger supplied No kitbox or bag supplied |
| Article Number | 4933478120 |





M18 HOAL M18" HIGH OUTPUT AREA LIGHT

- 4000 Lumens TRUEVIEW[™] of High Definition Output
- Up to 12 hours of run time on M18" REDLITHIUM " 5.0 Ah battery pack
- 120° rotatable light head and integrated key holes for horizontal and vertical hanging
- Impact resistant design and durable roll cage to protect the light from rough jobalte conditions
 AC/DC versatility: Powered by MILWAUKEE® M18" batteries, or mains
- plug supply

 Easy one-handed transport with built-in carry handles
- Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries



1 = {U = V = W M18

TRUEVEW M18

TRUEVEW M12

M18 PAL M18" PIVOTING AREA LIGHT

- TRUEVIEW[®] high definition lighting with up to 1500 Lumens and up to 20 hours of run time, allows replacement of 500 W halogen
- Two powerful magnets, a spring loaded clamp and a folding rotating light head design provide multiple mounting options and illumination possibilities from any angle
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Most compact M18" flood light designed for the on-the-go needs of service and maintenance trades
- . IP54 rating, the light is protected from dust and splashing water
- Integrated handle/tie off zone, designed to be carried or tethered while used on a scissor lift
- · Low battery indicator, light flashes when battery pack is low on charge
- Flexible battery system: works with all MILWAUKEE® M18" batteries



TRUEVEW" M18

TRUEVEW" M12

M18

| M18 PAL-0 |
|---|
| M18 |
| All MILWAUKEE® M18" batteries |
| LED |
| 1500 / 600 / 300 |
| 4.5 / 10 / 20 |
| 2.1 |
| No batteries supplied, No charger supplied No kitbox or bag supplied |
| 4933464105 |
| |

M18 AL M18" LED AREA LIGHT

- · TRUEVIEW" high definition lighting
- Eight high performance LEDs provide 1500 Lumens of light output up to 30% brighter than 250 W halogen lights
- Compact roll cage design provides superior durability
- Compact roll cage design provides superior durability
 Convenient built-in handle ability to hang vertically or horizontally
- Flexibility to mount vertically on a max. 13 mm diameter pipe, threaded rod
- or rebar to maximise hands-free operation
- Flexible battery system: works with all MILWAUKEE® M18 batteries



| | M18 AL-0 |
|--|---|
| System | M18 |
| Battery compatibility | All MILWAUKEE® M18" batteries |
| Buib type | LED |
| Max. light output High/Medium/Low/Stro (Lumens) | ^{be} 1500 / - / 780 |
| Max. run time with M18 B5 battery (h) | 5/10 |
| Weight with battery pack (kg) | 2.1 |
| Kit included | No batteries supplied, No charger supplied Blister packaging |
| Article Number | 4932430392 |

M12 PAL M12 " PIVOT AREA LIGHT

- TRUEVIEW™ high definition lighting with up to 700 Lumens
- Up to 8 hours of run time on M12" 4.0 Ah battery pack
- With powerful magnets as well as a rotating light head design with 40°
- rotation in each direction to provide multiple beam options
- . Highly durable and impact resistant design to withstand drops up to 3 m
- Most compact M12" flood light designed for the on-the-go needs of service and maintenance trades
- +2.1 AMP USB output for USB device charging
- . IP54 rating, the light is protected from dust and splashing water
- . Low battery indicator, light flashes when battery pack is low on charge
- *Flexible battery system: works with all MILWAUKEE® M12" batteries



| M12 PAL-0 | |
|--|--|
| M12 | |
| All MILWAUKEE® M12" batteries | |
| LED | |
| ⁶ 700 / 500 / - / - | |
| 5/10/- | |
| 0.7 | |
| No batteries supplied, No charger supplied, Blister packaging | |
| 4933478226 | |
| | |

M12 AL M12" LED AREA LIGHT

- · TRUEVIEW" high definition lighting
- Five high performance LEDs provide 1000 Lumens of light output replacing 250 W halogen lights
- Highly durable and impact resistant polycarbonate lens to withstand drops up to 2.7 metres
- Integrated magnets, clamping mechanism, and key hole for screws / nails
- provide multiple mounting options for different surfaces

 Most compact flood light designed for the on-the-go needs of service and
- maintenance trades

 IP54 rating, the light is protected from dust and splashing water
- Low battery indicator, light flashes when battery pack is low on charge
 Flexible battery system: works with all MILWAUKEE® M12™ batteries



| | M12 AL-0 |
|--|---|
| System | M12 |
| Battery compatibility | All MILWAUKEE® M12" batteries |
| Bulb type | LED |
| Max. light output High/Medium/Low/Stro (Lumens) | be 1000 / 500 / 250 |
| Max. run time with M12 B4 battery (h) | 3.5 / 7.5 / 15 |
| Weight with battery pack (kg) | 1.3 |
| Kit included | No batteries supplied, No charger supplied Blister packaging |
| Article Number | 4933451394 |

M18 SLED M18" LED SEARCH LIGHT

- TRUEVIEW™ high definition lighting
- Pivoting head provides 1250 Lumens with up to 650 m beam distance
- Privoting read provides 1250 curriers with up to 650 in Deam distance
 4 output modes: Spot, Flood, Spot/Flood, Strobe delivering multiple options in work space illumination
- Spot mode for long range identification: utility pole/high voltage cable inspection, inspection of long runs of conduit, cast or copper pipe, urider ground work, bridge work...
- . Flood mode for illuminating close work spaces
- IP54 rating, the light is protected from dust and splashing water.
- Ergonomic grip with rubber overmould enhances user comfort and grip during use
- . Key hole for hanging function
- ∘ Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 SLED-0 | |
|---|--|--|
| System | M18 | |
| Battery compatibility | All MILWAUKEE® M18** batteries | |
| Bulb type | LED | |
| Max, light output Spot-flood/Flood/Spot/ Strobe (Lumens) | 1250 / 1200 / 600 / 1200 | |
| Max. run time with M18 B5 battery (h) | 4/4/7/5 | |
| Beam distance (m) | 650 | |
| Weight with battery pack (kg) | 1.4 | |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | |
| Article Number | 4933459159 | |
| | | |



HL-SF ALKALINE SPOT FLOOD HEADLAMP

- 450 Lumens of TRUEVIEW* high definition output with 100 m spot beam distance and a wide flood beam
- · Gives users up to 25 hours of run time with five light output modes to optimise run time, beam type, and brightness
- · Supplied with four universal hard hat clips for secure connection to all hardhats
- IP52 rated for water and dust resistance and can withstand up to 2 m
- Equipped with a soft, sweat absorbing microfiber strap and forehead pad
- that provides users with all day comfort when worn on a bare head · Allows users to direct the pivoting light head using seven adjustable
- · Powered by (3) AAA batteries (included)



| | HL-SF |
|---|--------------------------------------|
| Battery compatibility | Alkaline |
| Bulb type | LED |
| Max. ligth output Hybrid Spot/Flood, Flood High/Medium/Low, Spot High (Lumens) | 450 / 350 / 150 / 25 / 350 |
| Max. run time (h) | 2/4/10/26/4 |
| Beam distance (m) | 100 |
| Weight with battery pack (kg) | 0.1 |
| Kit included | 3 x AAA Batteries, Blister packaging |
| Article Number | 4933471388 |

TRUEVEW"

TRUEVEW

1 x L4 B2 Battery pack, USB cable , Blister

L4 HL USB RECHARGEABLE HEADLAMP

- · 475 Lumens Spot & Flood beam with TRUEVIEW" high definition output
- Flood. Spot and Spot/Flood beam options in different output modes for
- optimal brightness and up to 31 hrs. run time
- 4 mounting clips for securing to helmets and adjustable strap with rubber
- Light can be maneuvered in (7) different positions and features 216° tilting
- motion to help users direct light where it's needed most · Removable strap connector allows for handheld use
- . IP53 rating, light is protected from dust and falling water
- · Impact and chemical resistant lens • Fuel gauge allows fast checking of REDLITHIUM™ USB battery charge
- Conveniently charge REDLITHIUM" USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- Jobsite tough micro-USB braided cable with metal ends
- Includes USB cable



Kit included

Article Number

| | L4 HL-201 |
|---|------------------------------|
| System | REDLITHIUM" USB |
| Battery compatibility | REDLITHIUM" USB battery |
| Buib type | LED |
| Max. light output Spot-flood/Flood/Spot/ Strobe (Lumens) | 475 / 25, 150, 300 / 300 / - |
| Max. run time with L4 B2 battery (h) | 2/31,8.5,4.5/4/- |
| Weight with battery pack (kg) | 0.2 |

packaging

4933459443

L4 HL-VIS USB RECHARGEABLE HI-VIS HEADLAMP

- Exceptional hands-free task lighting with safety light provides 600 Lumens of TRUEVIEW" high definition output with spot and flood beam options
- The safety light has steady and blinking options that make you visible up.
- to 400 m from all directions when used with the front headlamp
- . The clip on hard hat light has an elastic strap, silicon grip, includes two
- universal hard hat clips and is compatible with all hardhats Provides all-day run time with five light output modes: Hybrid Spot/Flood,
- Flood High, Flood Medium, Flood Low, Spot High IP53 water and dust resistant and can withstand up to 2 m drops
- Ideal for roadside, tunnel or underground work, spotters, signalers and
- professionals working around moving equipment Conveniently charge REDLITHIUM* USB battery internally with micro-USB
- cable from USB power source or AC outlet (wall plug not included) Fuel gauge allows fast checking of REDLITHIUM" USB battery charge
- · Includes USB cable



| REDLITHIUM | TRU | IEVIEW" |
|------------|-----|---------|
| 035 | | |

| | L4 HL-VIS-201 |
|---|---|
| System | REDLITHIUM** USB |
| Battery compatibility | REDLITHIUM** USB battery |
| Builb type | LED |
| Max. ligth output Hybrid Spot/Flood, Flood High/Medium/Low, Spot High (Lumens) | 600 / 400 / 150 / 25 / 400 |
| Max. run time with L4 B2 battery (h) | 2/4/8/20/4 |
| Weight with battery pack (kg) | 0.2 |
| Kit included | 1 x L4 B2 Battery pack, USB cable , Blister packaging |
| Article Number | 4933471389 |

ISHL

ALKALINE INTRINSICALLY SAFE HEADLAMP

- The intrinsically safe headlamp comes with a certified Zone 0 (category 1) approved ATEX rating
- Exceptional hands-free task lighting provides both Soot and Flood beam options with 310 Lumens of TRUEVIEW" high definition up to
- Designed with safety in mind, it has explicit on-tool intrinsically safe logos and the light strap is designed with a hi-visibility colour combination for easy identification, even at far distances
- Powered by 3 AAA batteries, it provides up to 40 hours of run time and features 5 output modes to manage the brightness and run time
- o IP64 water and dust resistant and can withstand up to 2 m drops Ideal for fire & rescue, oil & gas workers and professionals working

connect straight to a hard hat

around continuous long term gaseous, vaporous and fog/mist areas
Includes rubber strap for hard hat use & nylon strap for bare head use. Also includes DUAL LOCK" adhesive for a strapless option to







Designed with safety in mind, it has explicit on-tool intrinsically safe logos





L4 HLRP USB RECHARGEABLE HARD HAT HEADLAMP

4/6/10/40/8

- 600 Lumens of TRUEVIEW" high definition output
- . Features an ultra-thin light head that provides an unobstructed view with 125° of flood beam coverage
- . Designed with the battery pack in the rear for maximum maneuverability in tight spaces and a balanced design for all-day use
- . Equipped with a sweat absorbing microfiber strap for comfort on bare heads and four included hard hat clips for secure connections on all hardhats
- + It has four light output modes: High, Medium, Low and Eco for 25+ hours of run time to maximise light output or extend run time
- . The clip on hard hat light is IP54 rated for water and dust resistance and can withstand up to 2 m drops
- · Conveniently charge REDUTHIUM" USB battery internally with micro-USB cable from USB power source or AC outlet (wall plug not included)
- * Fuel gauge allows fast checking of REDLITHIUM" USB battery charge
- · Includes USB cable

Battery compatibility

Max. run time (h)

Beam distance (m) Article Number

Max. ligth output Hybrid Spot/Flood, Flood

High/Medium/Low, Spot High (Lumens)

Battery type



TRUEVIEW

| | L4 HLRP-201 |
|--|--|
| ystem | REDLITHIUM™ USB |
| attery compatibility | REDLITHIUM** USB battery |
| ulb type | LED |
| ax. light output Flood Mode High/ ledium/Low/Eco (Lumens) | 600 / 350 / 125 / 25 |
| ax. run time with L4 B2 battery (h) | 2/6/10/27 |
| eight with battery pack (kg) | 0.2 |
| t included | 1 x L4 B2 Battery pack, USB cable , Blister packaging |
| ticle Number | 4933471390 |
| | |

M18 JSR | M18" JOBSITE RADIO

- High performance audio system AM/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- Dual speaker with passive radiators deliver loud, clear sound with deep, accurate bass
- Customisable equalizer for enhanced sound quality and 10-station preset
- Shock absorbing end caps and metal speaker grills protect from drops, water and debris on the jobsite
- · Integrated handles allow for easy transport and storage
- Powered by MILWAUKEE® M18™ batteries or AC outlet. Up to 12 hours of runtime with an M18™ REDLITHIUM™ 5.0 Ah battery pack
- Weather sealed device compartment protects mobile devices
- Protected 2.1 A USB power outlet charges electronic devices in both AC and DC mode



| M18 JSR-0 |
|--|
| 522 - 1629 |
| 87.5 - 108 |
| 402 x 197 x 197 |
| 4.9 |
| No batteries supplied, No charger supplied, No kitbox or bag supplied |
| 4933451250 |
| |

M18 RC | M18™ JOBSITE RADIO CHARGER WITH BLUETOOTH®

- Built in charger function allows for quick, convenient charging of any M18[™] battery or electronic devices via USB port
- Digital Bluetooth® receiver: play music up to 30 m away from your smartphone, computer, or tablet
- AC/DC versatility: powered by MILWAUKEE® M18™ batteries, or 230 V mains supply
- Exclusive AM/FM tuner with digital processor delivers highest reception accuracy and signal clarity
- Premium speaker and 40 W amplifier produce rich, full sound
- Weather sealed auxiliary compartment protects Mp3 players and other audio devices
- Reinforced roll cage and metal handles protects against abusive jobsite conditions
- Customisable equalizer and 10-station preset
- Protected 2.1 Amp USB power outlet charges devices in both AC and DC mode
- Supplied with auxiliary input cord, 2 x AAA batteries. MILWAUKEE[®] batteries sold separately
- ∘ Flexible battery system: works with all MILWAUKEE® M18™ batteries



| | M18 RC-0 |
|--------------------|--|
| Dimensions (mm) | 300 x 307 x 370 |
| Speaker output (W) | 40 |
| Weight (kg) | 7.7 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933446639 |

M12-18 JSSP M12" - M18" BLUETOOTH® SPEAKER

- Advanced technology Bluetooth® jobsite speaker
- Bluetooth® wireless range of up to 30 m
- Flexible battery system: works with all MILWAUKEE® M12™ & M18™ batteries
- IP54 rated, water and debris resistant to withstand tough conditions on and off the jobsite
- · Loud, clear sounds at all volumes
- 2.1A USB charger, charges phones, tablets and media players
- · Premium speaker with bass port



| | M12-18 JSSP-0 |
|-------------------------------|--|
| Dimensions (mm) | 360 x 165 x 165 |
| Speaker output (W) | 40 |
| Weight with battery pack (kg) | 2.3 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933459275 |

M12

M18

M18

M18



M18 FMCS66

MIS FLIEL

M18 FUEL™ 66 MM METAL CIRCULAR SAW

- First 18V cordless metal circular saw with 66 mm cutting depth and 1800 W corded performance
- Faster cutting speed compared to corded unit
- Shoe designed to connect directly on MILWAUKEE[®] guide rail (sold separately). This allows the user to make straight and accurate cuts with minimum setup time
- Performance light indicates when the device is pushed to hard
- Electric break stops blade in under 1 sec
- Large metal chip collector captures debris produced while cutting and provides needed visibility
- Dry-cutting technology provides fast, clean and burr-free metal
- Dual-action trigger prevents any accidental start up
- Tool-free cutting depth adjustment and plunge lever for fast and effective plunge cuts
- Exclusive chip-release shield latch for fast waste disposal and blade
- Integrates three MILWAUKEE*-exclusive technologies the POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18st batteries



device is pushed to hard



debris produced while cutting and



| | M18 FMCS66-0C | M18 FMCS66-121C |
|-------------------------------|--|--|
| No load speed (rpm) | 4000 | 4000 |
| Blade diameter (mm) | 203 | 203 |
| Bore size (mm) | 15.87 | 15.87 |
| Max. cutting depth (mm) | 66 | 66 |
| Weight with battery pack (kg) | 14.1 | 7.5 |
| Kit included | No batteries supplied, No charger supplied, Kitbox | 1 x M18 HB12 Battery pack M12-18 FC Charger, Kittox |

4933472110

| | 1400, 1400 MM GUIDE RAI PLIED WITH CARRY BAG |
|--------------------------|---|
| Article Number 493245126 | Number 4932451 |

M18 FMCS M18 FUEL" 57 MM METAL CIRCULAR SAW

- . Brushless POWERSTATE" motor for fast cutting, longest tool life and up to 370 cuts in 3/4" EMT
- REDLINK PLUSⁿ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Cold cuts reduces sparks for increased jobsite safety
- Tool-free depth adjustment, quickly and easily adjusts cutting depth from
- · Compact and light weight design for most comfortable use
- · Integrated rafter hook for easy storage between uses
- On board allen key storage for easy access and preventing losing the key
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- · Fuel gauge displays remaining charge
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- . Supplied with 150 mm 34 teeth metal cutting blade

M18 FUEL

| | M18 FMCS-0X | M18 FMCS-502X |
|-------------------------------|---|--|
| No load speed (rpm) | 3900 | 3900 |
| Blade diameter (mm) | 150 | 150 |
| Bore size (mm) | 20 | 20 |
| Max. cutting depth (mm) | 57 | 57 |
| Weight with battery pack (kg) | - | 2.8 |
| Kit included | No batteries supplied, No charger supplied, HD Box | 2 x M18 B5 Battery packs M12-18 FC Charger, HD Box |
| Article Number | 4933459192 | 4933459193 |
| | | |







M18 FDG | M18 FUEL" DIE GRINDER

- * Brushless POWERSTATE™ motor with corded performance, up to 20 min of grinding on a 5.0 Ah battery and up to 10x more tool life
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- · REDLITHIUM" battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Universal reception to fit both, 6 and 8 mm accessories
- Slim handle design
- Removable dust screen to prevent debris entrance, prolonging motor life
- · Rubber front provides most comfortable handling
- · Line-lock out function to prevent automatic start up
- Fuel gauge displays remaining charge
- + Flexible battery system: works with all MILWAUKEE® M18™ batteries Supplied with 6 mm & 8 mm collet, 15 mm & 17 mm open ended spanner,
- 2 x dust screens

| | M18 FDG-0X | M18 FDG-502X |
|--|---|---|
| No load speed (rpm) | 27,000 | 27,000 |
| Collet capacity (mm) | 6/8 | 6/8 |
| Max. grinding accessories diameter (mm) | 50 | 50 |
| Weight with battery pack (kg) | D*51 | 2.1 |
| Kit included | No batteries supplied, No charger supplied, HD Box | 2 x M18 B5 Battery packs, M12-18 FC Charger, HD Box |
| Article Number | 4933459190 | 4933459107 |
| | | |



M18 FUEL

- · Brushless POWERSTATE" motor provides corded drilling performance with strongest magnet holding force on 1/4" steel and 40 x 18 mm holes per
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- · AUTOSTOP" lift-off detection: Detects excess rotation and automatically cuts power to the drill for best user protection
- Self-powered permanent magnet with 8,890 N of holding force prevents accidental magnet deactivation for improved user protection and easy
- +2 speed gear box for optimised drilling speed with 400 and 690 rpm's when using annual cutters or twist drill bits
- . Maximum drilling capacity of 38 mm with use of annual cutters and 13 mm straight shank twist drill bits
- . Keyless 19 mm Weldon reception for fast and easy accessory change



| | M18 FMDP-0C | M18 FMDP-502C |
|--|--|---|
| No load speed (rpm) | 400 / 690 | 400 / 690 |
| Max, diameter broaching capacity (mm) | 38 | 38 |
| Max, depth broaching capacity (mm) | 50 | 50 |
| Max, drilling solid bit (mm) | 13 | 13 |
| Magn. holding power (at drill point pressure) (N) | 8890 | 8890 |
| Strake length (mm) | 146 | 146 |
| Weight with battery pack (kg) | - | 13.0 |
| Kit included | No batteries supplied, No charger supplied, Kitbox | 2 x M18 B5 Battery packs, M12-18 FC Charger, Kitbox |
| Article Number | 4933451636 | 4933451012 |

M18 BMS12 M18" METAL SHEAR

- Accurate cuts with maximum cutting depth of 1,2 mm in steel
- Unique 360° tool-free rotating head with 12 locking positions to access
- tight spaces and increasing user comfort REDLINK™ overload protection electronics in tool and battery pack deliver
- best in class system durability
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability
- . In-Line wrist design for increased control during cutting
- Variable speed trigger for extra control during cutting
- . Belt clip for secure mobility
- REDLITHIUM™ battery pack provides superior pack construction. electronics and fade-free performance to deliver more run time and more work over pack life
- Flexible battery system: works with all MILWAUKEE® M18th batteries



| | M18 BMS12-0 |
|--------------------------------------|--|
| No load speed (rpm) | 0 - 2500 |
| Max, cutting capacity steel (mm) | 1,2 |
| Max. cutting capacity aluminium (mm) | 2.0 |
| Minimum cutting radius (mm) | 180 |
| Weight with battery pack (kg) | 2.3 |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied |
| Article Number | 4933447925 |



M18 FTS210

MIS FLIEL

Anti-kick-back pawls stoos material

M18 FUEL™ ONE-KEY™ TABLE SAW

- o The ONE-KEY" M18 FUEL" table saw delivers the power to rip cut at the same feed rate of an equivalent AC saw, with the ability to cut 190 m of 19 mm OSB board on one 12.0 Ah battery charge
- Next generation POWERSTATE" brushless motor, REDLINK PLUS" electronics and REDLITHIUM" HIGH OUTPUT" 12.0 Ah battery pack deliver superior performance, durability and run time in high demand
- Rack and pinion sliding fence allows the fence to be adjusted. accurately and easily from the front of the saw giving 622 mm of rip
- o 210 mm blade
- o ONE-KEY" to
- Quick change adjust the rivi throat plate
- Integrated car jobsite
- On board store
- Vacuum adapti

No batteries supplied, No. 1 x M18 HB12 Battery pack.

kitbox or bag supplied

charger supplied. No kitbox M12-18 FC Charger, No.

| allows 63 of tracking platform th | mm depth of cut at & security offers a c at supports both loc | 90 degrees loud-based inventory ation tracking and theft the user to remove and | | | | |
|---|---|---|------|----------|-----|--|
| | d guard without the | | • | | • | |
| | | tation on and off the | 1716 | Market . | . 0 | |
| | table saw attachmer d fits directly to all fv | | A | | | |
| 1.28 | 118 FTS210-0 | M18 FTS210-121B | | 96 | 曹 | |
| 677 | 22 A 1 (22) (2) | THE STATE OF T | | | | |
| | 300 | 6300 | | | | |
| | | 210 | | | | |

| 210 X 30 MM 24 CIRCULAR SAW | |
|--------------------------------|------------|
| 1.9 MM CUTTING | |
| Article Number | 4932478095 |



ONE THE DIGITAL JOSSITE:





On fence push stick storage

M18 FMS305

M18 FUEL™ ONE-KEY™ 305 MM MITRE SAW

- Delivers the power to cut at the same rate of an equivalent AC 305 mm saw, with the ability to cut up to 500 pieces of 78 mm pine base board on one 12.0 Ah battery charge
- Next generation POWERSTATE" brushless motor, REDLINK PLUS" electronics and REDLITHIUM" HIGH OUTPUT" 12.0 Ah battery pack deliver superior performance, durability and run time in high demand applications
- · Large sliding fences gives maximum support to the material being
- cut providing stability and accuracy

 Trenching stop with depth adjustment allows the user to make trenching and rebate cuts

| | M18 FMS305-0 | M18 FMS305-121 |
|--|--|---|
| No load speed (rpm) | 3600 | 3600 |
| Blade diameter (mm) | 305 | 305 |
| Bevel capacity left (*) | 48 | 48 |
| Bevel capacity right (*) | 48 | 48 |
| Mitre capacity left (") | 56 | 55 |
| Mitre capacity right (*) | 60 | 60 |
| Max. cutting capacity L45° mitre / L45° bevel (mm) | 235 x 65 | 235 x 65 |
| Max. cutting capacity R45° mitre / R45° bevel [mm] | 235 x 40 | 235 x 40 |
| Max, cutting capacity 45° mitre/ 90° bevel (mm) | 235 x 97 | 235 x 97 |
| Max. cutting capacity 90° mitre/ 45° bevel (mm) | 343 x 65 | 343 x 65 |
| Max. cutting capacity 90° mitre/ 90° bewel (mm) | 343 x 97 | 343 x 97 |
| Max. cutting capacity at fence 90° mitre / 90° bevel (mm) | 173 x 28 | 173 x 28 |
| Bore size (mm) | 30 | 30 |
| Weight with battery pack (kg) | 77.5 | 22.5 |
| Sit included | No batteries sup- plied, No charger supplied, No kittos or bag supplied | 1 x M18 HB12 Battery pack, M12-18 FC Charger, No kitbox or bag supplied |
| Article Number | 4933471205 | 4933471122 |



305 X 30 MM 60 TOOTH CIRCULAR SAW BLADE WITH 3.0 MM CUTTING WIDTH 4932471321

Article Number



M18 FLIEL

Large sliding fences



Trenching stop with depth adjustment



M18 FUEL

4933451729

TSS 1000 TABLE SAW STAND

. Light weight of only 6.6 kg - easy to transport onto the job site

or bag supplied

. Will hold up to 82 kg

Blade diameter (mm Bevel capacity (") Rip capacity (mm) Weight with battery pack (kg)

Kit included

- · Quick release bracket to hold the saw firmly in place
- . One point leg adjustment for leveling on uneven ground Comfortable work height at 559 mm
- . To be used with M18 FTS210 FUEL" ONE-KEY" table saw



| | TSS 1000 | |
|--------------------|---------------------------|--|
| Height (mm) | 559 | |
| Bearing force (kg) | 82 | |
| Weight (kg) | 6.6 | |
| Supplied in | No kitbox or bag supplied | |
| Article Number | 4933464227 | |

M18 FMS254 M18 FUEL" 254 MM MITRE SAW

- · Brushless POWERSTATE" motor for up to 2x longer motor life and up to 25% more power
- * REDLINK PLUS* intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load
- REDLITHIUM" battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 254 mm blade delivers large and accurate cut capacities
- . Quick release bevel setting with detents allows the simple setting of bevel angles to the left and right
- * Large sliding fences gives maximum support to the material being cut providing stability and accuracy
- . Trenching stop with depth adjustment allows the user to make trenching and rebate cuts
- Up to 307 cuts in 38 mm x 89 mm soft wood with a 9.0 Ah battery gives the ability to work a full day without recharging the battery
- · Integrated carry handle allows easy transportation on and off the jobsite - Steel detent plate with preset angles gives repeatable accurate cuts
- LED light to illuminate the work piece and cut line in low light conditions



| | M18 FMS254-0 | |
|---|---|--|
| No load speed (rpm) | 4000 | |
| Blade diameter (mm) | 254 | |
| Bevel capacity left (°) | 48 | |
| Bevel capacity right (°) | 48 | |
| Mitre capacity left (") | 50 | |
| Mitre capacity right (") | 60 | |
| Max. cutting capacity 45° mitre/ 45° bevel (mm) | 205.23 x 51.3 | |
| Max. cutting capacity 45° mitre/ 90° bevel (mm) | 205.23 x 91.2 | |
| Max. cutting capacity 90° mitre/ 45° bevel (mm) | 289.3 x 51.3 | |
| Max. cutting capacity 90° mitre/ 90° bevel (mm) | 289.3 x 91.2 | |
| Bore size (mm) | 30 | |
| Weight with battery pack (kg) | 20.0 | |
| Kit included | No batteries supplied, No charger supplied, No kitbox or bag supplied | |

Article Number