



## Technical data

<b>Degree of protection</b>	IP20
<b>Resistance to impact</b>	IK07
<b>Glow wire resistance</b>	650 °C



## Enclosures technical specifications

<b>Degree of protection</b>	IP40 / IP55
<b>Resistance to impact</b>	IK07
<b>Glow wire resistance</b>	650 °C
<b>Mechanisms technical specifications</b>	
<b>Rated voltage</b>	250 V
<b>Rated current</b>	10A / 16A / 20A
(20 A including fluorescent loads).	
<b>Entry section</b>	4 mm <sup>2</sup>



<b>Degree of protection</b>	IP65-IP67*
<b>Resistance to impact</b>	IK07
<b>Glow wire resistance</b>	650 °C
<b>Ambient temperature range</b>	-25 °C / +40 °C
<b>Maximum operating voltage</b>	1000 V AC / 1500 V DC
<b>Double insulation</b>	Class II
* Except EP048, EP088 and EX088 (IP54) references	



<b>Degree of protection</b>	IP33*
<b>Resistance to impact</b>	IK07*
<b>Glow wire resistance</b>	650 °C
<b>Ambient temperature range</b>	-5 °C / +40 °C
<b>Maximum operating voltage</b>	1000 V AC / 1500 V DC
<b>Double insulation</b>	Class II
*Except reference D88	



<b>Glow wire resistance</b>	850 °C
<b>Ambient temperature range</b>	-5 °C / +40 °C
<b>Maximum operating voltage</b>	400 V